GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE **NEW DELHI- 110001**

No. F.6/DFS/MS/School/2021/NDZ/ 58 2

Dated: 5 8 21

FIRE SAFETY CERTIFICATE

Certified that the Sanatan Dharam Senior Sec. School at Bhola Nath Nagar, Shahdara, Delhi-110032, comprised of ground plus one upper floor owned/occupied by Sanatan Dharam Senior Sec. School was issued FSC vide letter No. F.6/DFS/MS/School/2018/NDZ/395 dated 12/03/2018. The school building have complied with the fire prevention and fire safety requirements in accordance with the circular No. 262-362 dated 17/01/2005 issued by Director of Education and verified by the officer concerned of Fire Service on 29/07/2021 in the presence of Sh. Dharamveer, Principal of the school and that the building is fit for occupancy class "B" 'Educational Building' with effect from .5.7.8./.2./... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 & also conditions printed overleaf.

Issued on.....at New Delhi by

(Dr. S. K. Tomar) Dy. Chief Fire Officer

To,

The Principal, Sanatan Dharam Senior Sec. School, Bhola Nath Nagar, Shahdara, Delhi-110032

Copy:-

The Joint Director of Education (Land & Estate), Directorate of Education, Lucknow Road, Delhi-110054

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate_may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry

	INSPEC	TION REPORT	The spile of			
1.						
2.	Building is comprised of	: Ground plus one u				
1 5	3. Type of Occupancy : Educational					
4.		: Renewal				
5.	Details of Previous NOC letter	: F.6/DFS/MS/Scho dated-12/03/2018	ol/2018/NDZ/3	95		
6.	6. Fire Safety direction letter No. : old requirement (Circular No. 262-362 dated 17/01/05)					
7.	Date of Inspection	: 29/07/2021				
8.	8. Name of the Inspecting officers : ADO Nagender Singh					
	Name and designation of Officer					
	from the building side	: Sh. Dharamveer, Principal				
10.		: 1977				
11.	Applicant's email ID	: schoolsd@ymail	dated- 23/07/20	21		
Sr.	Minimum Standards on Fire	Circular	Provided at	Remarks		
No.	Prevention and Fire Safety U/R33	Requirement	Site	MR/NMR		
01	Access to Building					
	Road width	6 m	08 m	MR		
		N/A	N/A	N/A		
	Gate width	N/A	N/A	N/A		
	Width of internal road					
02	Number, Width, Type and Arrangeme	ent of Exits				
	a. Number of Staircases					
	Upper floor	2 nos.	2 nos.	MR		
	Basement	N/A	N/A	N/A		
	B. Width of Staircases	150 m	1.10 0-	MD(accented		
	Upper floor	1.50 m	1.10 m & 0.90 m	MR(accepted earlier)		
	Basement	N/A	N/A	N/A		
	c. Protection of Exits	14/11	1,1/11	14/14		
	Fire check door	N/A	N/A	N/A		
	Pressurization	N/A	N/A	N/A		
	d. No. of Continuous Staircases to	1 no.	1 no.	MR		
	Terrace	1				
	e. Width of Corridor	1.50 m	1.50 m	MR		
	f. Door Size	1 m	1 m	MR		
. 03	Compartmentation.					
	Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts	N/A	N/A	N/A		

	B. Width of Staircases		1.0			
		1.50 m	1.10 m &	MR(accepted		
	Upper floorBasement		0.90 m	earlier)		
		N/A	N/A	N/A		
	c. Protection of Exits	* 35				
	Fire check door	N/A	N/A	N/A		
	 Pressurization 	N/A	N/A	N/A		
	d. No. of Continuous Staircases to Terrace	1 no.	1 no.	MR		
	e. Width of Corridor	1.50 m	1.50 m	MR		
	f. Door Size	1 m	1 m	MR		
03	Compartmentation.					
	Fire check door	N/A	N/A	N/A		
	 Sealing of electrical shafts 	N/A	N/A	N/A		
	 Fire rating of shaft door 	N/A	N/A	N/A		
	Water curtain	N/A	N/A	N/A		
	Fire dampers	N/A	N/A	N/A		
04	Smoke Management System.					
	Basement	N/A	N/A	N/A		
	Upper floor	N/A	N/A	N/A		
05.	Fire Extinguishers					
	Total numbers	4 nos.	04 nos.	MR		
	• Types	ABC/CO ₂	ABC/CO ₂	MR		
	IS marking	ISI marked	ISI marked	MR		

N114

		01 no.	01 no.	MR		
	Total numbers on each floor	30 m	30 m	MR		
	Length of hose reel hose	5 mm	5 mm	MR		
	Nozzle diameter		J 11111			
7	Automatic Fire Detection and Alarming System	11.		DI/A		
	Type of detectors	N/A	N/A	N/A		
	Location of main panel	N/A	N/A	N/A		
	Location of repeater panel	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooter	N/A	N/A	N/A		
08	MOEFA	N/A	Provided	MR		
09	Public Address System.	N/A	Provided	MR		
10	Automatic Sprinkler System.					
10		N/A	N/A	N/A		
	Basement	N/A	N/A	N/A		
	• upper floor	N/A N/A	N/A	N/A		
	sprinkler above false ceiling	IN/A	111.4			
11	Internal Hydrants	NI/A	N/A	N/A		
2	size of riser/down-comer	N/A	N/A N/A	N/A		
	Number of hydrants per floor	N/A N/A	N/A	N/A		
	Hose box	N/A	14/11			
12	Yard Hydrants.	1		T >1/A		
	Total number of hydrants	N/A	N/A	N/A		
	Hose box	N/A	N/A	N/A		
13	Pumping Arrangements.					
	> Ground Level					
		N/A	N/A	N/A		
	Discharge of main pump	N/A	N/A	N/A		
	Head of main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	Jockey pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A	N/A	N/A		
	Standby pump out put	N/A	N/A	N/A		
	Standby pump head	N/A	N/A	N/A		
	Auto starting /manual stopping	N/A	N/A	N/A		
	Pump house access Terrace Level		*			
		220 LPM	220 LPM	MR		
	 Discharge of pump 	40 m	40 m	MR		
	 Head of the pump 	N/A	N/A	N/A		
	 Power supply 	N/A N/A	N/A	N/A		
	Auto starting of pump Auto starting of pump Auto starting of pump	11/71				
14	NI/A NI/A					
	 Underground tank capacity 	N/A	N/A N/A	N/A		
	 Draw-off connection 	N/A	N/A N/A	N/A		
	• Fire service inlet	N/A	N/A N/A	N/A		
	 Access to tank 	N/A	2500 Liters	MR		
	 Overhead tank capacity 	2500 Liters				
1	5 Exit Signage.	N/A	N/A	N/A		

16	Provision of Lifts.			
	Pressurization of lift shaft	N/A	N/A	N/A
	Pressurization of lift lobby	N/A	N/A	N/A
	Communication in lift car	N/A	N/A	N/A
	Firemen's grounding switch	N/A	N/A	N/A
	Lift signage	N/A	N/A	N/A
17	Standby Power Supply	N/A	N/A	N/A
18	Refuge Area.			See The See
	Total area	N/A	N/A	N/A
	• Location	N/A	N/A	N/A
19	Fire Control Room			
2	Detector system panel	N/A	N/A	N/A
	Flow switch panel	N/A	N/A	N/A
	PA system panel	N/A	N/A	N/A
	Battery backup	N/A	N/A	N/A
	Building floor plans	N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of Special Risks, if Any:	N/A	N/A	N/A

The Fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view of the compliance of the minimum standards of fire prevention and fire safety measures required as per circular No.262-362 dated 17.01.2005 issued by Director of Education, it is recommended to renew FSC under rule 37 of the Delhi Fire Service Rules, 2010.

F. G. p'. Dy. CFO (NDZ)

ADO(Shan) FT letter is placed for signatures please

ADOC M. Silell