, us

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F6/DFS/MS/GH/2021/ 3 08

FIRE SAFETY CERTIFICATE

Certified that the M/s Hotel SSENSSE Guest House, Plot no.28, Pocket.5-A, Sector-25, Rohini, Delhi-110085, comprised of Stilt and 04 upper floors, Guest House building having total 34 Guest rooms. The building was inspected by the officer concerned of this department on 01.07.2021 in the presence of Mr. lagdish Kumar (Owner) of the guest house and found that the building have complied with the fire prevention and fire safety requirements in accordance with rules 33 of the Delhi Fire Service Rules, 2010 and observed that the building is fit for occupancy class 'Residential (Guest House) Building with effect from ... 1218.1.21....... for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed below

Issued on 12/8/21... at New Delhi by

Ph: 011-23414000

Copy to:-

- 1. The Dy. Health Officer, North MCD, Sec-5, Rohini Zone, Delhi-110085.
- 2. M/s Hotel SSENSSE Guest House, Plot no.28, Pocket.5-A, Sector-25, Rohini, Delhi-110085. Conditions for the validity of Fire Safety Certificate:
- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wos/wcm/connect/doit_fire/FIRE/Home/Fire+Safety+Acts+and+Rules/ http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms

: Hotel SSENSSE Guest House, Plot no.28, Pocket.5-A, Sector-25, Rohini, Delhi-85. Type of Occupancy : Residential (Guest House) (still + 04 upper floors) 3. Type of Case : New Case (34 rooms) 4. Details of Previous NOC : Nil 5. Fire Safety directives letter No : Nil 6. Date of inspection : 01.07.2021 7. Name of Inspecting Officer : A. K. Sharma, ADO (Rohini) & D.B Mukherjee, DO (NW) 8. Name and designation of officers From the building side : Mr. Jagdish Kumar (Owner) 9. Year of Construction : 2014 10. Applicant's letter No. : Online e-mail dated 30.07.21 Provided at site Minimum Standards on fire prevention and BBL/NBC Remarks fire safety U/R 33 Requirement MR/NMR 1. Access to building Road width 12m 12m MR Gate width 4.5m Directly accessible MR Width of internal road -NA--NA--NA-Number, Width, Type & Arrangement of Exits 2. d. Number of staircases Upper Floors 02 02 MR Basements -NA--NA--NAe. Width of staircases Upper Floor 1.5m & 1.25 m 1.55 & 1.25m MR Basements -NA--NA--NAf. Protection of exits Fire check door -NA--NA--NA-Pressurization -NA--NA--NAd. No. of continuous staircases to terrace 02 02 MR e. Width of Corridor 1.8 mtr Provided MR Door Size 1.0 mtr Provided MR 3. Compartmentation Fire check door -NA--NA--NA-Sealing of electrical shafts -NA--NA--NA-Fire Rating of shaft door -NA--NA--NA-Water Curtain -NA--NA--NA-Fire Dampers -NA--NA--NA-4. Smoke Management System Basements -NA--NA-30 a/c per hour Upper floors 12 a/c per hour Natural ventilation MR 5. Fire Extinguishers Total numbers 10 No's 10 No's MR Types ABC/W. CO₂/CO₂ ABC/W. CO₂/CO₂ MR ISI marked IS marking Yes MR 6. First-Aid Hose Reels Total numbers on each floor One Provided MR Length of hose reel hose Provided MR 30m Nozzle diameter 5mm Provided MR 7. Automatic fire detection and alarming system Type of detectors CO Provided MR Location of Main Panel -NA--NA--NA-Location of Repeater Panel -NA--NA--NA-Alternate source of power -NA--NA--NA-

INSPECTION REPORT

Name& address of the building

	Hooters' Location	-NA-	-NA-	-NA-
8.	MOEFA	Required	Provided	MR
9.	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System			
	Basement	-NA-	-NA-	-NA-
	 Ground Floor 	Required at Stilt	Provided	MR
	 Sprinkler above false ceiling 	-NA-	-NA-	-NA-
11.	Internal Hydrants			
	Size of riser/down-comer	100 mm	Provided	MR
	 Number of hydrants per floor 	01	Provided	MR
	Hose Box	01	Provided	MR
12.	Yard Hydrants			
	 Total number of hydrants 	-NA-	-NA-	-NA-
	Hose Box	-NA-	-NA-	-NA-
13.	Pumping Arrangements			
	Ground Level			* 1.
	Discharge of main Pump	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Head of Main pump	-NA-	-NA-	-NA-
	Number of main pumps	-NA-	-NA-	-NA-
	Jockey Pump out putJockey pump head	-NA-	-NA-	-NA-
	Land Land	-NA-	-NA-	-NA-
	Standby Pump out putStandby Pump Head	-NA-	-NA-	-NA-
	➤ Auto Starting/Manual Stopping	-NA-	-NA-	-NA-
	> Pump House Access	-NA-	-NA-	
	Terrace level	-14/1-	-INA-	-NA-
	Discharge of pump	900LPM	900LPM	MD
	➤ Head of the pump	40m	40m	MR
	Power Supply	Required	Provided	MR
	Auto Starting of pump	Required	Provided	MR
14.	Captive Water Storage for fire fighting	Required	Flovided	MR
	Underground tank capacity	-NA-	-NA-	-NA-
	> Draw-off connection	-NA-	-NA-	-NA-
	Fire service inlet	-NA-	-NA-	NIA
	Access to tank	-NA-	-NA-	-NA-
	Overhead Tank capacity	15,000 ltr.	15,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
6.	Provision of Lifts.	1	1101144	IVIIC
	Pressurization of Lift Shaft	-NA-	-NA-	-NA-
	 Pressurization of Lift lobby 	-NA-	-NA-	-NA-
	Communication In lift Car	-NA-	-NA-	-NA-
	 Fireman's Grounding Switch 	-NA-	-NA-	-NA-
	• Lift Signage	-NA-	-NA-	-NA-
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area.	1,000	. 1071000	TATIX
	> Total Area	-NA-	-NA-	-NA-
	> Location	-NA-	-NA-	-NA-
9.	Fire Control Room		A 12 A	147.
	Detector System Panel	-NA-	-NA-	-NA-
	Flow Switch Panel	-NA-	-NA-	-NA-
		4 44 4	-1 ALX-	-1NH-
	PA System Panel	NIA	NIA	DT A
	PA System PanelBattery backup	-NA-	-NA-	-NA-

Signature of the Inspecting Office

Name: - D.B Mukherjee Designation: DO/NW

Name: - Ajay Kumar Sharma

Designation:- ADO/Rohini

As oldsensed wester ADS
Rohimi Mechanical Newhitakan
co provided