GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/2021/SZ/ 40

Dated: 18/08/2021

FIRE SAFETY CERTIFICATE

Issued 18/08 /2021 at New Delhi by

Copy to: -

1. Sh. Maneesh Raj, AGM/ Security, M/s Punjab National Bank, Security Division, Head Office, Plot No 4, Sector 10, Dwarka, New Delhi 110075

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 2. The Building sanctioning authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry." The form is available on www.dfs.delhigovt.nic.in

1	Name & Address of the Building	M/s Punjab National Bank, No.7, Bhikaji Cama Place,				
2	Type of Occupancy		New Delhi-110025 Business Occupancy (Office Complex)			
3	Building Comprised of	Basement , Lower ground, Upper ground + 08 upper floors				
4	Type of Case	Renewal				
5	Details of Previous NOC	F6/DFS/MS/2017/SZ/902 dated 23/06/2017				
6	Fire Safety Directives Letter No		F.6/DFS/MS/BP/85/1009 dated 02/12/1985			
7	Date of Inspection	29/07/2021				
8	Name of the Inspecting Officers	DO, Sh. S. K. Dua & ADO, Sh. Rajesh Kumar				
9	Name & Designation of Officers from the building side	Mr. Satyendra Sharma (Sr. Manager Fire & Safety)				
10	Year of construction	1985				
11	Applicant letter No.	Email dated 16/0	7/2021			
S. No	Minimum standards on Fire Prevention and Fire Safety U/R 33	Requirements/ Existing System	Provided at Site	Remarks MR/NMR		
1	Access to Building.			I.		
	Road width	9m	9m Provided	MR		
	Gate width	-NA-	-NA-	-NA-		
	Width of internal road	6m	6m on two side	MR(Old Case)		
2	Number, width, type & arrangement	of exits.				
	a) Number of Staircase					
	> Upper floors.	03 nos	LGF to UGF=03nos, UGF to 1 st Floor=05nos, 1 st Floor to Terrace =03nos	MR		
	Basement floor.	02nos	02nos	MR		
	b) Width of Staircase					
	Upper floor	1.5m	1.35m (each)	MR(old case)		
	Basement floor	1.5m	1.6 m & 1.35 m	MR		
	c) Protection of exits					
	Fire check door	Required	Provided	MR		
	Pressurization	-NA-	-NA-	-NA-		
	d)No. of continuous staircase to terrace	03nos	03nos	С		
	e)Width of corridor	-NA-	-NA-	-NA-		
	f) Door size	1m	1m	MR		
3	Compartmentation.					
	Fire check door.	Required	Provided	MR		
	 Sealing of electrical shafts. 	Required	Provided	MR		
	 Fire rating of shaft door. 	-NA-	-NA-	-NA-		
	• Water curtain	-NA-	-NA-	-NA-		
	• Fire dampers.	-NA-	-NA-	-NA-		
1	C-1-M	Management system.				
4.	Smoke Management system.					
4.	Basement	30ACPH	Exhaust Fans provided	MR		

5	Fire Extinguishers.		18.43	
	Total numbers	60nos	102nos	MD
	• Types	W.CO ₂ & CO ₂	ABC, CO ₂ , WCO ₂	MR
	ISI Marking	ISI marked	Provided	MR
6	First Aid Hose Reels.		TTOVIGCG	MR
	 Total numbers on each floor 	2nos	Provided	MR
	 Length of hose-reel hose. 	30m	30 m	MR
	Nozzle Diameter	5 mm	5 mm	MR
7	Automatic fire detection & alarming	system.		IVIIC
	 Type of detectors 	Heat &	Heat & Smoke	MR
	 Location of Main Panel 	Smoke		1711
	 Location of Repeater Panel 	FCR	Ground floor	MR
	 Alternate source of power 	-NA-	-NA-	-NA-
	 Hooter's location 	Required	Provided	MR
		Each floor	Each floor	MR
	MOEFA	Required	Provided	MR
	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			TVIIC
	Basement	Required	Provided	1.00
	 Upper floors 	-NA-	-NA-	MR
	 Sprinkler above false ceiling 	-NA-	-NA-	-NA-
11.	Internal Hydrants.	1471	-IVA-	-NA-
	Size of Riser / Down-comer	150 mm	Provided	MD
	 Number of Hydrant per floor 	02nos	02nos	MR
12	Hose box.	02nos	02nos	MR MR
12.	Yard Hydrants			1111
	Total number of hydrantsHose box	02nos	04nos	MR
13		02nos	04nos	MR
13.	Pumping arrangements.			
13.	Ground Level Discharge of main pump			
	Discharge of main pump.Head of main pump.	28001pm	2800lpm	MR
	Number of main pumps.	75m	80m	MR
	Jockey Pump output.	1nos	1nos	MR
	Jockey Pump head.	1801pm	1801pm	MR
	Standby Pump output.	75m	80m	MR
	Standby Pump head.	Required	Required	MR
	Auto Starting/Manual	75m	80m	MR
	Stopping.	Required	Provided	MR
	Pump house access Terrace Level	Required	Provided	MR
	TOTTUCE LEVEL			
	Discharge of pump.Head of pump.	-NA-	-NA-	-NA-
	Power supply.	-NA-	-NA-	··NA··
4-		-NA-	-NA-	-NA-
14.	Auto starting of pump. Captive water storage for firefighting.		-NA-	-NA-
1	Underground tank capacity.			
	> Draw-off connection.	2,00,000ltr	2,00,000ltr	MR
	Fire Service Inlet.	Required	Provided	MR
	Aggregate to 1	Required	Dravidad	3 (7)

9	 Overhead tank capacity. 	-NA-	-NA-	-NA-		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.					
	Pressurization of lift shaft.	Required	Provided	MR		
	 Pressurization of lift lobby. 	-NA-	-NA-	-NA-		
	Communication in lift car.Fireman's switch.	Required	Provided	MR		
		Required	Provided	MR		
	Lift signage.	Required	Provided	MR		
17	Standby Power Supply	Required	Provided	MR		
18.	Refuge Area					
	Total area	-NA-	-NA-	-NA-		
	• Location	-NA-	-NA-	-NA-		
19.	Fire Control Room.					
	Detector System Panel.Flow Switch Panel.PA system Panel.	Required	Provided	MR		
		-NA-	-NA-	-NA-		
		Required	Provided	MR		
	Battery backup Building floor plan	Required	Provided	MR		
	Building floor plan	Required	Provided	MR		
20.	Special Fire Protection System for the Protection of special Risk, if any.	Required	Novac System provided for HT, LT Panel and transformer	MR		

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Further, the party has complied all the observation / Shortcoming already issued & communicated by this department vide letter of even no 1955 dated 04/08/2020

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/2017/SZ/902 dated 23/06/2017, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: S. K. Dua

Designation: DO (SD)

Signature of the Inspection Officer

Name Sh. Rajesh Kumar Designation: ADO (BCP)

DCFO (SZ)

AD.

Los