635

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/Hotel/NDZ/2021/ 26

FIRE SAFETY CERTIFICATE

Issued -1-7-18-12-1-at New Delhi by.

Delhi Fire Service

Dated: 17/08/2021

Copy to:-

1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager,

M/s Golden Palms & Spa (A unit of Indogreen International), Plot No. 6C Community Centre, Mandawali Fazalpur, Delhi-92.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

	INSF	PECTION REPO	ORT						
1	Name & address of the building			ot No. 6C					
			M/s Golden Palms & Spa, Plot No. 6C Community Centre, Mandawali Fazalpur,						
		Delhi-92.		1					
2	Type of occupancy:- Residential								
	2 Basement + Gr. + 07 upper floors. 3. Type of case:- Renewal 4. Details of previous FSC:- F6/DFS/MS/Hotel/NDZ/2018/2139								
	dated 19/09/18								
	Fire safety directives No F6/DFS/MS/BP/Hotel/2008/1533 dated								
	09/06/08 & 01/06/10								
	5. Date of inspection:- 28/07/21								
	7. Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/LN) &								
ļ.,	Sh. Nagender Singh(ADO/SHAH)								
	8. Name & designation of officer		1 (D')						
(From the building side:- 9. Year of construction:-	2009	anday(Director)						
	0. Applicant's letter No:-	01050614506 1 4 1 1	2/07/2021						
S.No		Requirement	21070614706 dated 11	7					
J.1 10	Prevention and fire safety U/R 33	NBC-IV/UBBL	Provided at site	Remarks MR/NMR					
1.	Access to Building*			IVIK/INIVIK					
	1) Road width	12 mtr.	26 mtr.	MD					
	2) Gate width	4.5 mtr.	06 mtr.	MR					
				MR					
	3) Width of internal road	06 mtr.	06 mtr.	MR					
2.	Number, Width Type & Arr	angement of E	xits						
	A. Number of staircases								
	1. Upper floors	02 Nos.	02 Nos.	MR					
	2. Basements	02 Nos.	02 Nos.	MR					
	B. Width of staircase								
	1. Upper floors	1.5 mtr.	1.5 mtr.	MR					
	2. Basements	1.5 mtr.	1.5 mtr.	MR					
	C. Protection of exits								
au de la constante de la const	1. Fire check door	Required	Provided	MR					
	2. Pressurization	Required	Provided	MR					
	D. No. of continuous	01 Nos.	02 Nos.	MR					
	staircase to terrace			1.11					
	E. Width of corridor	1.5 mtr.	1.5 mtr.	MR					
	F. Door size	1 mtr.	1 mtr.	MR					
3.	Compartmentation								
	1) Fire check door	Required	Provided	MR					
	2) Sealing of electrical shafts	Required	Provided	MR					
	3) Fire rating of shaft door	02 hrs.	Provided	MR					
	4) Water curtain	N/A	N/A	N/A					
	5) Fire Dampers	Required	Provided	MR					
4.	Smoke Management System								
25	1) Basements	30 ACPH	Provided	MR					
	2) Upper floors	12 ACPH	Provided	MR					
5.	Fire Extinguishers		-						
	1) Total numbers	60 Nos.	60 Nos.	MR					
	2) Types	ABC & CO2	ABC & CO2	MR					

6.	First-Aid Hose Reel							
	1) Total number of eachfloor	02		02		MR		
	2) Length of hose reel hose	30 m			mtr.	MR		
	3) Nozzle diameter 6.5 mm				5 mm	MR		
7.	Automatic Fire Detection & Alarming System							
	1) Type of detectors		& Smoke		ovided	MR		
	2) Location of main panel	Grou		-	ovided	MR		
	3) Location of repeater panel	Amount Marketine	rity room	-	ovided	MR		
	4) Alternate source of power		y & DG set	-	ovided	MR		
	5) Hooter's Location	Stair	case	Pr	ovided	MF	MR	
8.	MOEFA (Emergency light)	Required		Pr	Provided		MR	
9.	Public Address System	Requ	uired	Provided		MR		
10.	Automatic Sprinkler System						a 2	
	1) Basement Require				ovided	MR		
	2) Upper floors	Requ		-	ovided	MR		
	3) Sprinkler above false	When		Pr	ovided	MR		
4.4	ceiling	Requ	ure				a ^a	
11.	Internal Hydrants				0			
	1) Size of riser/down-comer	150	-	-	0 mm	MR		
	2) Number of hydrants per floor	02 n		-	nos.	MR		
10	3) Hose box	02 n	os.	02	nos.	MR		
12.	Yard Hydrants		2					
	1) Total number of hydrants	04 nos.		04 nos.		MR		
12	2) Hose box	* 04 nos.		04 nos.		MR		
13.	Pumping Arrangement							
	1. Ground level					3		
	a) Discharge of main	22	280 LPM		2280 LPM		MR	
	pump			g				
	b) Head of main pump	90			90 m		MR	
	c) Number of main pump			02 nos			MR	
	d) Jockey pump out put	180 LPM X					MR	
	e) Jockey pump head	70 m		70 m		1	MR	
	f) Stand by pump output	2280 LPM		2280 LPM			MR	
	g) Stand by pump head	90 m		90 m		-	MR	
	h) Auto starting/Manual	Auto		Auto		P	MR	
	stopping		a a					
	2. Terrace level		0.7.75					
	a) Discharge of pump	-450 LPM		900 LPM		MR		
	b) Head of pump	39 m		39 m			MR	
	c) Power supply	Required		Provided			MR	
1.4			quired Provided		Provided	I	ИR	
14.	Captive Water Storage for Fi						1	
	1) Under ground tank capacity		1,50,000 ltr.		1,50,000 ltr.		MR	
	a) Draw-off connection		Required		Provided Provided		MR	
				^			MR	
	c) Access to tank		Required			-	MR	
	d) ()viou lagad tous la serve de						MR	
15.	d) Over head tank capacity Exit Signage.	/	Required		provided		IVII	

En

16	Provision of Lifts.							
	Pressurization of lift shaft	Required	Provided	MR				
	Pressurization of lift lobby	Required	Provided	MR				
	• Communication in lift car	Required	Provided	MR				
	Firemen's grounding switch	Required	Provided	MR				
	Lift signage	Required	Provided	MR				
17	Standby Power Supply	Required	Provided	MR				
18 Refuge Area.								
	Total area	44 Sqm.	Provided	MR				
1000	• Location	5 th & 7 th floor	Provided	MR				
19	Fire Control Room							
	Detector system panel	Required	Provided	MR				
	Flow switch panel	Required	Provided	MR				
	PA system panel	Required	Provided	MR				
	Battery backup	Required	Provided	MR				
	Building floor plans	Required	Provided	MR				
20	Special Fire Protection Systems for	Required	Provided for	MR				
	Protection of Special Risks, if Any:		HT/LT panels	2				

The fire protection systems provided in the building were randomly checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/Hotel/NDZ/2018/2139 dated 19/09/18 renewal under rule 37 of the Delhi Fire Service Rules, 2010, is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

(Nagender Singh)

ADO (Shahdara)

ADO (LN)

Recd.on.

11/9/21

Dy. CFO (NDZ)

CFO(H.D) -