GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO.F6/DFS/MS/2021/CNG WZ) 419

Dated: 27/08/2021

FIRE SAFETY CERTIFICATE

Certified that the CNG Filling Station (IGL) located at Sector-21, Rohini, Delhi, comprised of Ground + One upper floor_owned / occupied by Indraprastha Gas Limited was granted NOC by this department vide letter no F.6/DFS/MS/2018/CNG/826 dated: 24.04.2018. The premises was re-inspected by officer concerned of this department on 19.08.2021 in the presence of Sh. Shivam Gupta (Dy. Manager) and found that the premises have deemed complied with the fire prevention and fire safety requirement in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and the building/ premises is fit for occupancy CNG Filling Station Group 'J' with effect from 27/ or 2021 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rule, 2010 subject to conditions printed below.

Issued on 29/08/2021 at New Delhi by

(Dhrampal Bhardwaj) Dy. Chief Fire Officer Ph:- 01123414250

Copy to:

- 1. Chief General Manager (project), Indraprastha Gas Limited, IGL Bhawan, Plot no-4, Community Center, R.K. Puram, Sect-9, New Delhi-110022.
- 2. The Addl. Commissioner of Police (Lic), 1st Floor, Police Station, Defense Colony, Delhi Conditions for the validity of Fire Safety Certificate:
- 1 All the fire safety arrangement provided there in shall be maintained in good working conditions at all times.
- 2 Any loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3 The trained fire fighting staff should be available round the clock.
- 4 Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5 This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use for land if any.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 8. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The is available on http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms

		INSPECTIO	N REPORT	Gr. + 0	ne Upper floor
	 Type Type Detail Fire \$ Date Name Name from Year 	e of Occupancy : of Case : I ils of previous NOC : Safety directives letter No : If of inspection : of the Inspecting Officers : and designation of officers the building side : Soft Construction : If officers is the state of Construction is the state of Constructio	CNG Filling Station Delhi-85. CNG Filling Station Renewal (Gr. + 1) F.6/DFS/MS/2018/C Nil 19.08.2021 A.K.Sharma ADO,Ro Sh. Shivam Gupta (D 2010 Online e-mail dated 3	Group 'J' NG/826 dated: 24.0 ohini by. Manager)	
	N	Iinimum Standards on fire	NBC	Provided at	Remarks
1		vention and fire safety U/R 33 to building	Requirement	site	MR/NMR
1	Access	Road width	Required	30m	MD
		Gate width		Y	MR
		Width of internal road	N.A	N.A	N.A
2			N.A	N.A	N.A
	Number	er, Width, Type & Arrangement	of Exits		
	a. Num	iber of staircases			
	•	Upper Floors	Required	Provided	MR
	0	Basements	N.A	N.A	N.A
	b. Wid	th of staircases			
	•	Upper Floors	1.25 mtr	1.25 mtr	MR
	•	Basements	N.A	N.A	N.A
	c. Prote	ection of exits			11.71
		Fire check door	N.A	N.A	N.A
	•	Pressurization	N.A	N.A	N.A
		of continuous staircases to terrace	N.A		,
		h of Corridor	N.A N.A	N.A N.A	N.A
	f. Door				N.A
3		rtmentation.	1.0m	1.0m	MR
3		Fire check door	N.A	» T A	27.
			N.A N.A	N.A N.A	N.A N.A
		Sealing of electrical shafts	N.A	N.A	
		Fire Rating of shaft door			N.A
	The same	Water Curtain	N.A	N.A	N.A.
1		Fire Dampers	N.A	N.A	N.A
4		Management System.	20 /		
	•	Basements	30 a/c per hour	N.A	N.A
-	10° 10	Upper floors	12 a/c per hour	N.A	N.A
5	Fire Ex	xtinguishers			

A Anti-

	Total 1	100		
	Total numbers	09 ABC/CO2	26nos.	M.R
	• Types		08 trolley- 75kg. 18-DCP	M.R
	 IS marking 	ISI marked	YES	M.R
6	First-Aid Hose Reels.			
	 Total numbers on each floor 	N.A	N.A	N.A
	 Length of hose reel hose 	30 m	N.A	N.A
	Nozzle diameter	5 mm	N.A	N.A
7	Automatic fire detection and alarming	g system.		
	• Type of detectors	N.A	N.A	N.A
	 Location of Main Panel 	N.A	N.A	N.A
	 Location of Repeater Panel 	N.A	N.A	N.A
	 Alternate source of power 	N.A	N.A	N.A
	 Hooters' Location 	N.A	N.A	N.A
8	MOEFA	Required	Provided	MR
9	Public Address System.	N.A	N.A	N.A
10	Automatic Sprinkler System.			
	Basement	N.A	N.A	N.A
	 Upper Floor 	N.A	N.A	N.A
	 Sprinkler above false ceiling 	N.A	N.A	N.A
11	Internal Hydrants			
	Size of riser/down-comer	N.A	N.A	N.A
	Number of hydrants per floor	N.A	N.A	; N.A
12	Hose Box	N.A	N.A	N.A
12	Yard Hydrants.			
	Total number of hydrants	N.A	N.A	N.A
12	Hose Box	N.A	N.A	N.A
13	Pumping Arrangements.			
	• Ground Level			
	Discharge of main Pump	N.A	N.A	N.A
	Head of Main pump	N.A	N.A	N.A
	Number of main pumps	N.A	N.A	N.A
	Jockey Pump out put	N.A	N.A	N.A
	Jockey pump head	N.A	N.A	N.A
	Standby Pump out put	N.A	N.A	N.A
	Standby Pump HeadAuto Starting/ Manual	N.A	N.A	N.A
	stopping	N.A	N.A	N.A
	Pump House Access	N.A	N.A	N.A
	Terrace level Discharge of nump		***	11011
	Discharge of pumpHead of the pump	N.A	N.A	N.A
	Lamb	N.A	N.A	NA

1		Power Supply	NI A		
		Auto Starting of pump	N.A	N.A	N.A
14	Cant	ive Water Starreng of pump	N.A	N.A	N.A
-		ive Water Storage for fire fig	hting.		
	•	Underground tank capacity	N.A	N.A	27.4
		Diaw-off connection	N.A	N.A	N.A
		Fire service inlet	N.A		N.A
	. >	Access to tank		N.A	N.A
	•	Overhead Tank capacity	N.A	N.A	N.A
15	Exit S	ignage.	N.A	N.A	N.A
		ion of Lifts.			
	•	Pressurization of Lift Shaft	N.A	N.A	
	•	Pressurization of Lift lobby	N.A	N.A	N.A
	•	Communication In lift Car	N.A	N.A	N.A
	•	Fireman's Grounding Switch	N.A		N.A
		Lift Signage		N.A	N.A
7 5	Standby power supply		N.A	N.A	N.A
8 F	Refuge Area.		N.A	N.A	N.A
		Total Area			
	1	ocation	N.A	N.A	N.A
F			N.A	N.A	N.A
	Fire Control Room				
	1	Detector System Panel	N.A	N.A	
	•	Flow Switch Panel	N.A	N.A	N.A
	•	PA System Panel	N.A	N.A	N.A
	•]	Batter backup	N.A		N.A
	• I	Building Floor Plans	N.A	N.A	N.A
Sp	ecial F	ire Protection Systems		N.A	N.A
	Protection of special Risks, if any: DCP Spray System for cascade		Fire buckets filed with sand, No smoking boards were found displayed in Hindi & English. No lose electric wiring were seen in premises & CO2 flooding system found provided.		M.R
DC			Provid		

The fire protection systems provided in the building premises were test checked and found functional at the time of inspection.

in view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the DFS rules of NOC issued vide letter no. F.6/DFS/MS/2018/CNG/826 dated: 24.04.2018, renewal under rule 37 of the Delhi Fire Service rules 2010, is recommended.

DO(NW)

En 24/03/202

Signature of the Inspecting Officer
Name Ajay Kumar Sharma
Designation ADO(Rohini)