FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F-6/DFS/MS/2021/SZ/

Dated: 35/08/2021

Delhi Fire

FIRE SAFETY CERTIFICATE

Certified that the building 352 multi storied two bedroom apartments adjoining pocket -3 Sector-19 B Dwarka New Delhi, having three residential block comprised of Basement + Stilt/Ground +10Upper floor owned/ occupied By DDA have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officers concerned of this department on 18/08/2021 in the presence of Sh Jitender Shati (EE) and found that the said building that the premises is fit for occupancy class "Residential Building "Group A with effect from Solvey for a period of five years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on at 18 at New Delhi by.

Copy to:

1. The Executive Engineer (E), Electrical Division-10, Delhi Development Authority, B-2B, Janak Puri, New Delhi-110058

2. The Chairman, DDA, Vikas Sadan, INA, Delhi – 110023.

Following fire safety directives must be adhered to:-

- 1. Electric are still not provided for individual flat. The electric meters/ panel must be segregated & must not be installed bellow the stairs.
- 2. The trimming of trees must be done at regular interval to ensure free passage for fire vehicles.
- 3. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 4. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 5. The trained staff should be available round the clock.
- 6. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 7. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 8. Basement shall be not used as undertaking given by owner.
- 9. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 10. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

Re inspection to see the compliance of shortcomings communicated vide letter no. F6/DFS/MS/SZ/2021/1342 dated 08/07/2021 are complied.

INSPECTION REPORT

1. Name & address of the building: 352 multi storied two bedroom apartments adjoining pocket -3 Sector-19 B Dwarka New Delhi.

2. Type of Occupancy : Residential (03- Blocks=Basement + Stilt/Ground +10UF)

3. Type of Case : New

4. Details of previous NOC : Nil

5. Fire Safety directives Letter No.: F-6/DFS/MS/BP/2014/348 Dated 23/12/2014

6. Date of inspection : 18/08/2021

7. Name of the Inspecting Officer: Dy.CFO/SZ &ADO/DWK

8. Name and designation of Officer

from the building side : Sh. Jitender Shati (EE)

9. Year of Construction : 2015-20

10. Applicant's letter No.: F10(26)/EE(E)/ELD-10/DDA/2020-21/325 Dated 06/08/2021

S No		um standards on fire tion and fire safety	BBL Requ	iiremen	ts	Provided at	site	Remar MR/NI	
1.	Access	s of building	2				100 010 - 600		
	•	Road width	12	m		Provided		MR	
and the second	•	Gate width	4.5	m		Provided		MR	
	•	Width of internal road	06	m		Provided		MR	
2.	Numbe	er, width, Type & Arrai	ngeme	ents of e	exits				7
	a.	Number of staircases					5 F. B.		
	•	Upper floors				ch block	Provided		MR
	•	Basements		Three	in ea	ich block	Provided & 2 R	Ramp	MR
	b.	Width of staircases				197	: 5,		1 (1)
	•	Upper floors	te.	1.5m			ding railing) in ea deferent location		
and the second	•	Basements		1.5m	3x & 7	1.5 m (Inclι Γwo Ramp o	iding railing) in e f6.25 m width	ach bloc	k MF
	=				(M	easured at 3	deferent location	on)	
	c.	Protection of exits		=		*			1 (D
	•	Fire check door		Requi		Provided			MR
	•	Pressurization		Requi		Provided			MR
	d.	No of continuous stair to terrace	rcase	Requi	red	Provided		9	MR
	e.	Width Of Corridor		1.5m		Provided		\$1	MR
	f.	Door Size	¥	1.5m		Provided (Including door fra	ame)	MR

							-			-
3.	Compartmentation		D.		Т	rovided	1		MR	1
	• Fire check door	0		quired		dad contract of the				l
	Sealing of electrical sh	- 1		quired	1000	rovided		# I	MR	16
	• Fire Rating of shaft do	or		quired	177	rovided			MR	3
	Water Curtain			quired		Provided	d		MR	*
	Fire Dampers		NA		1	VA			NA	re F
4.	Smoke managements System						*		MD	9
	 Basements 		30 hrs	a/c per		Provide	d		MR	Í
	• Upper floors			a/c per]	NA(Nat	ural Ventilatio	n)	NA	
5.	Fire Extinguishers								1.00	l
	 Total numbers 			os. at eac		Provide	710		MR	1
	 Types 		flo			Provide			MR	-
	IS marking			3C & CO2 marked	2 [Provide	d		MR	11 49
6.	First – Aid Hose Reels	-							1 (7)	
	Total numbers on each	ı		in each		Provide	d		MR	-
	floor			m		Provide	d		MR	-
	• Length of hose reel ho	se		m nm		Provide			MR	1
-	Nozzle diameter	1				riovide	u		TATIL	-
7.	Automatic fire detection and a	alarm	ıng	Smoke &	Pr He	at at	Provided	MR	-	-
	 Type of detectors 			basemen		at at	Tiovided	IVIIC		
	 Location of Main Pane 	a1		Ground		r	Provided	MR	0	1
	 Location of Repeater 1 			Required		1	Provided	MR		-
				Required			Provided	MR		1
	Alternate source of poHooters' Location	WEI		Required			Provided	MR		-
8.	MOEFA		1	Required			Provided	MR		1
9.	Public Address System			Required			Provided	MR	1	1
10.	Automatic Sprinkler System	1		redame					100	1
10.	Basements	Req	uire	ed		Provi	ded	MR		T
	 Upper Floor 	NA				NA		NA		The second
	 Sprinkler above 	NA				NA	_	NA		1
	false ceiling	2				,,,,				
11.	Internal Hydrants									
	Size of riser/down-	150	mn	1	Pro	vided	ų a	MR		CONTRACTOR DESCRIPTION OF
	comerNumber of hydrants	3(2	t ea	ch	Pro	vided	- ×	MR		-
	per floor	Blo			110	. 1000				-
	Hose Box	2			D _w =	uidad		MR		
12.	Yard Hydrants	3			Pro	vided		IVIK	11	
12.	Total number of	Rec	quire	ed	Pro	vided		MR		-
	hydrants		quire		Pro	vided		MR		-
	Hose Box		*							-
										Decision for
				14				****		CONTRACTOR STATE
	•									-
										or pleasure man
				2	-					Charles and
				-	1					No. of Concession,
								La Card		-
								а.		The same of the same of
								W IN		

13.	Pump	ing Arrangements								
13.	Pump	ing Arrangements Ground Level								
- 1				23/2050	, D		• 1 1		7.50	· ·
	•	Discharge of main pu	mp	3X2850	A		rided		MR	
		Head of main pump		70 m			rided		MR	
1		Number of main pum	ps	03		100	rided		MR	
	A	Jockey pump out put		2x180 lp			rided		MR	
	-	Jockey pump head		70 m			rided		MR	
	A	Standby Pump out pu	t	2850 lpm			rided		MR	
	A	Standby Pump Head	2	70m		rov	rided		MR	
	>	Auto Staring/Manual		Required	P	rov	rided		MR	
		stopping			27					
		Pump House Access		Required	P	rov	rided	_	MR	
	•	Terrace level		0001	41-	Т	1		1 (1)	
**	1	Discharge of pump		900lpm(a	ii each	F	Provided		MR	5
		Head of the pump	-	block)		D				
		Power supply	-	Required		_	ovided		MR	
	>	Auto starting of pump)	Required		_	ovided		MR	
1.4	0		0	Required		Pr	ovided		MR	
14.	Captiv	ve water Storage for fire								
	•	UG tank cpty		0 litres			Provided		MR	
	>	Draw of connection	Requi				Provided		MR	
		Fire service inlet	Requi				Provided		MR	
	>	Access to tank	Requi				Provided		MR	
	•	Overhead Tank cpty	25,000	ltrs(at ea	ch block)	Provided		MR	
15	Exit S	ignage	Requir				Provided		MR	
16.	Provis	ion of Lifts								-
	~	Pressurization of Lift	Shaft	Require	d		Provided		MR	
	>	Pressurization of lift l	obby	Require			Provided		MR	
2	>	Communication in lift		Require			Provided		MR	
2	>	Fireman's Grounding		Require			Provided		MR	
		Switch		Require	u		Tiovided		IVIIV	
7	>	Lift Signage		Require	d	+	Provided		MR	
17.		by power supply		Require		-	Provided		MR	-11
18.		e Area		require	u ·	+	Tiovided		IVIIX	
	>	Total area		NA		-	NA		NA	
	A	Location		NA			NA	-		
19.	Fire co	ontrol room		INA			NA .		NA	
17.	>	Detector system	Dogwin	and a	D	1	4 C El		1 (D	
		panel	Requir	eu	Provide	ed a	t G Floor		MR	
	<i>D</i>	Flow Switch Panel	D .	1	D 11	1				
			Requir		Provide			1	MR	
		PA System Panel	Requir				at G Floor	1	MR	
	~	Battery backup	Requir		Provide		1		MR	
		Building Floor Plans	Requir	ed	Provide	ed			MR	
		11			-					
										٠
		8								
The second secon		h								
		0								
		9	3.		5					
2										
								50 gr		
-										

systems for Protection of special Risks, if any;	20.	Special Fire Protection Systems for Protection of	Required	ABC Extinguishers	MR
--	-----	---	----------	-------------------	----

fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue numbers serial noted shortcomingsNIL.....

1. Electric meter are still not provided for individual flat. The electric meters/ panel may be segregated & may not be installed bellow the stairs.

2. The trimming of trees may be done at regular interval to ensure free passage for fire vehicles.

Signature of the Inspecting Officer

Name: Sh. Udaivir Singh Designation:- ADO/DWK

Signature of the Inspecting Officer Name Sh. Sunil Chaudhary Designation:- Dy. CFO/SZ

where is D.O. Six Dolsto was busy in court