FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE **NEW DELHI**

No.F6/DFS/MS/SZ/2021/

Dated: 24/08/2021

FIRE SAFETY CERTIFICATE

Certified that the M/S Drool kitchen (A unit of 4RS Hospitality Pvt. Ltd.), is running at ground floor of Metro Commercial Space, Metro station, Sec – 10, Dwarka, New Delhi – 110075 was issued FSC by this department vide letter no. F6/DFS/MS/EH/2012/2962 Dated 14/08/2012 (FSC has already issued to metro station sector 10 Dwarka vide letter no F6/DFS/MS/2020/SZ/179 Dated 30/03/2020) The premises was re - inspected by the officer concerned of this department on 5/08/2021 in the presence of Sh. Ravinder kumar Dhankhar and found that the premises have deemed complied with fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010, and that the building is fit for occupancy class "Assembly" Group D with effect from ________ for a period of three years Issued on . ________ at New Delhi by.

(Sunil Chaudhary) Dy. Chief Fire Officer

Delhi Fire Service

Copy to:

- 1. The Dy Health Officer, South Delhi Municipal Corporation, Najafgarh Zone, Dhansa Stand Najafgarh New Delhi.
- 2. The Manager, M/S Drool kitchen (A unit of 4RS Hospitality Pvt. Ltd.) Metro Commercial Space, Metro station, Sec – 10, Dwarka, New Delhi – 110075.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building: M/S Drool kitchen (A unit of 4RS Hospitality Pvt. Ltd.) at Metro Commercial Space, Metro station, Sec - 10, Dwarka, New Delhi – 110075

2. Type of Occupancy

: Class-D (Assembly)(Restaurant- Ground floor)

3. Type of Case

: Renewal

4. Details of previous NOC: F6/DFS/MS/EH/2012/2962 Dated 14/08/2012 (F6/DFS/MS/2020/SZ/179 Dated 30/03/2020 issued to Sector 10 Metro

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

: 05/08/2021

7. Name of the Inspecting Officer; Sh. Udai vir Singh ADO (DWK)

8. Name and designation of Officer

from the building side

: Sh. Ravinder kumar Dhankhar

9. Year of Construction

: 2010

10. Applicant's letter No.

: Email dated 20/07/2021

2.0			· Linaii dale	34 ZU/07/2021			
S	Minimum standards on fire As per N/7 Proventing the proventing t						
No	prevention and fire safety U/R 3.		As per N/7	Provided at site			
1.	Access of building	3		Trovided at site			
	D duliding				MR/NMR		
	 Road width 	2	12 mtrs				
	• Gate width		12 IIIIrs	12 mtr	MR		
	 Width of internal road 		1.5 mtr Dire	041	IVIIX		
2.	N. 1			ectly accessible from	n road MR		
4.	Number, width, Type & Arranger a. Number of staircasses	nonto	C	NA	NA		
	a. Number of staircases	Helits	or exits		11/21		
	• Upper floors				1 5		
	• Basements	N	A	NA			
	b. Width of at.		A		NA		
	vidul of staircases	N. 1		NA	NA		
	 Upper floors 	N	Λ				
	• Basements			NA	NA		
	c. Protection of exits	N.	A	NA			
	• Fire check door			NA			
	• Pressurization	NA	NA NA				
	d. No of continuous staircase		1	NA	NA		
				NA	NA		
	toterrace	NA NA		NA	NA		
	e. Width Of Corridor			NIA	IVA		
	f. Door Size	02 1	ntr	NA	NA		
0			1161	02 mtr 1.08 mtr	MR(Old		
100	ompartmentation		2.0	N 2			
	 Fire check door 	1		/	case)		
	• Sealing of electrical	NA		NA			
	• Sealing of electrical shafts	NA		NA	NA		
	• Fire Rating of shaft door				NA		
	• water Curtain	NA NA		NA	NA		
	Fire Dampers			NA	NA		
				NA			
					NA		

1.	• Basements	NA		NA	× .	N.	A	
		12 a/c per hour	r E	xhaust fans	Provide		MR	
	• Upper floors	12 a/c per nous		Antaust Turis				
· .	Fire Extinguishers	00.31	70	00 Na	1	M	TD.	
	 Total numbers 	08 Nos.		08 Nos.	/*:		IR	
	 Types 	ABC, CO2		ABC				
- 0	• IS marking	ISI marked	2	Provided		IV	IR	
5.	First – Aid Hose Reel			2 11 1		M		
	 Total numbers on each 	01 No		Provided		IV	IR ·	
	floor	20	_	D		N	1R	
	 Length of hose reel hose 	30 mtr		Provided Provided			îR	
	Nozzle diameter	5 mm		Provided		IV		
7.	Automatic fire detection and alarmin		D	• 1 1	7	(D		
	 Type of detectors 	Smoke		ovided		MR		
	 Location of Main Panel 	Reception	Reception NA			MR NA		
	 Location of Repeater Panel 	NA						
	 Alternate source of power 	Required		attery back	1	MR		
	Hooters' Location	Near entry		rovided		MR		
8.	MOEFA	Required	d Provid		MI			
9.	Public Address System			Provided		MR		
10.	Automatic Sprinkler System							
	Basements	NA	N			NA		
	Upper Floor	Ground floor		Provided			MR	
	Sprinkler above false	NA	N	A		NA		
	ceiling							
11.	Internal Hydrants:							
	Size of riser/down- comer	100 mm	P	rovided		MR	4	
	 Number of hydrants per 	Ground floor	and floor 02			MR		
	floor	é						
	Hose Box	Required	P	rovided		MR	6 2	
12.	Yard Hydrants						n V	
	Total number of hydrants	NA NA			NA			
	Hose Box	NA	N	JA		NA		
13.	Pumping Arrangements: Common	with Metro St	ation	1				
15.	Ground Level							
	Discharge of main pump	NA		1800 lpn	n		NA	
	➤ Head of main pump	NA		70 mtr			NA	
	> Number of main pumps	NA		01			NA	
	> Jockey pump out put	NA		180 lpm			NA	
	> Jockey pump head	NA		70 mtr			NA	
	> Standby Pump out put	NA		1800 lpr	n		NA	
	> Standby Pump Head	NA		70 mtr			NA	
	> Auto Staring/Manual	NA		Provided			NA	
	stopping	NA		Provided			NA	
	Pump House Access				*		-	
	Terrace level	450 LPM	Not	provided	MR as	pum	p at G.	
	Discharge of pump	150 151 111				l at higher side		
	> Head of the pump	40 m Not pro		providedDO.				
	> Power supply				DO			
	> Auto starting of pump			provided	DO			

-			10100					
	14.	The storage for the righting. Common with Metro Station						
		Under ground tank capacity	NA	50000ltrs	NA			
		Draw off connection	NA	Provided	NA			
		Fire service inlet	NA	Provided	NA			
		Access to tank	NA	Provided	NA NA			
		 Overhead Tank capacity 	10000 ltrs N					
-					as pump at G. level aigher side			
	15	Exit Signage	Required	Provided	MR			
	16.	Provision of Lifts		IVIK				
		Pressurization of Lift Shaft	NA	NA	NA			
		Pressurization of lift lobby	NA	NA	NA NA			
		Communication in lift Car	NA	NA	NA NA			
	A,	Fireman's Grounding	NA	NA	NA NA			
4		Switch	NA	NA	NA NA			
***	17.	Lift Signage			INA			
	18.	Standby power supply	Required	DG set 125 KV	A MR			
-	10.	Refuge Area						
-		Total area	NA	NA	NA			
	9.	Docution	NA	NA	NA			
	9.	The control room						
		Detector system panel Flow Switch Panel	NA	NA	NA			
		Thow Switch Faller	NA	NA	NA			
-		Joseph I dilei	NA	NA	NA			
		➤ Battery backup ➤ Building Floor Plans Special Fire Protection Systems for	NA	NA	NA			
h	0.		NA	NA	NA			
	0.		Required CO2	2 fire extinguisher provided MR				
		Protection of special Risks, if any;	near	electric panel.				
1					4			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/EH/2012/2962 Dated 14/08/2012 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name: Sh. Udaivir Singh Designation: ADO (DWK)

Dolptu
Impertion Report required to be continued to be continu

Dy choless, F.f.

do hux