

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/EH/2021/SZ/ 2 00

Dated: 28 / 7 /2021

## FIRE SAFETY CERTIFICATE

Certified that M/s **Govindas Restaurant** located at Iskcon Temple Complex, Sant Nagar, East of Kailash, New Delhi–110065, comprised of ground floor only. The restaurant running at ground floor only was issued Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/EH/SZ/2018/1619 dated 12/07/2018. The premise was re-inspected by the officer concerned of this department on 13/08/2021 in the presence of Mr. Abhay and observed that the said restaurant premise have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class **Assembly Group 'D'** (Eating House) with effect from 1/2/12021 for a period of **three years** in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 28 / 7 /2021 at New Delhi by

(Sunil Chawdhary)
Dy. Chief Fire Officer (SZ)
Delhi Fire Service

## Copy to: -

- 1. The Dy. Health Officer, South Delhi Municipal Corporation, Public Health Department, Central Zone, Lajpat Nagar, New Delhi–110024
- 2. Authorized Signatory, M/s Govindas Restaurant located at Iskcon Temple Complex, Sant Nagar, East of Kailash, New Delhi–110065

## Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

7	INSPECTION	REPORT			
3		M/s Covindas Res	stt Iskcon Temple C	Complex.	
1	Name & Address of the Building	M/s <b>Govindas Restt</b> ., Iskcon Temple Complex, Sant Nagar, East of Kailash, New Delhi–110065			
2 :	True of Occupancy	Group-D, "Assembly" (Eating House)			
3	Type of Occupancy Building Comprised of	Ground Floor only			
4	Type of Case	Renewal			
5	Details of Previous NOC	F.6/DFS/MS/EH/S	SZ/2018/1619 dated 1	12/07/2018	
6	Fire Safety Directives Letter No	F.6/DFS/MS/EH/2005/718 dated 04/04/2005			
7	Date of Inspection	13/08/2021			
8	Name of the Inspecting Officers	DO (SD)			
9	Name & Designation of Officers	Mr. Abhay			
	from the building side	1006	i e		
10	Year of construction	1996	33011771 dated 06/0	8/2021	
11	Applicant letter No.		Provided at Site	Remarks	
S.	Minimum standards on Fire Prevention	Old FSC	Provided at Site	MR/NMR	
No.	and Fire Safety U/R 33	Requirement		11111111111111	
1	Access to Building.	(400	Provided	MR	
	Road width	6m	N/A	N/A	
	Gate width	N/A		N/A	
	Width of internal road	N/A	N/A	IN/A	
2	Number, width, type & arrangement of exits.				
	a) Number of Staircase				
	Upper floors.	N/A	Restt. at GF	N/A	
	Basement floor.	N/A	N/A	N/A	
	b) Width of Staircase				
	> Upper floors	N/A	N/A	N/A	
	Basement floor	N/A	N/A	N/A	
		11/12			
	c) Protection of exits	N/A	N/A	N/A	
	Fire check door		N/A.	N/A	
	Pressurization	N/A	N/A	N/A	
	d) No. of continuous staircase to terrace	N/A N/A	N/A	N/A	
	e) Width of corridor	2 exits	1.40m & 1.13m	MR (old case	
2	f) Door size	2 CAILS	1.40111 & 1.15111	17.4.1	
3	Compartmentation.	Wooden doors	Provided	MR	
	• Fire check door.	N/A	N/A	N/A	
	Sealing of electrical shafts.		N/A	N/A	
	<ul> <li>Fire rating of shaft door.</li> </ul>	N/A		N/A	
	Water curtain	N/A	N/A		
	• Fire dampers.	N/A	N/A	N/A	
4	Smoke Management system.				
	Basement	30 ACPH	N/A	N/A	
	Upper floors	12 ACPH	Provided in kitchen	MR	
5	Fire Extinguishers.				
3	• Total numbers	Required	08 Nos	MR	
	Total numbers	A DC / CO-	ABC & CO2	MR	

Types

6

• ISI Marking

First Aid Hose Reels.

Total numbers on each floor.

Length of hose-reel hose.

Nozzle Diameter

ABC / CO<sub>2</sub>

Required

One

30m

5mm

ABC & CO2

Provided

Two

Provided

Provided

MR

MR

MR

MR

MR

-	N/	1	-
	~ ''	1	

7	Automatic fire detection & alarming system	l.	DI/A	N/A
	Type of detectors	N/A	N/A	
	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A	N/A
	<ul> <li>Location of Repeater Panel</li> </ul>	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	Hooter's location	N/A	N/A	N/A
3	MOEFA	Required	Provided	MR
9	Public Address System	N/A	N/A	N/A
0	Automatic Sprinkler System			1
U	Basement	N/A	N/A	N/A
	• Upper floor	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
1	Internal Hydrants.			
	Size of Riser/Down-comer	N/A	N/A	N/A
	Number of Hydrant per floor	N/A	N/A	N/A
	Hose box.	N/A	N/A	N/A
12	Yard Hydrants.			
	Total number of hydrants.	N/A	N/A	N/A
	Hose box.	N/A	N/A	N/A
13	Pumping arrangements.	Ì		
	Ground Level			
	Discharge of main pump.	N/A	N/A	N/A
	Head of main pump.	N/A	N/A	N/A
	Number of main pumps.	N/A	N/A	N/A
	<ul> <li>Jockey Pump output.</li> </ul>	N/A	N/A	N/A
	<ul> <li>Jockey Pump head.</li> </ul>	N/A	N/A	N/A
	Standby Pump output.	N/A	N/A	N/A
	Standby Pump head.	N/A	N/A	N/A
	Auto Starting/Manual Stopping.	N/A	N/A	N/A
	Pump house access.	N/A	N/A	N/A
	Terrace Level	225 1 DV4	450:LDM	MR
	Discharge of pump.	225 LPM	450 LPM	MR
	Head of pump.	Required	35m Provided	MR
	Power supply.	Required	Provided .	MR
	Auto starting of pump.	Required	riovided	IVIIX
14	Captive water storage for fire fighting.	N/A	N/A	N/A
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> </ul>	N/A	N/A	N/A
	Fire Service Inlet.	N/A	N/A	N/A
	Access to tank.	N/A	N/A	N/A
	<ul> <li>Overhead tank capacity.</li> </ul>	2,500 Ltrs	6,000 Ltrs	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
10	Pressurization of lift shaft.	N/A	N/A	N/A
	C1:C1 11	N/A	N/A	N/A
		N/A	N/A	N/A
	Communication in lift car.	N/A N/A	N/A	N/A
	• Fireman's switch.			
	• Lift signage.	N/A	N/A	N/A
17	Standby Power Supply	Required	Provided	MR
18	Refuge Area			
	Total area	N/A	N/A	· N/A
	• Location	N/A	N/A	N/A

19	Fire Control Room.			
	Detector system panel.	N/A	N/A	N/A
	• Flow switch panel.	N/A	N/A	N/A
	• PA system panel.	N/A	N/A	N/A
	Battery backup.	N/A	N/A	N/A
	Building floor plan.	N/A	N/A	N/A
20	Special Fire Protection Syste Protection of special Risk, if		ABC type fire extinguisher provided near electrical panel	MR

The fire protection system provided in the restaurant premises were checked, tested at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the fire safety certificate issued vide letter No. F.6/DFS/MS/EH/SZ/2018/1619 dated 12/07/2018, renewal under Rule 37 of the Delhi Fire Service Rules 2010, is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer
Name : S.K. Dua

Designation: DO (SD)

DCFO (SZ)

er is put up for My. pl,

Defo(sh)

Ms-cell