GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI- 110001

No. F.6/DFS/MS/CNG/2021/SZ/ 425

Dated: 3/ 08/2021

FIRE SAFETY CERTIFICATE

Certified that **Okhla DIMTS Bus Depot**, located at **Okhla**, **New Delhi** comprised of Single Story building owned/occupied by M/s Indraprastha Gas Limited, was granted FSC by this department vide letter no. F6/DFS/MS/2016/1550 Dated 16/06/2016. The premise was re-inspected by the officer concerned of this department on 11.08.2021 in the presence of Mr. Shaswat Kaushik (Manager) of the said filling station and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class **Hazardous** (CNG Pump) as above with effect from $\frac{31/\sqrt{68}}{2021}$ for a period of **three years** in accordance with rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010.

Issued on 3/ / 08 /2021 at New Delhi by

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER

Copy to: -

1. The Joint C.P (Lic.) First Floor, PS Defence Colony, New Delhi 110049.

2. Sh. Ajay Khatri, DGM-(Fire & Safety) (IGL) LGL Bhawan, Plot No 4, Community Centre, R. K Puram, Sector- 09, New Delhi 110049.

Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting system.

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

	INSPECT	TON REPORT	These principalest out this	mojys X	
1	Name & Address of the Building	Okhla DIMTS Bus Depot, with 02 CNG Dispensers Okhla, New Delhi			
2	Type of Occupancy	Hazardous "Group –J (CNG Pump)			
3 8	Building Comprised of	Ground floor only			
4	Type of Case	Renewal			
5	Details of Previous NOC		016/1550 D + 116/06/20		
6	Fire Safety Directives Letter No	F6/DFS/MS/2016/1550 Dated 16/06/2016			
7	Date of Inspection	Nil			
8	Name of the Inspecting Officers	14-04-2021			
		Mr. Rajesh Kumar (ADO BCP) Mr. Shaswat Kaushik (Manager)			
	Name & Designation of Officers from the building side				
	Year of construction	2016			
11	Applicant letter No.	Gmail Dated 03-08-2021			
	Minimum standards on Fire	Ollivio			
	Prevention and Fire Safety U/R 33	Requirement	Provided at Site	Remarks	
1	Access to Building.			MR/NMR	
The state of the s	Road width	06 mtr	Provided	MR	
	Gate width	-NA-	-NA-	-NA-	
2	Width of internal road	-NA-	-NA-	-NA-	
	Number, width, type and arrangements	of exits.		2	
	a. Number of Staircase				
	Upper floors	-NA-	-NA-	-NA-	
	 Basement floor 	-NA-	-NA-	-NA-	
1	b. Width of Staircase			. 14	
	• Upper floors	-NA-	NTA .		
the state of the s	Basement floor	-NA-	-NA-	-NA-	
C	c. Protection of exits	"IVA"	-NA-	-NA-	
_	Fire check door				
	Pressurization	-NA-	-NA-	-NA-	
		-NA-	-NA-	-NA-	
d	l. No. of continuous staircase to terrace	-NA-	-NA-		
e	. Width of corridor	37 32 32 32 32 32 32 32 32 32 32 32 32 32	-NA-	-NA-	
	*	-NA-	-NA-	-NA-	
f.	. Door size	-NA-	-NA-	-NA-	
3 (Compartmentation.		2144	-IVA-	
	Fire check door.	-NA-	-NA-	-NA-	
	Sealing of electrical shafts.Fire rating of shaft door.	-NA-	-NA-	-NA-	
	Water curtain	-NA-	-NA-	-NA-	
	• Fire dampers.	-NA-	-NA-	-NA-	
4. S	moke Management system.	T 17 7	-1N/1-	-NA-	
	Basement	-NA-	-NA-	NT 4	
	• Upper floors	-NA-	-NA-	-NA-	
5. F	ire Extinguishers.	11/1-	-INA-	-NA-	
	Total numbers	Dogwin-1	20.37		
	• Types	Required	32 Nos	MR	
	ISI Marking	ISI Marked	Co2 flooding- 01, DCP/75 kg- 05, DCP/09kg	MR	
			-11 & CO ₂ -06	IVII	
6. Fi	The state of the s		Provided	MR	
U. F	irst Aid Hose Reels.				
	Total numbers on each floor.	-NA-	-NA-	-NA-	
-18	 Length of hose-reel hose. 	-NA-	-NA-	-NA-	
- 43	Nozzle Diameter	-NA-	-NA-	NIA	

		Gas & Flame	Provided in compressors	MR
	Type of detectors	Required	Ground floor	MR
	Location of Main Panel	-NA-	-NA-	-NA-
	Location of Repeater Panel	Required	Provided	MR
	Alternate source of power Hooter's location	Required	Technician room	MR
8.	Hooter's location MOEFA	-NA-	-NA-	-NA-
9.	Public Address System	-NA-	-NA-	-NA-
		-1471		
10.	Automatic Sprinkler System		-NA-	-NA-
	Basement	-NA-		-NA-
	Upper floorsSprinkler above false ceiling	-NA-	-NA-	-NA-
		-NA-	-NA-	-11/7-
11.	Internal Hydrants.			NIA
	Size of Riser / Down-comer	-NA-	-NA-	-NA-
	Number of Hydrant per floor	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
12.	Yard Hydrants.			
	Total member of hydroute	-NA-	-NA-	-NA-
	Total number of hydrants.Hose box.	-NA-	-NA-	-NA-
13.	Hose box. Pumping arrangements.			de Participant
15.				
		-NA-	-NA-	-NA-
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	Terrace Level		N/A	-NA-
	Discharge of pump.	-NA-	-NA- -NA-	-NA-
	Head of pump.	-NA-	-NA-	-NA-
	Power supply.	-NA-	-NA-	-NA-
	Auto starting of pump.	-NA-	-1/V-	1112
14.	Captive water storage for fire-fighting	-NA-	-NA-	-NA
-37	Underground tank capacity.	-NA-	-NA-	-NA
	Draw-off connection.	-NA-	-NA-	-NA
	Fire Service Inlet.	-NA-	-NA-	-NA
	Access to tank.	-NA-	-NA-	-NA
15.	Overhead tank capacity. No Smoking signage	Required	Provided in Hindi &	MR
			English	
16.		-NA-	-NA-	-NA
	Pressurization of lift shaft.	-NA-	-NA-	-NA
	 Pressurization of lift lobby. 	-NA-	-NA-	-NA
	 Communication in lift car. 	-NA-	-NA-	-NA
	Fireman's switch.		-NA-	-NA
	Lift signage.	-NA-		
1'	Standby Power Supply	NA	Provided (DG Set)	147
18	Refuge Area		(d) Lara Do Pile hom	
	Total area	-NA-	-NA-	-NA
	• Total area	-NA-	-NA-	-NA

19.	Fire Control Room.			
	 Detector System Panel. Flow Switch Panel. PA system Panel. Battery backup Building floor plan Special Fire Protection System for the Protection of special Risk, if any.	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
20.		-NA-	-NA-	-NA-
		Co2 flooding system connected through detectors provided in each compressor unit		MR

"No Smoking" Sign boards were found displayed both in Hindi & English at conspicuous places. No loose electric wiring was seen in the premises.

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under rules, renewal of the FSC issued vide letter No. F6/DFS/MS/2016/1550 Dated 16/06/2016 under rules 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly, DFA is put up for perusal and signature please.

Signature of the Inspecting Officer

Name: Mr. Rajesh Kumar Designation: ADO (BCP)

s approved fit better