GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001

No.F6/DFS/MS/School/NDZ/2021/ 689

Dated:- 62 /08/2021

FIRE SAFETY CERTIFICATE

Certified that the Rishabh Public School located at Pocket-IV, Mayur Vihar, Phase-1, Delhi-91, comprised of A block (G+02 upper floors) & B block (B+G+03 upper floors) owned/occupied by Rishabh Public School, was granted FSC by this department vide letter No. F6/DFS/MS/School/2018/NDZ/1567 dated 05/07/2018. The premises was re-inspected by the officer concerned of this department on 23/08/2021 in the presence of the Mr. Amit Bhati (Manager) and found that school have deemed complied with the fire prevention and fire safety requirements in accordance with Circular No. F.16/Estate/CC/Fire Safety/2011/3298-3398 dated 01/03/2011 issued by Director of Education and the building premises is fit for occupancy of class Group B "Educational Building" Sub-Div. B-I with effect from -O2-4--2021 for a period of three years, subject to conditions printed below.

(Dr. S.K. Tomar) Dy. Chief Fire Officer Delhi Fire Service

0×10mm

Copy to:-

1. The Dy. Director of Education, D-Block, Anand Vihar, Delhi-91.

2. The Principal, Rishabh Public School, Pocket-IV, Mayur Vihar, Phase-1, Delhi-21.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1.	. Name & address of the building		blic School, Pocket	-IV, Mayur				
~	T		e-1, Delhi-91	. 2) . 0				
2	2. Type of occupancy:-	B block(B+	Group, A block (GG+3)	+2) &				
3	3. Type of case:-	Renewal						
4	I. Details of previous NOC:-	F6/DFS/M	S/School/2018/ND	Z/1567 dated				
		05/07/2018						
5	5. Fire safety directives No		c/CC/Fire Safety/20	11/3298-3398				
		dated 01/03	/2011					
	5. Date of inspection:-	23/08/2021						
	Name of the inspecting officer: Sh. Manoj Kumar Sharma (ADO/LN) Name & designation of officer From the building side: Manoj Kumar Sharma (ADO/LN)							
8								
0	From the building side:- Year of construction:-		Bhati (Manager)					
		2002	1 dated 09/08/2021					
1'	0. Applicant's letter No:-	RPS/08/202	1 dated 09/08/2021	Old Case				
S.No.	. Minimum Standards on fire	Requirement	Provided at site	Remarks				
5.110	Prevention and fire safety	Circular	1 Tovided at Site	MR/NMR				
	U/R 33	Circular		TVITOTVITO				
1.	Access to Building							
	1) Road width	06 mtr.	10 mtr.	MR				
	2) Gate width	4.50 mtr.	05 mtr.	MR				
	3)Width of internal road	NA	NA	NA				
2.	Number, Width Type & Arran	gement of Exits		# 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				
	A. Number of staircases	04 NOS.	04 NOS.	MR				
	1. Upper floors A Block	02 NOS.	02 NOS.	MR				
18	B block	02 NOS.	02 NOS.	MR				
	2. Basement in B Block only	01 NOS.	01 NOS.	MR				
	B. Width of staircase	-						
	1. Upper floor A Block	1.25 mtr	1.25 mtr & 1.15	MR				
	(G+2)	. 2	mtr.					
	B Block (G+3)	1.5 mtr	1.5 mtr each	MR				
	2. Basement in B Block only	1.5 mtr	1.5 mtr	MR				
- 5	C. Protection of exits							
	1. Fire check door	N/A	N/A	N/A				
	2. Pressurization	N/A	N/A	N/A				
	D. No. of continuous	02 NOS.	03 NOS.	MR				
,	staircase to terrace							
	E. Width of corridor	1.5 mtr	1.5 mtr.	MR				
_	F. Door size	1 mtr.	1 mtr.	MR				
3.	Compartmentation			2 14				
ii ii	1) Fire check door	Required	Provided	MR				
	2) Sealing of electrical shafts	N/A	N/A	N/A				
	3) Fire rating of shaft door	N/A	N/A	N/A				
	4) Water curtain	N/A	N/A	N/A				
4	5) Fire Dampers	N/A	N/A	N/A				
4.	Smoke Management System							
	1) Basements	Required	Provided	MR				
	2) Upper floors	N/A	Ventilated	MR				

5.	Fire Extinguishers							
	1) Total numbers	-	Nos.		2 Nos.	-	IR	
	2) Types	-	3C & CO2	_	BC, CO2	_	IR	
	3) ISI marking	Re	quired	Pı	rovided	N.	IR .	
).	First-Aid Hose Reel		1.					
	1)Total number of each floor	01	no.	0	l no.	M	íR	
	2) Length of hose reel hose	30	m	30	0 m	N	1R	
	3) Nozzle diameter		5 mm		5 mm		MR	
7.	Automatic Fire Detection & Alarming System							
	1) Type of detectors N		A	N	/A	N	I/A	
	2) Location of main panel	N/	A	N	/A	N	I/A	
	3) Location of repeater panel	N/	Α	N	/A	N	I/A	
	4) Alternate source of power	N/	Ά	N	/A	N	I/A	
	5) Hooter's Location	N/	A	N	/A	N.	[/A	
8.	MOEFA	N/	A	P	Provided		MR	
9.	Public Address System	N/A		P	Provided		1R	
10.	Automatic Sprinkler System			12				
	1) Basement	N/	'A	N	I/A	N	I/A	
	2) Upper floors	N/			I/A		I/A	
	3) Sprinkler above false	N/			I/A		I/A	
	ceiling							
11.	Internal Hydrants				2		**************************************	
	1) Size of riser/down-comer	10	0 mm	1	00 mm	N	1R	
	2) Number of hydrants per	11	no.	1	no.	N	⁄IR	
	floor		W.					
	3) Hose box	11	no.	1	no.	N	/IR	
12.	Yard Hydrants							
	1) Total number of hydrants		'A	N	I/A	N	I/A	
	2) Hose box		'A	N	I/A	N	I/A	
13.	Pumping Arrangement					. ;		
	1) Ground level		N/A		N/A		N/A	
	a) Discharge of main		N/A		N/A		N/A	
	pump							
	b) Head of main pump		N/A		N/A		N/A	
	c) Number of main pur		N/A		N/A	1	N/A	
	d) Jockey pump out pu	-	N/A		N/A	1	N/A	
4	e) Jockey pump head		N/A		N/A		N/A	
	f) Stand by pump outp	ut	N/A		N/A	,	N/A	
	g) Stand by pump head		N/A	-	N/A		N/A	
	h) Auto starting/Manu		N/A		N/A		N/A	
	stopping							
	2) Terrace level							
	a) Discharge of pump		450 LPM		2X450 LPM		MR	
	b) Head of pump		40 m		40 m		MR	
	c) Power supply		Required		Provided		MR	
	d) Auto starting of pur	nn	Required		Provided		MR	
1	a) Traco starting of pur	MIN	1 LOUGHILOU		AIUTIUUU		TATT	

m

00 11

ed lit.

N/A V/A /A A

14.	Captive Water Storage for Fire Fighting					
	1) Under ground tank capacity	N/A	50,000 lit.	MR		
	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	Required	Provided	MR		
	d) Over head tank capacity	10,000 lit.	15,000 lit.	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.	1		1711		
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	N/A	N/A	N/A		
	d) Fireman's switch	N/A	N/A	N/A		
	e) Lift signage	N/A	N/A	N/A		
17.	Stand by Power Supply	N/A	N/A	N/A		
18.	Refuge Area	N/A	N/A	N/A		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	N/A		
5	c) PA system panel	N/A	N/A	N/A		
É	d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A		
20.	Special Fire Protection System any:	for Protection o	of special Risk, if	N/A		

The fire protection system provided in the school building were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/School/2018/NDZ/1567 dated 05/07/2018, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- M.K. Sharma Designation :- ADO (LN)

DCFO(NDZ)

OCHO!

ADOCUM

F.T. lette is prot

is but upth

mush

D. No 3 - ZON
Date 27 May
Pate 27 May
Pate