GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2021/ 357

Dated: .3./.9./2021

FIRE SAFETY CERTIFICATE

Certified that the Shivlok Palace Guest House located at 4648-4650, Shora Kothi, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (04 guest rooms + reception + 01 store), 1st floor to 3rd floor (07 guest rooms at each floor) and terrace floor - temporary shed & D.G set, total 25 guest rooms owned/occupied by Shivlok Palace Guest House was earlier granted FSC by this department vide letter No. F6/DFS/MS/GH/2018/NDZ/1836 dated 07/08/18. Now, the premise was re-inspected by the officer concerned of this department on 28/08/21 in the presence of Sh. Tarun Nagpal and found that the said guest house building having an affidavit on dated 28.09.2019 submitted by by owner regarding not to use any floor above third floor, has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (04 guest rooms + reception + 01 store), 1st floor to 3rd floor (07 guest rooms at each floor) Total -25 guest rooms only at ground to 3rd floor with effect from ----3-6-7-1-for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 3 9 - - - at New Delhi by.

(Dr. S.K.Tomar) Dy. Chief Fire Officer Delhi Fire Service

X/ Omn

Copy to:-

3. The Manager,

- 1. The Commissioner, North MCD, New Delhi: to ensure the occupancy in the building.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. Online id no. 2021072816168 dated 28.07.21

Shivlok Palace Guest House 4648-4650, Shora Kothi, Pahar Gani, New Delhi. Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction,
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INS	PF	CTI	ON	REP	ORT

1. Name & address of the building Shivlok Palace Guest House at 4648-4650,

Shora Kothi, Pahar Ganj, New Delhi.

2. Type of occupancy:- Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 25 Guest rooms)
Ground floor (04 guest rooms + reception + 01 store), 1st floor to 3rd floor (07 guest rooms at each floor) and terrace floor – (02 room sealed) and not in use as per

affidavit dated 28.09.21

3. Type of case:- Renewal

4. Details of previous FSC:- No. F6/DFS/MS/GH/2018/NDZ/1836 dated

07/08/18.

5. Fire safety directives No.- N/A6. Date of inspection:- 28/08/21

6. Date of inspection:- 28/08/27. Name of the inspecting officer:- Sh. Ray

Sh. Rayinder Singh (ADO/CC) Sh. Rajinder Atwal (DO/CD)

8. Name & designation of officer From the building side:-

Sh. Tarun Nagpal

9. Year of construction:-

10. Applicant's letter No:- ID No 2021072816168 dated 28.07.21

Old Case

				Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			
	1) Road width	N/A	N/A	N/A
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arr	angement of Ex	its	
	A. Number of staircases			
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	0.80 mtr.	1.19 mtr. to 1.25 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	01 mtr.	01 mtr.	MR
3.	Compartmentation			
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			
	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 ACPH	Natural/exhaust fan	MR
5.	Fire Extinguishers			
	1) Total numbers	10 Nos.	10 Nos.	MR



4/20

		ADC 8 CO2	ABC & CO2	MR
	2) 1 1 1 1 2 2	ABC & CO2	Provided Provided	MR ?
	5) 151 1114111115	Required	Flovided	
6.	First-Aid Hose Reel	0.1	01	MR
	1) Total Hamber of Carting	01 30 mtr.	30 mtr.	MR
	2) Length of hose reel hose	05 mm	05 mm	MR
	3) Nozzle diameter			
7.	Automatic Fire Detection & A	Required	Provided	MR
	1) Type of detectors CO type	Ground floor	Provided	MR
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	Required	Provided	MR
	4) Alternate source of power	Ground floor	Provided	MR
	5) Hooter's Location	The state of the s	Provided	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	IVIIC
10.	Automatic Sprinkler System	27/4	NI/A	N/A
	1) Basement	N/A	N/A N/A	N/A
	2) Upper floors	N/A	N/A N/A	N/A
	3) Sprinkler above false	N/A	IN/A	14/1
	ceiling			
11.	Internal Hydrants	DI/A	N/A	N/A
	1) Size of riser/down-comer	N/A	N/A N/A	N/A
	2) Number of hydrants per	N/A	IN/A	1 1/1 2
	floor	N/A	N/A	N/A
	3) Hose box	N/A	INA	1
12.	Yard Hydrants	N/A	N/A	N/A
	1) Total number of hydrants	N/A N/A	N/A	N/A
	2) Hose box	IN/A	11/11	
13.	Pumping Arrangement	N/A	N/A	N/A
	1) Ground level	N/A N/A	N/A	N/A
	a) Discharge of main	IN/A	11/11	
1	pump	N/A	N/A	N/A
	b) Head of main pumpc) Number of main pum		N/A	N/A
	a) Number of main bull			IN/A
		A		N/A N/A
	d) Jockey pump out put	N/A	N/A	
	d) Jockey pump out pute) Jockey pump head	N/A N/A	N/A N/A	N/A N/A
	d) Jockey pump out pute) Jockey pump headf) Stand by pump output	N/A N/A t N/A	N/A N/A N/A	N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head	N/A N/A t N/A N/A	N/A N/A N/A N/A	N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual	N/A N/A t N/A N/A	N/A N/A N/A	N/A N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping	N/A N/A t N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	N/A N/A t N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump	N/A N/A t N/A N/A N/A	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump	N/A N/A t N/A N/A N/A N/A N/A 225 LPM 30 mtr.	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	N/A N/A t N/A N/A N/A N/A N/A 225 LPM 30 mtr. Required	N/A N/A N/A N/A N/A 225 LPM 30 mtr.	N/A N/A N/A N/A N/A N/A N/A MR
	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pum	N/A N/A t N/A N/A N/A N/A N/A 225 LPM 30 mtr. Required Required	N/A N/A N/A N/A N/A N/A 225 LPM 30 mtr. Provided Provided	N/A N/A N/A N/A N/A N/A MR MR MR MR
14.	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pum Captive Water Storage for	N/A N/A t N/A N/A N/A N/A N/A 225 LPM 30 mtr. Required Required Fire Fighting	N/A N/A N/A N/A N/A N/A 225 LPM 30 mtr. Provided Provided	N/A N/A N/A N/A N/A N/A MR MR MR
14.	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pum Captive Water Storage for 1) Under ground tank	N/A N/A t N/A N/A N/A N/A N/A 225 LPM 30 mtr. Required Required	N/A N/A N/A N/A N/A N/A N/A 225 LPM 30 mtr. Provided Provided	N/A N/A N/A N/A N/A N/A N/A N/A MR MR MR MR N/A
14.	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pum Captive Water Storage for 1) Under ground tank capacity	N/A N/A t N/A N/A N/A N/A N/A 225 LPM 30 mtr. Required Required Fire Fighting N/A	N/A N/A N/A N/A N/A N/A N/A 225 LPM 30 mtr. Provided Provided	N/A N/A N/A N/A N/A N/A MR MR MR MR
14.	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pum Captive Water Storage for 1) Under ground tank capacity a) Draw-off connection	N/A N/A t N/A N/A N/A N/A N/A 225 LPM 30 mtr. Required Required Fire Fighting N/A N/A	N/A N/A N/A N/A N/A N/A N/A 225 LPM 30 mtr. Provided Provided	N/A N/A N/A N/A N/A N/A N/A N/A MR MR MR MR N/A
14.	d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pum Captive Water Storage for 1) Under ground tank capacity	N/A N/A t N/A N/A N/A N/A N/A 225 LPM 30 mtr. Required Required Fire Fighting N/A	N/A N/A N/A N/A N/A N/A 225 LPM 30 mtr. Provided Provided N/A N/A	N/A N/A N/A N/A N/A N/A N/A MR MR MR MR N/A N/A



15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	em for Protect	tion of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2018/NDZ/1836 dated 07/08/18 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval up to third floor only.

Signature of the inspecting officer

Name: - Rajinder Atwal Designation: - DO (CD)

Signature of the Inspecting Officer

Name: Ravinder Singh Designation: ADO (CC)

D. No. 311 ON Date 3 (3) 20 No. 511 ON Date 3 (3) 20 No. 511 ON Date 3 (3) 20 No. 510 No. 510

Dycholmoz) F. G. pl.

Reens I and Synalton Place

Dannas

0×10mm