GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2021/ 224

Dated: 10 9 21

FIRE SAFETY CERTIFICATE

Certified that the Embassy Restaurant located at D- 11, Inner Circle, Connaught Circus, New Delhi comprises of Ground + Mezzanine + 02 Upper floor, Restaurant is running at Ground + Mezzanine floor was earlier granted FSC by this department vide letter No.F6/DFS/MS/EH/2018/NDZ/323 dated 27/02/18. Now, The premises was re-inspected by the officer concerned of this department on 06/09/21 in the presence of Mr. Sunil Malhotra and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D with effect from 10/19/12]... for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 1019 (2) at New Delhi by.

Dr. S.K.Tomar) Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), Ist floor, Defence Colony Police station, New Delhi id no.2021082018389 dated 20/08/2021
- 2. The Medical Officer of Health, Health Department, Palika Kendra, New Delhi.
- 3. The Manager,

Embassy Restaurant at D-11, Inner Circle, Connaught Circus, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.
- 3. The trained firefighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

1/21

INSPECTION REPORT

1. Name & address of the building Embassy Restaurant at D-11, Inner

Circle, Connaught Circus, New Delhi.

2. Type of occupancy:- Assembly Building Group-D

Gr. + Mezz. + 02 upper floors, Restaurant is running

at Ground + Mezzanine floor.

3. Type of case:- Renewal

4. Details of previous FSC:- F6/DFS/MS/EH/2018/NDZ/323 dated

27/02/18

5. Fire safety directives No.- N/A

6. Date of inspection: 06/09/21

7. Name of the inspecting officer:-

8. Name & designation of officer from the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Sh. Ravinder Singh (ADO/CC)

Mr. Sunil Malhotra Old Heritage Bldg.

online id no.2021082018389 dated 20/08/2021

| S.No | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement/ Existing fire safety arrangements | Provided at site | Remarks MR/NMR | |
|------|---|--|------------------|-------------------|--|
| 1. | Access to Building | | | | |
| | 1) Road width | 09 mtr. | 09 mtr. | MR | |
| | 2) Gate width | N/A | N/A | N/A | |
| | 3)Width of internal road | N/A | N/A | N/A | |
| 2. | Number, Width Type & A | | 11/11 | | |
| | A. Number of staircases | | | 1000 | |
| | 1. Upper floors | 01 No. | 02 No. | MR | |
| | 2. Basements | N/A | N/A | N/A | |
| | B. Width of staircase | | | | |
| | 1. Upper floors | 1.0 & 1.25 mtr. | 1.0 & 1.25 mtr. | MR | |
| | 2. Basements | N/A | N/A | N/A | |
| | C. Protection of exits | N/A | N/A | N/A | |
| | 1. Fire check door | N/A | N/A | N/A | |
| | 2. Pressurization | N/A | N/A | N/A | |
| | D. No. of continuous staircase to terrace | 01 | 01 | MR | |
| | E. Width of corridor | N/A | N/A | N/A | |
| | F. Door size | 1.20 mtr. | 1.20 mtr. | MR | |
| 3. | Compartmentation | | | | |
| | 1) Fire check door | N/A | N/A | N/A | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | |
| | 4) Water curtain | N/A | N/A | N/A | |
| | 5) Fire Dampers | N/A | N/A | N/A | |
| ١. | Smoke Management System | | | | |
| | 1) Basements | 30 ACPH | N/A | N/A | |
| | 2) Upper floors | 12 ACPH | Exhaust fan | MR | |
| | Fire Extinguishers | | | | |
| | 1) Total numbers | 10 Nos. | 10 Nos. | MR | |
| | 2) Types | ABC & CO2 | ABC & CO2 | MR | |
| | 3) ISI marking | Required | Provided | MR | |



| (| - HJ0 | | | | | |
|-----|--|----------|--------------|---------------|--|--|
| 6. | First-Aid Hose Reel | | | \rightarrow | | |
| | | | | | | |
| | 1) Total number of each | 01 | 01 | MR | | |
| | floor | | 01 | IVIIC | | |
| | 2) Length of hose reel hose | 30 mtr. | 30 mtr. | MR | | |
| | 3) Nozzle diameter | 05 mm | 05 mm | MR | | |
| 7. | Automatic Fire Detection & Alarming System | | | | | |
| | 1) Type of detectors | N/A | N/A | N/A | | |
| | 2) Location of main panel | N/A | N/A | N/A | | |
| | 3) Location of repeater | N/A | N/A | N/A | | |
| | panel | | | | | |
| | 4) Alternate source of | N/A | N/A | N/A | | |
| | power | | | | | |
| | 5) Hooter's Location | N/A | N/A | N/A | | |
| 8. | MOEFA | Required | Provided | MR | | |
| 9. | Public Address System | N/A | N/A | N/A | | |
| 10. | Automatic Sprinkler System | | | | | |
| | 1) Basement | N/A | N/A | N/A | | |
| | 2) Upper floors | Required | Provided | MR | | |
| | 3) Sprinkler above false | N/A | N/A | N/A | | |
| | ceiling | | | | | |
| 11. | Internal Hydrants | - | | | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A | | |
| | 2) Number of hydrants per | N/A | N/A | N/A | | |
| | floor | | | | | |
| | 3) Hose box | N/A | N/A | N/A | | |
| 12. | Yard Hydrants | | | | | |
| | 1) Total number of hydrants | N/A | N/A | N/A | | |
| | 2) Hose box | N/A | N/A | N/A | | |
| 13. | Pumping Arrangement | | | | | |
| | 1) Ground level | | | | | |
| | a) Discharge of main | N/A | N/A | N/A | | |
| | pump | | | | | |
| | b) Head of main pump | N/A | N/A | N/A | | |
| | c) Number of main | N/A | N/A | N/A | | |
| | pump | | | | | |
| | d) Jockey pump out put | N/A | N/A | N/A | | |
| | e) Jockey pump head | N/A | N/A | :N/A | | |
| | f) Stand by pump | N/A | N/A | N/A | | |
| | output | | | | | |
| | g) Stand by pump head | N/A | N/A | N/A | | |
| | h) Auto | N/A | N/A | N/A | | |
| | starting/Manual | | | | | |
| | stopping | | | | | |
| | 2) Terrace level | | | | | |
| | a) Discharge of pump | 450 LPM | 450 &180 LPM | MR | | |
| | b) Head of pump | 30 mtr. | 30 mtr. | MR | | |
| | c) Power supply | Required | Provided | MR | | |
| | d) Auto starting of | Required | Provided | MR | | |
| | pump | | | | | |
| 14. | Captive Water Storage for 1 | | 3 | | | |
| | 1) Under ground tank | N/A | N/A | N/A | | |



| | capacity | | 27/4 | NI/A |
|-------|--|--------------|------------------|------|
| | a) Draw-off connection | N/A | N/A | N/A |
| | b) Fire service inlet | Required | Provided | MR |
| | c) Access to tank | N/A | N/A | N/A |
| ax. * | d) Over head tank capacity | 5,000 ltr. | 5,000 ltr. | MR |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | · N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| 100 | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection Syste Risk, if any: ABC & Co2 | em for Prote | ction of special | MR |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2018/NDZ/323 dated 27/02/18, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval pl.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

Doled

Sycholonoz)

F. A. Pl.

As cuppowers pari pertup Ferlew ferresp

Service * Tan Se

ANOCOES