FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [See sub-rule (1) of rule 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No.F.6/DFS/MS/School/2021/SZ/ 789

Dated: 25/ 9 /2021

FIRE SAFETY CERTIFICATE

Certified that the Rao Mansa Ram Public School located at Plot No. 991/1, Near Oberai Farm, Kapashera, New Delhi-110037 comprised of Basement (storage and activites), Ground Floor & Three Upper Floors only owned / occupied by Rao Mansa Ram Public School was issued Fire Safety Certificate by department this Vide letter No. F6/DFS/MS/School/2018/SZ/863 dated 27/04/2018. The premises was re-inspected by the officer concerned of this department on 18/09/2021 in the presence of Sh. Vikas Yadav and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with rule 33 of Delhi Fire Service Rules, 2010 and that the building / premises is fit for occupancy class "Educational" (Group-B) with effect from $\frac{23}{9}$ /2021 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rules, 2010.

Issued on at New Delhi by

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER (S.Z.) oral

Copy to :-

- 1. Principal, Rao Mansa Ram Public School, Plot No. 991/1, Near Oberai Farm, Kapashera, New
- 2. Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054.

Conditions for the validity of Fire Safety Certificate:

- 1. All the means of escape / entry / exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided there in shall be maintained in good working conditions
- 3. Any loss of life or property due to non- functional fire safety measure shall be at the
- 4. All the staff members must know the correct method of operation of fire fighting system.
- 5. This Fire Safety Certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3. of UBBL-2016), if any. 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in
- Form 'J' [sub-rule (1) of rule37] along with a copy of this Certificate, six months prior to its
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first 2010. The WWW.dfs.Delhigovt.nic.in from is available on

			NJ-16		÷			
		INSPEC	TION REPOR	<u>r</u>	N. 001/1			
1. Na	ame & a	ddress of the building:	Rao Mansa Ram Pu	blic School, Plot	No. $991/1$, Pelbi-110037.			
о т.	ma of O		Near Oberai Farm, I	Kapashera, New L				
		Comprised of :	: Educational : Basement, Ground plus three upper floors.					
4 Tx	me of C	ase .	Renewal					
5. De	etails of	previous NOC No. F6/	DFS/MS/School/20	18/SZ/863 dated 2	27/04/2018			
6. Fi	re Safet	y directives Letter No.	: NBC (Part-IV)				
7. D	ate of in	spection	: 18/09/2021					
		he Inspecting Officer	: A.D.O. (S.J.)					
9. N		designation of Officer	: Sh. Vikas Yao	lav				
10 V		m the building side	: Sh. Vikas Tac : 2002	lav				
10. Y	ear of C	onstruction	: 2002 ail ID-rmr4007@gmai	.com dated 10/09/20	021			
S II. A	Applicant's letter received through er Minimum standards on fire		Old NOC	Provided at	Iternatio			
No	prevention and fire safety		Requirements	site	MR/NMR			
140	U/R 33		roquin					
1		of building						
1.		Road width	бт	Provided	MR			
	•		NA	NA	NA			
	•	Gate width		NA	NA			
	•	Width of internal road						
2.	Number, width, Type & Arrangements of exits							
	a.		2	2	MR			
	•	Upper floors	NA	NA	NA			
	•	Basements						
	Width	of staircases	1.5m / 0.90m	2m & 1.10m	MR			
	•	Upper floors	NA	NA	NA			
	•	Basements	INA					
		tion of exits	NA	NA	NA			
		Fire check door		NA	NA			
		Pressurization	NA	Provided	MR			
	b.	No of continuous	1	Provided	IVIIX			
		staircase to terrace Width Of Corridor	1.5m	1.5m	NA			
	C.			Provided	MR			
		Door Size	1m	Trovided	ITIN			
3.	Comp	artmentation		NA	NA			
	٠	Fire check door	NA	NA	NA			
	•	Sealing of electrical	NA	NA	NA			
		shafts						
	•	Fire Rating of shaft	NA	NA	NA			
		door	NA	NIA	NIA.			
	•	Water Curtain	NA	NA	NA			
	٠	Fire Dampers	NA	NA	NA			
4.	Smoke	e managements System						
	٠	Basements	30 a/c per hour	Exhaust fan	MR			
	٠	Upper floors	12 a/c per hour	NA	NA			
5.	Fire E	xtinguishers		A	l			
	•	Total numbers	20	Provided	MR			
	•	Types	ABC /Co ₂	Provided	MR			
	•	ISI marking	ISI Marked	Provided	MR			
		A NO A TILBOR INTITION						

N-17

5.	First – Aid Hose Reels			NFIA			
		1		1	MD		
	each floor	1		1	MR		
	Length of hose reel hose	30m		30m	MR		
	Nozzle diameter	5mm		5mm	MR		
7.	Automatic fire detection and alarming system						
	 Type of detector 		NA	NA	NA		
	Location of Main Par		NA	NA	NA		
	 Location of Repeater Panel 		NA	NA	NA		
	• Alternate source of p	ower	NA	NA	NA		
	Hooters' Location	NA		NA	NA		
3.	MOEFA		NA	NA	NA		
9. Public Address System		NA		NA	NA		
0.	Automatic Sprinkler System						
	Basements	Requir	ed	Provided	MR		
	Upper Floor	NA		NA	NA		
	Sprinkler above false ceiling	NA		NA	NA		
1.	Internal Hydrants						
1.	Size of riser/down-	NA		Provided			
	comer			Provided	NA		
	• Number of hydrants per floor	NA		ŇA	NA		
	Hose Box	NA		NA	NA		
2.	Yard Hydrants						
	• Total number of hydrants	NA		NA	NA		
	Hose Box	NA		NA	NA		
3.	Pumping Arrangements						
•	010 011 01						
٠		NA NA		NA	NA		
				NA	NA		
	 Number of main pumps 	NA		NA	NA		
	- Jockey pump out put	NA		NA	NA		
	Jockey pump headStandby Pump out put	NA		NA NA	NA NA		
4	11 D TT 1	NA NA		NA	NA		
2		NA		NA	NA		
Auto Staring/Manual stopping							
4		NA M		NA	NA		
•	Terrace level						
2	0 1 1			900 LPM + 180LPN			
>		Required		40 mtr	MR		
	Power supply	•		Provided	MR		
	Auto starting of pump	Required		Provided	MR		
. (Captive water Storage for fire I	The second			-		
	• Under ground tank capacity	NA		NA	NA		
 Draw of connection Fire service inlet 		NA NA		NA	NA		
				NA	NA		
	Access to tank	NA		NA	NA		
	Overhead Tank capacity	15,000 ltr		15,000 ltr	MR		

15	Exit Signage	Required		Provided	MR		
16.	Provision of Lifts						
	 Pressurization of Lift Shaft 	NR		NR	NR		
	 Pressurization of lift lobby 	NR	×	NR	NR		
	 Communication in lift Car 	NR		NR	NR		
	 Fireman's Grounding Switch 	NA		NA	NA		
	Lift Signage	NR		NR	NR		
17.	Standby power supply	NA		NA	NA		
18.	Refuge Area						
	Total area	NR		NR	NR		
	> Location	NR		NR	NR		
19.	Fire control room						
	Detector system panel	NR	٦.	NR	NR		
	Flow Switch Panel	NR	٢	NR	NR		
	PA System Panel	NR	Ν	NR	NR		
	 Battery backup 	NR	Ν	IR	NR		
	 Building Floor Plans 	NR	N	IR	NR		
20.	Special Fire Protection Systems for Protection of special Risks, if any;	Required	Two ABC type (5kg) fire extinguishers & 4 fire bucket with dry sand & stand provided near electrical panel			MR	

General requirements for schools as per NBC (Part-IV) / DOE Cir. Dated 01/03/2011.

- 1. Escape route:- Clear
- 2. LPG cylinders in laboratories :- Nil
- 3. Electric wiring- Conduit Wiring MCB and ELCB..... Electric circuit- MCB Provided
- 4. Electric meter board / switch board panel .:- Not Under the staircase
- 5. Basement use as per BBL 1983 :- N/A
- 6. Emergency telephone no. board :- Displayed
- 7. Generator set :- at the terrace

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS/MS/School/2018/SZ/863 dated 27/04/2018 renewal under rule 35 of the Delhi Fire Service rules 2010.

Signature of the Inspecting Officer : Ashok Kumar Jaiswal Name Designation : A.D.O. (S.J.)

F.T. is added for