GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/Indl./2021/WZ/ 479

Dated: 0 / / 0 / 2021

FIRE SAFETY CERTIFICATE

Issued 0/1/0/2021 at New Delhi by

(Dharampal Bhardwaj)
Dy. Chief Fire Officer
West Zone

Copy to: -

1. Micro Footwears Pvt. Ltd., Plot no. C-2, Udyog Nagar, Rohtak Road, New Delhi-41

2. The Executive Engineer (Bldg.), NDMC, Civic Centre, Minto Road, New Delhi-110002.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

-		INSP	ECTION REPORT	CO III	Negan	
1 Name & Address of the Building Micro Footwears Pvt. Ltd., Plot no. C-2, Udyog						
			Rohtak Road, New De			
2	Туре	of Occupancy	Group-G (Industrial)			
		ding Comprised of	Basement + Ground f	loor		
1	Type	of Case	Renewal	10/1470 1 4 1 22/06/2	019	
5	Deta	ils of Previous NOC	F.6/DFS/MS/Indl./20			
6	Fire	Safety Directives Letter No	F.6/DFS/MS/BP/2000	0/828 dated 09/05/200	0	
		of Inspection	21/09/2021			
8	Name of the Inspecting Officers Name & Designation of Officers from the building side		ADO Aman Kumar Lathar Mr. Dube (Plant Head)			
9						
9						
0		r of construction	2000	A		
	Applicant letter No.		Email dated 15/09/2021			
11			BBL/NBC	Provided at Site	Remarks	
S.	Mir	imum standards on Fire	Requirement	1 Toyland at Site	MR/NMR	
No	_	vention and Fire Safety U/R 33	Requirement		14	
1		ess to Building. Road width	06 m	06 m	MR	
				5 m	MR	
		Gate widthWidth of internal road	5 m	-N/A-	-N/A-	
			-N/A-	-IN/A-	-1 1/11	
2	Nu	mber, width, type & arrangement	of exits.		*.	
	a)	Number of Staircase	-	NT/A :	-N/A-	
		> Upper floors.	-N/A-	-N/A-		
	1	Basement floor.	2 nos	04 nos	MR	
	b)	Width of Staircase			112-21	
	0)	> Upper floors	-N/A-	-N/A-	-N/A-	
		Basement floor	Old case	1.75 m × 4	MR(old case)	
			Old case	1.10	11111(0101010)	
	c)	Protection of exits		NI/A	-N/A-	
	11	> Fire check door	-N/A-	-N/A-		
		> Pressurization	-N/A-	-N/A-	-N/A-	
	d)]	No. of continuous staircase to	-N/A-	-N/A-	-N/A-	
	terrace				27/4	
	e) 1	Width of corridor	-N/A-	-N/A-	-N/A-	
	0		1.20 m	1.50 m	MR	
	/	Door size	1.20 111	1.30 111		
3	Co	ompartmentation.	-N/A-	-N/A-	-N/A-	
		• Fire check door.		-N/A-	-N/A-	
		• Sealing of electrical shafts.	-N/A-	-N/A-	-N/A-	
		• Fire rating of shaft door.	-N/A-	-N/A-	-N/A-	
		Water curtain	-N/A-	-N/A-	-N/A-	
		• Fire dampers	-11/11-	1.1/4.4		
4.	Sı	moke Management system.	D ' 1	Provided	MR	
		Basement	Required		MR	
		Upper floors	Required	Provided	IVIIV	
5.	F	ire Extinguishers.	· .		1.00	
		Total numbers	15 nos	30 nos	MR	
	4	• Types	WCO ₂ /CO ₂ /DCP	Provided	MR	
		ISI Marking	ISI marked	Provided	MR	
	117	irst Aid Hose Reels.		,		
6.	·		2 nos	02	MR	
16		Total numbers on each floor		30 m	MR	
		• Length of hose-reel hose.	30 m	5 mm	MR	
		Nozzle Diameter	5 mm	5 mm	VIK	

•	Type of detectors	-N/A-	-N/A-	-N/A-			
	 Location of Main Panel 	-N/A-	-N/A-	-N/A-			
	Location of Repeater Panel	-N/A-	-N/A-	-N/A-			
	Alternate source of power	-N/A-	-N/A-	-N/A-			
	Hooter's location	-N/A-	-N/A-	-N/A-			
8.	MOEFA	-N/A-	Provided	-N/A-			
9.	Public Address System	-N/A-	-N/A-	-N/A-			
10.	Automatic Sprinkler System						
	• Basement.	Required	Provided	MR			
	 Ground & Above floors 	-N/A-	-N/A-	-N/A-			
	 Sprinkler above false ceiling 	-N/A-	-N/A-	-N/A-			
11.	Internal Hydrants.	_					
	Size of Riser / Down-comer	100 mm	100 mm	MR			
	 Number of Hydrant per floor 	2	2	MR			
	Hose box.	2	2	MR			
12.	Yard Hydrants						
	Total number of hydrants	4	4	MR			
	 Hose box 	4	4	MR			
13.	Pumping arrangements.						
	Ground Level						
	Discharge of main pump.	Not mentioned in guidelines	2280 LPM	MR			
	Head of main pump.	Not mentioned in guidelines	60 MH	MR			
	Number of main pumps.	1	1	MR			
	> Jockey Pump output.	-N/A-	-N/A-	-N/A-			
	Jockey Pump head.	-N/A-	-N/A-	-N/A-			
	Standby Pump output.	-N/A-	-N/A-	-N/A-			
	Standby Pump head.	-N/A-	-N/A-	-N/A-			
	Auto Starting/ManualStopping.Pump house access	Required	Provided	MR			
		Required	Provided	MR			
	•	Required	Tiovided	IVIIC			
	 Terrace Level Discharge of pump. 	Not mentioned in guidelines	900 LPM	MR			
	Head of pump.	Not mentioned in guidelines	40 MH	MR			
	Power supply.	Required	Provided	MR			
	Auto starting of pump.	Required	Provided	MR			
14.	Captive water storage for firefighting						
A F1	Underground tank capacity.	1,00,000 ltrs	1,00,000 ltrs	MR			
	> Draw-off connection.	NR	Provided	NR			
	Fire Service Inlet.	NR	Provided	NR			
	Access to tank.	Required	Provided	MR			
	Overhead tank capacity.		DO 120100 1, 101000 0 000	MR			
1 =		25,000 ltrs	25,000 ltrs Provided	MR			
15.	0 0	Required	riovided	IVIK			
16.		-N/A-	-N/A-	-N/A-			
	Pressurization of lift shaft.						
	Pressurization of lift lobby.	-N/A-	-N/A-	-N/A-			
	Communication in lift car.	-N/A-	-N/A-	-N/A-			
	• Fireman's switch.	-N/A-	-N/A-	-N/A-			
1	• Lift signage.	-N/A-	-N/A-	-N/A-			

17	Standby Power Supply	Required	Provided	MR		
18.	Refuge Area					
	Total area	-N/A-	-N/A-	-N/A-		
	Location	-N/A-	-N/A-	-N/A-		
19.	Fire Control Room.					
	Detector System Panel.	-N/A-	-N/A-	-N/A-		
	Flow Switch Panel.	-N/A-	-N/A-	-N/A-		
	• PA system Panel.	-N/A-	-N/A-	-N/A-		
	Battery backup	-N/A-	-N/A-	-N/A-		
	Building floor plan	-N/A-	-N/A-	-N/A-		
20.	Special Fire Protection System for the Protection of special Risk, if any.	At DG set,/Foam fire extinguisher required	Provided	MR		

The fire protection system provided in the building were randomly tested/ checked and found functional at the time of inspection.

The shortcoming issued by this department vide letter No. F/6/DFS/MS/WZ/2021/1479 dated 29/07/2021 has been compiled by the building management.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no. F.6/DFS/MS/Indl./2018/1472 dated 22/06/2018, renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

23/09/21

Signature of the Inspecting Officer

Name : Aman

: Aman Kumar Lathar

Designation:

ADO (JWP)

DO (WD)

DOR (WZ)

28/9/2021

PRO Jul

F. T. Letter is put-up for rignature 101

ACFO (WZ)

1508 9 8021

AM (WI)

mes cill