

# **GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI** HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2021/ 448

Dated: 30/. 8.... 2021

#### FIRE SAFETY CERTIFICATE

Certified that the Sunrise Dx. Guest House located at 3738. Street Ram Nath Patwa, Pahar Ganj, New Delhi comprised of Basement + Ground + 04 Upper floors. Basement (Storage), Ground floor (02 guest rooms + reception), 1st floor to 3rd floor (05 guest rooms at each floor) and 4th floor (staff room sealed by MCD), total 17 guest rooms owned/occupied by Sunrise Dx. Guest House was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/ NDZ/2018/1962 dated 27/08/18. Now, the premise was re-inspected by the officer concerned of this department on 22/09/21 in the presence of Sh. Sheelu Babu and found that the said guest house building having given an affidavit dated 16.10.19 regarding not to use any floor above third floor has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules. 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (02 guest rooms + reception), 1st floor to 3rd floor (05 guest rooms at each floor) total - 17 guest rooms unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 30/9/2 (at New Delhi by.

(Dr. S.K.Tomar) Dy. Chief Fire Officer Delhi Fire Service

### Copy to:-

1

- 1. The Commissioner, North MCD, Civic Centre, New Delhi: to ensure the occupancy in the building as detailed above.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID No. 2021082018418 dated 20.08.21.
- 3. The Manager, Sunrise Dx. Guest House at 3738, Street Ram Nath Patwa, Pahar Ganj, New Delhi.

#### Condition for the validity of fire safety certificate

- 1. This clearance/ FSC shall stand cancelled if guest house owner/occupier fails to comply all other conditions mentioned in the gazette notification dated 27.05.2019 & clarification issued on dated 29.06.2021 latest by 30.09.2021
- 2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

M1-30

## INSPECTION REPORT

1. Name & address of the building

Sunrise Dx. Guest House at 3738, Street

Ram Nath Patwa, Pahar Ganj, New Delhi

2. Type of occupancy:-Residential, Sub Division-A-1

B + Gr. + 04 Upper floors (total 17 Guest rooms) Basement (storage), Ground floor (02 guest rooms + reception), 1<sup>st</sup> floor to 3<sup>rd</sup> floor (05 guest rooms at each floor) and 4<sup>th</sup> floor

(staff room sealed by MCD) and not in use as per affidavit dated 16.10.19 given by owner

3. Type of case:-

4. Details of previous FSC:-No. F6/DFS/MS/GH/NDZ/2018/1962 dated

27/08/18.

5. Fire safety directives No.-

N/A

Date of inspection:-

22/09/21

7. Name of the inspecting officer:-

Sh. Ravinder Singh (ADO/CC)

Sh. Rajinder Atwal DO (CD)

8. Name & designation of officer From the building side: -

Sh. Sheelu Babu

9. Year of construction: -

2000

10. Applicant's letter No: -

ID No. 2021082018418 dated 20.08.21.

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR		
1.	Access to Building					
	1) Road width	N/A	06 mtr.	N/A		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Ar					
	A. Number of staircases					
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	02 Nos.	02 Nos.	MR		
	B. Width of staircase					
	1. Upper floors	0.80 mtr.	1.23 mtr.	MR		
	2. Basements	0.80 mtr.	0.80 to 1.20 mtr. & 0.83 mtr.	MR		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase to terrace	01	01	MR		
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	01 mtr.	01 mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
- Inches	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
	Smoke Management System					
	1) Basements	30 ACPH	Exhaust fan	MR		
	2) Upper floors	Required as per G.N dated 27.05.19	Not provided	Last dt. 30.09.21 of compliance extended vid order dt. 29.06.2021		

#31

1.

	- 4				
Fire Extinguishers		12 Nos.	MR		
1) Total numbers	12 Nos.		MR MR		
2) Types					
3) ISI marking	Required	Provided	- IVIK		
First-Aid Hose Reel		0.1	MR		
1) Total number of eachfloor			MR		
2) Length of hose reel hose	30 mtr.		MR		
3) Nozzle diameter	05 mm		IVIK		
Automatic Fire Detection & Alarming System  Last dt.					
1) Type of detectors CO type	Required as per G.N dated 27.05.19	Not provided	30.09.21 of compliance extended vid order dt. 29.06.2021		
2) Location of main panel	N/A	N/A	N/A		
	N/A	N/A	N/A		
	N/A	N/A	N/A		
	N/A	N/A	N/A		
	N/A	N/A	N/A		
1 2 3 2 4 1 1 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2	A10471 (V 111)	Provided	MR		
1		Provided	MR		
	N/A	N/A	N/A		
3) Sprinkler above false	N/A	N/A	N/A		
Internal Hydrants					
1) Size of riser/down-comer	N/A	N/A	N/A		
2) Number of hydrants per floor	N/A	N/A	N/A		
3) Hose box	N/A	N/A	N/A		
Yard Hydrants					
1) Total number of hydrants	N/A	N/A	N/A		
2) Hose box	N/A	N/A	N/A		
Pumping Arrangement					
Ground level	N/A	N/A	N/A		
a) Discharge of main	N/A	N/A	N/A		
pump					
b) Head of main pump	N/A	N/A	N/A		
	N/A N/A	N/A N/A			
b) Head of main pump			N/A		
<ul><li>b) Head of main pump</li><li>c) Number of main pump</li></ul>	N/A	N/A	N/A N/A		
<ul><li>b) Head of main pump</li><li>c) Number of main pump</li><li>d) Jockey pump out put</li></ul>	N/A N/A	N/A N/A	N/A N/A N/A		
<ul><li>b) Head of main pump</li><li>c) Number of main pump</li><li>d) Jockey pump out put</li><li>e) Jockey pump head</li></ul>	N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A		
<ul> <li>b) Head of main pump</li> <li>c) Number of main pump</li> <li>d) Jockey pump out put</li> <li>e) Jockey pump head</li> <li>f) Stand by pump output</li> </ul>	N/A N/A N/A N/A	N/A N/A N/A	N/A N/A N/A		
b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A		
b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A		
b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump	N/A N/A N/A N/A N/A N/A 450 LPM	N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A		
b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A		
	2) Types 3) ISI marking First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & 1) Type of detectors CO type  2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Yard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main	2) Types 3) ISI marking  First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter  Automatic Fire Detection & Alarming Syst 1) Type of detectors CO type  2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location  MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box V/A Vard Hydrants 1) Total number of hydrants 1) Total number of hydrants 1) Total number of hydrants 1) Ground level a) Discharge of main N/A	1) Total numbers		

14.	Captive Water Storage for Fire Fighting					
	Under ground tank capacity	N/A	N/A	N/A		
	<ul> <li>a) Draw-off connection</li> </ul>	N/A	N/A	N/A		
	<ul> <li>b) Fire service inlet</li> </ul>	N/A	N/A	N/A		
	c) Access to tank	N/A	N/A	N/A		
	<ul> <li>d) Over head tank capacity</li> </ul>	2500 ltr.	2500 ltr.	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.					
	<ul> <li>a) Pressurization of lift shaft</li> </ul>	N/A	N/A	N/A		
	<ul> <li>b) Pressurization of lift lobby</li> </ul>	N/A	N/A	N/A		
	<ul> <li>c) Communication in lift car</li> </ul>	N/A	N/A	N/A		
	d) Fireman's switch	N/A	N/A	N/A		
	e) Lift signage	N/A	N/A	N/A		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	N/A		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	N/A		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A		
	e) Building floor plan	N/A	N/A	N/A		
0.	Special Fire Protection System Risk, if any:	n for Protecti	ion of special	N/A		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2018/NDZ/1962 dated 27/08/18, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended upto third floor only.

Signature of the Inspecting Officer

Name :- Rajinder Atwal

Designation :- Do /CD

Signature of the Inspecting Officer

Name :- Ravinder Singh

Designation :- ADO (CC)

d Signa mit Meale , ),