## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/2021/SZ/ Pall 472

Dated: 28/08/2024

## FIRE SAFETY CERTIFICATE

Certified that the Prem Service Station (Retail outlet of B.P.C.L. Petroleum Class A & B located at J.B. Tito Marg, Andrews Ganj, New Delhi-110049, comprised of Ground Floor only owned / occupied by M/s Prem Service Station, was earlier issued Fire Safety Certificate vide letter No. F6/DFS/MS/2018/SZ/1660 dated 16/07/2018.The premises was re-inspected by the officer concerned of Fire Service on 18/09/2021 in the presence of Sh. Rajiv Sethi (Partner) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Mixed" (Petrol Pump & Service Station) with effect from 28/09/2021 for a period of 3 (three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 28 09 2021 at New Delhi by.

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER (S.Z.).

Copy to :-

- 1. Territory Manager (Retail), B.P.C.L., Bijwasan Installation, Bijwasan, New Delhi-110061.
- 2. Sh. Rajiv Sethi (Partner), Prem Service Station (Retail outlet of B.P.C.L. Petroleum Class A & B at J.B. Tito Marg, Andrews Ganj, New Delhi-110049.

## Conditions for the validity of Fire Safety Certificate:-

- 1. "No Smoking" and "Not to use Mobile Phone" sign board should be displayed in such a manner as to be easily readable by all persons.
- 2. No trade Susceptible to Cause Ignition Petroleum vapors by generating heat, mechanical / electric spark should be allowed within the premises and its vicinity.
- 3. 04 no's of CO2 gas type ISI capacity of 4.5 kg, 02 no's of ABC stored pressure power type ISI capacity 05kg and 01 numbers of AFFF type ISI capacity 50 ltrs provided should be maintained in proper working order all the time.
- 4. The working employed at the petrol pump must be taught the correct method of operation and maintenance of record of the extinguishers be ensured.
- 5. Overhead electric cable not passing across the licensed premises.
- 6. Work under procurement / installation mentioned in the undertaking shall be complied before the commencement of the plant. The same shall be get inspected from OISD under intimation to this department.
- "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".

1. N	ame & address of the	building : M/s Prem Ser	vice Station (Retai	loutlet of	В.	
0	L. Petroleum Class	A & B at J.B. Tito Mar	g, Andrews Ganj,	New Delh	1-1-54	
	ype of Occupancy	Mixed Occupa	: Mixed Occupancy (Petrol Pump & Service Stati : Renewal (Ground Floor only) : F6/DFS/MS/2018/SZ/1660 dated 16/07/2018 : NBC (Part-IV) : 18/09/2021			
3. T	ype of Case	: Renewal (Gro				
4. D	etails of previous NO	C F6/DFS/MS/20				
5. F	ire Safety directives L	etter No. : NBC (Part-IV)				
6. D	ate of inspection	: 18/09/2021				
7. N	ame of the Inspecting	Officer : A.D.O. (S.J.)				
8. N	ame and designation	of Officer				
fi	om the building side	: Sh. Rajiv Sethi	(Partner)			
9. 1	ear of construction	: 1965		-1.67/00/20	171	
10. A	pplicant's letter receiv	ed through email ID-prembp	cl@hotmail.com date	Remark	1 1 1	
S.	Minimum standards		Provided at	MR/NN		
No	prevention and fire s	safety Requirements	site	INTRO INT	41 I.	
	U/R 33					
1.	Access of building		10	MR		
	<ul> <li>Road width</li> </ul>	Required	12 mtr	NA		
	<ul> <li>Gate width</li> </ul>	NA	NA	NA		
	Width of inte		NA			
2.		e & Arrangements of exits	5			
	a. Number of s	and the second design of the second design of the second second second second second second second second second	1	MR		
	<ul> <li>Upper floors</li> </ul>		NA	NA	pendigian	
	<ul> <li>Basements</li> </ul>	NA	INA			
	b. Width of stai		0.90m	MR		
	<ul> <li>Upper floors</li> </ul>		NA	NA	1000000	
	Basements	NA				
	c. Protection of		NA	NA		
	<ul> <li>Fire check do</li> </ul>		NA	NA		
	<ul> <li>Pressurizatio</li> </ul>		NA	NA		
	d. No of contin		N/A			
	e. Width Of Co		NA	NA		
		1.00 mtr	1.00 mtr	MR		
3.	Compartmentation	oor N/A	N/A	N/A		
	Fire check do		N/A	N/A		
	<ul> <li>Sealing of ele shafts</li> </ul>					
	• Fire Rating of s		N/A	N/A		
	Water Curtai		N/A	N/A		
	Fire Damper	s N/A	N/A	N/A	and the second second	
4.	Smoke management	s System				
	<ul> <li>Basements</li> </ul>	NA	NA	NA		
	Upper floors	NA	NA	NA	1979-1980-1970	
5.	Fire Extinguishers					
	fotal number	rs Required	2 CO, DCP	con conce	MF	
			16 fire buck	16 fire buckets		
	• Types	ABC/DCP/ C	O <sub>2</sub> Provided	1	MF	
	ISI marking	Required	Provided	1	MF	
		10				

. .

			A1/10				
6.	First - Aid Hose Reels	an a					
	Total numbers on each floor	NA	NA	NA			
	Length of hose reel	NA	NA	NA			
	hose     Nozzle diameter	NA					
7	A		NA	NA			
	Automatic fire detection and alarming system						
	Type of detector     Location of Main	NA	NA	NA			
	Panel	NA	NA	NA			
	<ul> <li>Location of Repeater Panel</li> </ul>	NA	NA	NA			
	<ul> <li>Alternate source of power</li> </ul>	NA	NA	NA			
	<ul> <li>Hooters' Location</li> </ul>	NA	NA	NA			
8	MOEFA	NA	NA	NA			
9	Public Address System	N/A	N/A	N/A			
10.	Automatic Sprinkler System						
	Basements	NA	NA	NA			
	Upper Floor	NA	NA	NA			
	<ul> <li>Sprinkler above false</li> </ul>	NA	NA	NA			
	ceiling						
11.	Internal Hydrants	-		L			
	<ul> <li>Size of riser/down- comer</li> </ul>	NA	NA	NA			
	<ul> <li>Number of hydrants per floor</li> </ul>	NA	NA	NA			
	Hose Box	NA	NA	NA			
12.	Yard Hydrants						
7. 54.7	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13.	The second se		andan manunu any mananany na kaominina many minany minany amin' amin' amin' amin' amin' amin' amin' amin' amin'	a the same of the second s			
	Ground Level						
	Discharge of main pump	N/A	N/A	N/A			
	<ul> <li>Head of main pump</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Number of main pumps</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Jockey pump out put</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Jockey pump head</li> </ul>	N/A	N/A	N/A			
4	<ul> <li>Standby Pump out put</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Standby Pump Head</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Auto Staring/Manual stopping</li> </ul>	N/A	N/A	N/A			
•	Pump House Access     Ierrace level	N/A	N/A	N/A			
	<ul> <li>Discharge of pump</li> </ul>	NA	NA	NA			
	<ul> <li>Head of the pump</li> </ul>	NA	NA	NA			
	<ul> <li>Power supply</li> </ul>	NA	NA	NA			
,	<ul> <li>Auto starting of pump</li> </ul>	NA	NA	NA			
14.	Captive water Storage for fire fighting						
	<ul> <li>Undergrowind (ank capitality)</li> </ul>	NA	NA	NA			
	> Draw of connection	NA	NA	NA			
	<ul> <li>Fire service inlet</li> </ul>	NA	NA	NA			
	<ul> <li>Access to tank</li> </ul>	NA	NA	NA			
	Overhead Tank	NA	NA	NA			
	capacity		chal				

P.

-

a de la compañía de la		Alt	1)			
15	No Smoking Signage English		uired	Provided	MR	
	& Hindi			English & Hindi		
16.	Provision of Lifts					
	Pressurization of Lift S	Shaft	N/A	N/A	N/A	
	<ul><li>Pressurization of lift lobby</li><li>Communication in lift Car</li></ul>		N/A	N/A	N/A	
			N/A	N/A	N/A	
	<ul> <li>Fireman's Grounding Switch</li> </ul>		N/A	N/A	N/A	
	Lift Signage		N/A	N/A	N/A	
17.	Standby power supply	andby power supply		NA	NA	
18.	Refuge Area		N/A	N/A		
	Total area		N/A	N/A	N/A	
	Location		N/A	N/A	N/A	
19.	Fire control room					
	▶ Detector system panel         N/A           ▶ Flow Switch Panel         N/A           ▶ PA System Panel         N/A			N/A	N/A	
				N/A	N/A	
				N/A	N/A	
	Battery backup	N/A		N/A	N/A	
	Building Floor Plans		N/A N/A		N/A	
20.	Special Fire Protection				NA	
	Systems for Protection of					
	special Risks, if any;					

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS/MS/2018/SZ/1660 dated 16/07/2018 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

20/09/2021

09/2011

Signature of the Inspecting Officer Name : Ashok Kumar Jaiswal Designation : A.D.O. (S.J.)

ADDLED F.T. is added for sep. Sf.