

No.F.6/DFS/MS/EH/2021/SZ/ 2-65

Dated: 30 | 9 / 2 |

FIRE SAFETY CERTIFICATE

Certified that the M/s Haritima Restaurant (Naagar Infrastructure Pvt. Ltd.) at Delhi Tourism N Trans Development Corporation Ltd, Tourist Complex, Kaganheri,, New Delhi-110088, owned/occupied by Naagar Infrastructure Pvt. Ltd. have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and verified by the officer concerned of this department on 17/09/2021 in the presence of Mr. Dilip Nagar (owner) and found that the building is fit for occupancy 'Group D "Assembly Building" (Restaurant) with effect from 3/9/21 for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010,

Issued on at New Delhi by

(Atul Garg) Director

Delhi Fire Officer

To.

The Manager, M/s Haritima Restaurant (Naagar Insfrastructure Pvt. Ltd.) at Delhi Tourism N Trans Development Corporation Ltd, Tourist Complex, Kaganheri, New Delhi-110088

Copy to:-

The Joint Commissioner of Police, Licensing Unit, First Floor, Police Station, Defence Colony, New Delhi.

Following fire safety directives must be adhered to:-

- This NOC is valid only for ground floor.
- The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- All the means of escape shall be kept free of all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be
- The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc may be got verified from the authorities concerned.
- This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year, in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

	Ī	NSPE(CTION REPORT		
1. Na	ame & address of the building			ant (Nagar Insfrastruct	ure Pvt. Ltd.)
	_			anss Devlopment Corp	
				anheri,, New Delhi-11	
2. B	uilding is comprised of		ound floor only	amien, new benn-11	0000.
	ype of Occupancy		•		
	ype of Case		sembly (Restlin)		
-	etails of Previous NOC	: Ne			
	re Safety direction letter No	: Nil			
	ate of Inspection	: Ni			
	•		09/2021		
0. IN	ame of the Inspecting Officers:	: R.I	K. Yadav (ADO)		
	ame of the designation of Officer	•	,		
	om the building side		Dilip Nagar (Owne	er)	
	Year of Construction	: 2014			
	pplicant's letter No		ine application 202		D 1
S.No	Minimum Standards on fire	safety	Requirement	Provided at Site	Remarks
	requirements		i		MR/NMI
1	Access to building			•	
	Road width		06 m	Provided	MR
	Gate width		N.A	N.A.	N.A.
	Width of internal road	•	N.A	N.A.	N.A.
2	Number, Width, Type and Arran	gement	t of Exits.		
	a. Number of Staircases	5			
	Upper Floor		N.A	N.A.	N.A.
	Basement		N.A	N.A.	N.A.
	B. Width of Staircases	·	,	11.11.	
۶,	Upper Floor		N.A	N.A.	N.A.
	Basement	4.	N.A	N.A.	N.A.
	c. Protection of exits		IV.A	IV.A.	IN.A.
	Fire check door		N.A	N.A.	N.A.
	Pressurization		N.A	N.A.	
	e. No. of continuous staircases to		N.A *		N.A.
	terrace	_		N.A.	NA.
	g. Width of Corridor		N.A	N.A.	N.A.
	h. No. of door	-	2 no.	2 no.	MR
	Door Size	M	2 m 1.5 each	2 m & 1.5 m	MR
3	Compartmentation.	1/2	/ 200		
,	Fire check door		NI A	NT 4	
			N.A .	N.A.	N.A.
	Sealing of electrical shafts		N.A	N.A.	N.A.
	Fire rating of shaft door		N.A	N.A.	N.A.
	Water curtain	4.	N.A.	N.A.	N.A.
	Fire Dampers		N.A.	N.A.	N.A.
	Smoke Management System.			- · · · · · · ·	IN.A.
	Basement		N.A	N.A.	3.4
	Upper floor	<u></u>	N.A		N.A.
	Fire Extinguisher			N.A.	NA.
	Total numbers	•	0.1		
		-	04 no.	04 no.	MR
	types	-	ABC & CO ₂	ABC & CO ₂	MR
	ISI marking		ISI marked	ISI marked	
					MR

à		
A		3
		Aller .
	- 3	

				1
6 First and Hose Reels				
Total numbers of each floor	01 no	Ol no	MR	1
Length of hose reel hose	4. 10 m	10 m	MR	L .
Nozzle diameter	d tatian	mm ?	MR	1
Automatic fire detection and alarm	ning system			
Type of detectors	NA	NA	NA	
Location of main panel	NA .	N A	NA	
Location of repeater panel	NA .	NA	NA	
Alternate source of power	NA .	NA	NA	
	N.A.	NA	NA	
Hosters	· · ·	7 2	1.60	
S MOETA	Required	Provided	MR	
Public address System	NA	NA	N.A.	
10 Automatic Sprinkler System				
 Basement 	N A	N A	N A	
upper floor	6. A	NA	N A	
sprinkler above false ceiling	NA	N A	N.A.	
11 Internal Hydrants		rough to the forest of	MD	
size of riser/down-comer	100 mm	100 mm	MR	
Number of hydrants each floor	l no	l no	MR	
Hose box each floor	1 no	lno	MR	
12 Yard Hydrants		VII. 1		
Total number of hydrants	A A	NA.	NA	
Hose Box	NA	, N.A	NA	
13 Pumping Arrangements				
Ground Level	A A	, NA	NA	
Discharge of main Pump	, , , , ,	NA ,	NA	
Head of Main Pump	N A	NA.	NA	
Number of main pumps		· A	NA -	
Jockey pump out put		. ` A	14	
Jockey pump head	\ A	\ A	NA	
Standby pump out put	1 -1		24	
Standby pump Head	1.1	. A.A.	1.1	
 Auto Starting (Manual) 	N.A	1	11	
stopping	N	14	11	
Pump House Access				
Terrace Level	dest PM	450 LPM	MK	
Discharge of pump	40 1	40 M	MR	
Head of the Pump	Required	Provided	MR	
Power supply	Required	Provided	MR	
Auto Starting of pump	regardea.	E 1519 HJ 634	(AT1.0"	
The second second the second s				
4 Captive Water Storage for the Light	T.M.			
Underground tank capacity	7 A	A	1	- 441
Draw-off connection	1.1	NA .	11	
Fire service inlet	N.A.	11	1.1	
Access to tank	NA	1.1	1.1	
Overhead Fank capacity	20,0004 iters	20,000 Liters	MR	
15 Exit Signage	Required	Provided	MR	
E (II DIROND)	A 200 SA 50			

16	Provision of Lifts.					
	Pressurization of Lift Shaft Pressurization of Lift lobby Communication in lift car	N.A	N.A.	N.A.		
		N.A	N.A.	N.A.		
		N.A	N.A.	N.A.		
	Firemen's grounding switch	N.A	N.A.	N.A.		
	Lift Signage	N.A	N.A.	N.A.		
7	Standby power supply	N.A	N.A.	N.A.		
18	Refuge Area.					
	Total area .	N.A	N.A.	N.A.		
	Location	N.A.	N.A.	N.A.		
19	Fire Control Room					
	Detector system panel	N.A	N.A.	N.A.		
	Flow switch panel	N.A	N.A.	N.A.		
	PA system panel	N.A	, N.A.	N.A.		
	Batter backup	N.A	N.A.	N.A.		
	Building Floor Plans	N.A	N.A.	N.A.		
20	Special Fire Protection systems for protection of special Risks, if any:	N.A	N.A.	N.A.		

(1) The total covered area of the ground floor restaurant is 200 sq. meters (Approx.) including sitting area, toilet area, kitchen area.

(2) As per the NBC Part –IV, the number of occupants comes out to be approx 111 persons i.e (200/1.8=111)

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name :-R.K.Yadav Designation:-ADO (JKP)

DO (South West)

By cho (\$2)

0/0

21/8

P/c 8/5K.

Due Nor Fire City