## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

<u>NEW DELHI</u>

No. , /DFS/MS/School/WZ/2021/ 806

## FIRE SAFETY CERTIFICATE

Certified that the Govt. Sarvodaya Co-ed. Sr. Sec. School (ID-1411123), Located at C-Block, Saras ati Vihar, Delhi-110034, comprised of Three Blocks (Ground + 01 Upper Floor) was issued Fire afet Certificate by this department Vide Letter No. F6/DFS/MS/School/2018/WZ/2027 dated 04.09.2018. Management has constructed a M. P. Hall & have complied with the fire prevention and fire safety requirements in accordance D.O.E Cr. No. 3298 to 3398 dated 01.03.2011 and Verified by the officer concerned of Fire Service on 21.09.2021 in the presence of Sh. R.K. Sharma (HOS), and that the premises/building is fit for occupancy class "Educational" Group B (Three Blocks - Ground + 01 Upper Floor & M. P. Hall) with effect from  $\underline{\Lambda [00] 2.1}$  for a period of three years, subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on  $\dots$  .. .. .. .. .. at New Delhi by



Copy to: -

- 1. The Director, Directorate of Education Old Secretariat, Delhi 110054.
- 2. The Principal, Govt. Sarvodaya Co-ed. Sr. Sec. School (ID-1411123), Located at C-Block, Saraswati Vihar, Delhi-110034.

## Following fire safety directive must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <u>www.dfs.delhigovt.nic.in</u>.
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

C-13

Dated: //٥/2021

## **INSPECTION REPORT**

IA OA!

N-5

- Name and address of the building: Govt. Sarvodaya Co.-ed. Sr. Sec. School (ID-1411123) Located at C-Block, Saraswati Vihar, Delhi-110034.
- 2. Type of Occupancy: Educational 03 blocks (Ground + 01 Upper Floor & a new M.P. Hall 24x48 m)
- 3. Type of Case : Renewal/addition M.P. Hall
- 4. Details of previous NOC : F6/DFS/MS/School/2018/WZ/2027 dated 04.09.2018
- 5. Fire Safety directives Letter No. : D.O.E Circular no.3298-3398 dated 01-03-2011
- 6. Date of inspection : 21.09.2021
- 7. Name of the Inspecting Officer : S.P. Bhardwaj, ADO (WP)
- 8. Name and designation of Officer

from the building side : Sh. R.K. Sharma (HOS)

- 9. Year of Construction : 2015
- 10. Applicant's letter No. : email dated 10.09.2021

S No	prevention and fire safety		101.03	3.2011/letter	Provided at site		arks NMR
_		dated 04.0	9.2018				
1.	Access of building			D 111		(D	
	Road width	Access		Provided		<u>AR</u>	
	• Gate width	Access	able	Provided		MR NA	
	• Width of internal road	· NA		NA	ľ	NA	
2.	Number, width, Type & Arrang	ements of	exits				
	a. Number of staircases						
	• Upper floors	BL(A-	4, B-2	& C-1) 10 r		MR	
	• Basements	NA		NA	1	NA	
	b. Width of staircases						
	• Upper floors	150cm	BL·	-A=6X155 cm -B=2X148 cm -C=1X150 cm	& 1X153	cm	MR
	• Basements	NA		NA		NA	
	c. Protection of exits						
	<ul> <li>Fire check door</li> </ul>	NA		NA		NA	
	<ul> <li>Pressurization</li> </ul>	NA		NA		NA	
	d. No of continuous	01		Provided		MR	
	staircase to terrace						
	e. Width Of Corridor	1.5 m		BL-A=17	70 cm	NA	
				BL-B=22	20 cm		
				BL-C=17	73 cm		
	f. Door Size	1 m	103 o Fran	cm & 116 cm ne)	(Include I	Door	MR
3.	Compartmentation						
	• Fire check door	NA		NA		NA	
	<ul> <li>Sealing of electrical shafts</li> </ul>	NA		NA		NA	
	• Fire Rating of shaft doo	r NA		NA		NA	
	• Water Curtain	NA		NA		NA	
	• Fire Dampers	NA		NA		NA	
4.	Smoke managements System						
	Basements	NA		NA		NA	1
	<ul><li>Upper floors</li></ul>	NA		NA		NA	1

ĩr

ınd

	Fire Extinguishers							
	Total numbers	27 nos		56 nos		MR		
	• Types	ABC &		Provid		MR		
	IS marking	ISI ma		Provid		MR		
	First-Aid Hose Reels			TIOVIC		IVIK		
	• Total numbers on each floo			А	NLA	NIA		
	Length of hose reel hose			A	NA NA	NA		
	<ul> <li>Nozzle diameter</li> </ul>			A		NA		
	Automatic fire detection and alarn	IN	A	NA	NA			
	Type of detectors	NA		<b>N</b> T 4				
	<ul> <li>Location of Main Panel</li> </ul>		NA		NA	NA		
	<ul> <li>Location of Repeater Pane</li> </ul>	NA		NA	NA			
	<ul> <li>Alternate source of power</li> </ul>			NA	NA			
	<ul> <li>Hooters' Location</li> </ul>	NA		NA	NA			
	MOEFA		NA		NA	NA		
			NA	-	NA	NA		
).	Public Address System		NA	<b>\</b>	NA	NA		
/.	Automatic Sprinkler System							
	Basements		NA		NA	NA		
	Upper Floor		NA		NA	NA		
1	Sprinkler above false ceilin	ng	NA	1	NA	NA		
	Internal Hydrants:							
	<ul> <li>Size of riser/down- comer</li> </ul>	_	NA		NA	NA		
	• Number of hydrants per flo	oor	NA		NA	NA		
2	Hose Box		NA	1	NA	NA		
2.	Yard Hydrants							
	<ul> <li>Total number of hydrants</li> </ul>		NA	1	NA	NA		
	<ul> <li>Hose Box</li> </ul>		NA		NA	NA		
	Pumping Arrangements:							
	Ground Level							
	<ul> <li>Discharge of main pump</li> </ul>		NA		NA	NA		
	Head of main pump		NA	A	NA	NA		
	<ul> <li>Number of main pumps</li> </ul>		NA		NA	NA		
	Jockey pump out put		NA		NA	NA		
	<ul> <li>Jockey pump head</li> </ul>		NA		NA	NA		
	Standby Pump out put		NA		NA	NA		
	Standby Pump Head		NA		NA	NA		
	<ul> <li>Auto Staring/Manual stop</li> <li>Pump House Access</li> </ul>	ping	NA		NA	NA		
	<ul><li>Pump House Access</li><li>Terrace level</li></ul>		NA	A	NA	NA		
	<ul> <li>Terrace level</li> <li>Discharge of pump</li> </ul>			,				
	<ul> <li>Discharge of pump</li> <li>Head of the pump</li> </ul>		NA		NA	NA		
	<ul> <li>Power supply</li> </ul>		NA		NA	NA		
	<ul> <li>Auto starting of pump</li> </ul>		NA		NA	NA		
14.			NA	4	NA	NA		
ŧ.	Captive water Storage for firefighting:							
	<ul> <li>Underground tank capacit</li> </ul>	У	NA		NA	NA		
	<ul> <li>Draw off connection</li> </ul>		NA		NA	NA		
	<ul> <li>Fire service inlet</li> </ul>		NA		NA	NA		
	<ul> <li>Access to tank</li> <li>Organization Transmission</li> </ul>		NA		NA	NA		
5	Overhead Tank capacity		N/		NA	NA		
	Exit Signage		NA	4	NA	NA		
6.								
	<ul> <li>Pressurization of Lift Shaft</li> </ul>		NA		NA	NA		
	<ul> <li>Pressurization of lift lobby</li> </ul>		NA		NA	NA		
	Communication in lift Car		NA		NA	NA		
	Fireman's Grounding Swit	NA		NA	NA			
	<ul> <li>Lift Signage</li> </ul>	<ul> <li>Lift Signage</li> </ul>		1	NA	NA		
7.	Standby power supply		N L A		NT A			
8.			NA	1	NA	NA		
υ.	<ul> <li>Total area</li> </ul>		NA		NA	NA		
	<ul> <li>Total area</li> </ul>		INF	۱ I	INA	I INA		



Location	N/	NA NA	NA		
Fire control room					
Detector system	NA	NA	NA		
panel	NA	NA	NA		
Flow Switch Panel	NA	NA	NA		
PA System Panel	NA	NA	NA		
<ul> <li>Battery backup</li> <li>Building Floor Plans</li> </ul>	NA	NA	NA		
<ol> <li>Special Fire Protection Systems for Protection of special Risks, if any;</li> </ol>	NA	NA	NA		

Fire protection systems provided in the building were checked and found functional at the time of inspection.

Note:- Management has constructed a M. P. hall 24x48 m & have provided 08 nos. exit doors 02 m wide each & have complied all fire safety measures.

In view of the substantial compliance of the minimum standards on fire prevention and fire safety requirements as per D.O.E. Circular no. 3298-3398 dated 01.03.2011, grant of Fire Safety Certificate is recommended.

かと

A not WP FT is put up for Signal flue incute Allol 202

Cho (W2)

der

In Atuf 19/201

Direct

hardwaj 2219121