C74

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F6/DFS/MS/GH/2021/ 496

Dated 22/10 / 2021

FIRE SAFETY CERTIFICATE

Certified that the M/s Grand Venizia Guest House located at 6, Bhama Shah Marg, Opp. Kripal Bagh Ashram, Near Model Town, Delhi-110009 comprised of Basement, Ground and three upper floors owned/occupied by Sh. Arpit Bindal was issued fire safety certificate vide letter no. F6/DFS/MS/GH/2018/2263 dated 08.10.2018. The premises was re-inspected by the officer concerned of Fire Service on 12.10.2021 in the presence of Sh. R.D. Gupta and observed that all the fire prevention & fire safety arrangements as provided in the premises found in good working condition The premises have therefore, deemed complied with the requirement under rule 33 of Delhi Fire Service Rules, 2010 and the building is fit for occupancy Class Group A-1 Residential (Rooming & Lodging) for total 65 guest rooms (GF-06, FF-17, SF-23 & TF-19 guest rooms only) with effect from 23 10 2011 for a period of 03 (Three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 22 10 202 at New Delhi by

(Sunil Choudhary)
Dy. Chief Fire Officer
Ph.-011-25156707

Copy to:-

- 1. The Addl. Commissioner of Police/ Lic, 1st Floor, Police Station, Defence Colony, New Delhi.
- 2. The Owner, M/s Grand Venizia Guest House at 6, Bhama Shah Marg, Opp. Kripal Bagh Ashram, Near Model Town, Delhi-110009

Conditions for the validity of Fire Safety Certificate:

1 All the means of escape/entry/exit shall be kept free from any obstruction.

2 All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.

3 All the staff members must know the correct method of operation of firefighting system.

The owner / occupier shall submit a declaration **every year** in **Form "K"** provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on http://delhi.gov.in./wps/wcm/connect/doit fire/FIRE/Home/Forms.

This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.

6 "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

1. N		wn, Delhi-110009.	a Shah Marg Opp. Kirpal					
2 Tv		asement + ground + 03 u	upper floors only)					
	Type of Case : Renewal							
	etails of previous NOC : F6/DFS/MS/GI	H/2017/WZ/1278 Date						
5. Fire Safety directives letter No : NBC Part IV 6. Date of inspection :12.10.2021 7. Name of the Inspecting Officers : ADO (RN) 8. Name and designation of officers from the building side : Sh. Arpit Bind			Basement- Vacant Ground – Reception + Hall+6rooms 1 nd floor- 17 guest room 2 rd floor- 23 guest room					
		ndal (Owner) 3 rd floor – 19 guest room						
9. Y	Vear of Construction : 2010-2017							
10. A	Applicant's letter No. : Online I.D No.	o-2021091621612 dated	1: 22/09/2021					
		NDC / DDI	Provided at site	Remarks				
	Minimum Standards on fire prevention and fire safety U/R 33	NBC / BBL	Flovided at site	MR/NMR				
	Access to building							
	Road width	09m	24 m	MR				
	• Gate width	5m	5m	MR				
	Width of internal road	NA	NA	NA				
	Number, Width, Type & Arrangement of Exits							
	a. Number of staircases							
	Linnar Floors	02	02	MR				
	Upper FloorsBasements	02	02	MR				
	b. Width of staircases	1.50m	1.50m & 1.40m	MR(old case)				
	Upper FloorsBasements	1.50m	1.50m & 1.40m	MR(old case				
. 9	c. Protection of exits	Required	Provided	MR				
	Fire check door	NA	NA NA	NA				
	Pressurization			MR				
	d. No. of continuous staircases to terrace	02	02					
	e. Width of Corridor	1.5m	1.5m	MR				
	f. Door Size	1m	1m	MR				
3	Compartmentation.							
	Fire check door	Required	Provided	MR				
	Sealing of electrical shafts	Required	Provided	MR				
	Fire Rating of shaft door	Required	Provided	MR				
	Water Curtain	NA	NA	NA				
	• Fire Dampers	NA	NA	NA NA				

1-1 Amer 201 2

		10 / 1	D :1.1	100			
	Basements	12 a/c per hour	Provided	MR			
	• Upper floors	12 a/c per hour	Provided	MR			
5	Fire Extinguishers						
	Total numbers	26nos	28nos,	MR			
	• Types	ABC & WCo2	ABC – 18 /Co2- 10	MR			
	ISI marking	Yes	Yes	MR			
6	First-Aid Hose Reels.	1 03	1 05	IVIK			
	Total numbers on each floor	01	01	MR			
	Length of hose reel hose	30m	30m	MR			
	Nozzle diameter	5mm	5mm	MR			
7	Automatic fire detection and alarming system.						
	Type of detectors	Required(carbon	Provided(carbon	. MR			
	Location of Main Panel	monoxide) Required	monoxide) Provided	MR			
	Location of Repeater Panel	NA	NA	NA			
	Alternate source of power						
	Hooters' Location	NA	NA	NA			
		NA	NA	NA			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	NA	NA	NA			
10	Automatic Sprinkler System.						
	Basement	Required	Provided	MR			
	Upper Floor	NA	NA	. NA			
	Sprinkler above false ceiling	NA	NA	NA			
11	Internal Hydrants						
	Size of riser/down-comer	100mm	Provided	MR			
	Number of hydrants per floor	01	01	MR			
	Hose Box	01	01	MR			
12	Yard Hydrants.						
		D :11					
	Total number of hydrantsHose Box	04	Provided	MR			
1.2		04	Provided	MR			
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	1600lpm	1600lpm	MR			
	Head of Main pump	40m	40m	MR			
	Number of main pumps	N/A	N/A	N/A			
	> Jockey Pump out put	N/A	N/A	N/A			
	> Jockey pump head	· N/A	N/A	N/A			
	Standby Pump out put	1600lpm	1600lpm	MR			
	Carrello D. H. J	Toonpin	Tooolpin	1411			

	> Pump House Access					
	Terrace level	900lpm	900lpm	MR		
	Discharge of pump	40m	40m	MR		
	Head of the pump	Required	Provided	MR		
	> Power Supply			MR		
	Auto Starting of pump	Required	Provided	IVIK		
1	Captive Water Storage for firefighting.					
	Underground tank capacity	1,00,000ltr	1,00,000ltr	MR		
	> Draw-off connection	NA	NA	NA		
	> Fire service inlet	NA	NA	NA		
	> Access to tank	NA	NA	NA		
	Overhead Tank capacity	20,000ltr	20,000ltr	MR		
	Exit Signage.	Required	Provided	MR		
5	Provision of Lifts.	1.no Passenger lift				
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication In lift Car	Required	Provided	MR		
	Fireman's Grounding Switch			MR		
	Lift Signage	Required	Provided			
	Bitt Sig.ing	Required	Provided	MR		
7	Standby power supply	Required	Provided	MR		
8	Refuge Area.					
	> Total Area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
9	Fire Control Room					
	Detector System Panel	N/A	N/A	N/A		
	Flow Switch Panel	N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Batter backup	N/A	N/A	N/A		
	Building Floor Plans		<u> </u>	N/A		
		N/A	N/A NA	N/A NA		
0.0	Special Fire Protection Systems for Protection of special Risks, if any:	NA	INA	INA		

Note:- The compliance of the provision contained as per gazette notification no. F.5(189)/AD/LB/2016/4053-67 dated 27.05.2019 has been complied

The fire protection systems provided in the building were tested/ checked and found some in working order at the time of inspection. The observations/ shortcomings issued and communicated vide this department letter of even no. 69 dated 18.01.2021 have been compiled by the management.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 37 of the Delhi Fire Service Rules 2010.

DO(NW) - ON Leave

Signature of the Inspecting Officer
Name: - C.L. Meena