GOVERNMENT OF NATIONAL CAPITALTERRITORYOF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001

No. F6/DFS/MS/DMRC/NDZ/2021/ 5 24

Dated:- 25 /10/2021

FIRE SAFETY CERTIFICATE

(Atul Garg)
Director

Delhi Fire Service

Copy to:-

Mr. Vivek Shrivastava, JGM/E&M-II

Metro Bhawan, Fire Brigade Lane, Barakhamba Road, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building : Laxmi Nagar Metro Station (Line-4) Delhi

2. Type of Occupancy : Assembly Building "Group D-7"

(ground level, concourse level and platform level)

3. Type of Case : Renewal

4. Details of previous FSC/NOC : F6/DFS/MS/09/3823 dated 17/12/2009

5. Fire Safety directives Letter No. : N/A

6. Date of inspection : 07/10/2021

7. Name of the Inspecting Officer : Sh. M.K. Sharma ADO/LN

8. Name and designation of Officer

from the building side : Mr. Vikas Bhardwaj (Manager/Fire) &

Mr. Omkar Kumar (Fire Inspector)

9. Year of Construction : 2009

10 Applicant's letter No. : Email dated 16/09/2021

| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement As per Directive | Provided at site | Remarks MR/NMR |
|-------|--|---|--|-------------------|
| 1. | Access to Building | | | |
| | 1) Road width | 09 mtr. | 20 mtr. | MR |
| | 2) Gate width | N/A | N/A | N/A |
| | 3) Width of internal road | N/A | N/A | N/A |
| 2. | Number, Width Type & Arra | angement of Ex | its | |
| 4. | A. Number of staircases | | | |
| | Upper floors | 2 | | - 4 |
| | 1. Ground to concourse | 05 Nos. | 05 Nos. | MR |
| | 2.Con. to Platform | 04 Nos. | 04 Nos. | MR |
| | Basements | N/A | N/A | N/A |
| | B. Width of staircase | | | |
| | Upper floors | | | |
| | Ground to concourse | 3 no. of 1.8 m 1 no. of 2.0 m &1 no. of 3.4 m | 3 no. of 1.8 m 1 no. of 2.0 m & 1 no. of 3.4 m | MR |
| | | 2 no. of 4.0 m & | 2 no. of 4.0 m & | MR |
| | Con. To Platform | 2 no. of 2.25 m | 2 no. of 2.25 m | IVIIC |
| | 2. Basements | N/A | N/A | N/A |
| | C. Protection of exits | 1 1/1 2 | | |
| | 1. Fire check door | N/A | N/A | N/A |
| | 2. Pressurization | N/A | N/A | N/A |
| | D. No. of continuous staircase to terrace | N/A | N/A | N/A |
| | E. Width of corridor | N/A | N/A | N/A |
| | F. Door size | 2.0 mtr. | 2.0 mtr. | MR |
| 3. | Compartmentation | | | |
| 3. | 1) Fire check door | N/A | N/A | N/A |
| | 2) Sealing of electrical shafts | | N/A | N/A |
| | 3) Fire rating of shaft door | N/A | N/A | N/A |
| | 4) Fire curtain | N/A | N/A | N/A |
| | 5) Fire Dampers | N/A | N/A | N/A |

| 4. | Smoke Management System | | | |
|-----|----------------------------------|-----------------|-------------------|------|
| | 1) Basements | N/A | N/A | N/A |
| | 2) Upper floors | Required | Natural | MR |
| 5. | Fire Extinguishers | | Ventilated | |
| 5. | 1) Total numbers | 32 Nos. | 32 Nos. | MR |
| | 2) Types | ABC & CO2 | ABC & CO2 | MR |
| | 3) ISI marking | ISI marked | ISI marked | MR |
| 6. | First-Aid Hose Reel | 151 markeu | 151 marked | IVIK |
| 0. | 1) Total number of each floor | 02 nos. | 02 nos. | MR |
| | 2) Length of hose reel hose | 30 mtr. | 30 mtr. | MR |
| | 3) Nozzle diameter | 5 mm | 5 mm | |
| 7. | Automatic Fire Detection & | | 3 IIIIII | MR |
| 1. | 1) Type of detectors | Smoke & Heat | Smoke & Heat | MR |
| | 2) Location of main panel | concourse level | Provided Provided | MR |
| | 3) Location of repeater panel | Main entry | Provided | MR |
| | 4) Alternate source of power | Required | Provided | MR |
| | 5) Hooter's Location | Required | concourse level | MR |
| 8. | MOEFA | Required | | |
| 9. | Public Address System | | Provided | MR |
| 10. | Automatic Sprinkler System | Required | Provided | MR |
| 10. | 1) Basement | N/A | N/A | DT/A |
| | 2) Upper floors | N/A N/A | | N/A |
| T T | | | N/A | N/A |
| v. | 3) Sprinkler above false ceiling | N/A | N/A | N/A |
| 11. | Internal Hydrants | | | |
| 11. | 1) Size of riser/down-comer | 150 mm. | 150 mm. | MD |
| | | | | MR |
| | 2) Number of hydrants per floor | 02 nos. | 02 nos. | MR |
| | 3) Hose box per floor | 02 nos. | 02 nos. | MR |
| 12. | Yard Hydrants | | | W 15 |
| | 1) Total number of hydrants | 10 nos | 10 nos | MR |
| | 2) Hose box | 10 nos | 10 nos | MR |
| 13. | Pumping Arrangement | | | 6 |
| 0 0 | 1) Ground level | | | |
| | a) Discharge of main | 1800 LPM | 1800 LPM | MR |
| | pump | | | |
| | b) Head of main pump | 70 mtr. | 70 mtr. | MR |
| | c) Number of main | 1 No. | 1 No. | MR |
| | pump | | | 2 12 |
| | d) Jockey pump out put | 180 LPM | 180 LPM | MR |
| | e) Jockey pump head | 70 mtr. | 70 mtr. | MR |
| | f) Stand by pump output | 1800 LPM | 1800 LPM | MR |
| | g) Stand by pump head | 70 mtr. | 70 mtr. | MR |
| | h) Auto starting/Manual stopping | Required | Provided | MR |
| | 2) Terrace level | | | |
| | a) Discharge of pump | N/A | N/A | N/A |
| | b) Head of pump | N/A | N/A | N/A |
| | c) Power supply | N/A | N/A | N/A |
| | d) Auto starting of | N/A | N/A | N/A |
| | pump | | | |
| 14. | Captive Water Storage for F | ire Fighting | | |
| # 1 | 1) Under ground tank | 50,000 ltrs. | 50,000 ltrs. | MR |
| | | | | |

no

| | capacity | 2 | D 11-1 | MR |
|-----|--|---|----------|-----|
| | a) Draw-off connection | Required | Provided | |
| | b) Fire service inlet | Required | Provided | MR |
| | c) Access to tank | Required | Provided | MR |
| | d) Over head tank capacity | N/A | N/A | N/A |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | | |
| V | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift | Required | Provided | MR |
| | d) Fireman's switch | Required | Provided | MR |
| | e) Lift signage | Required | Provided | MR |
| 17. | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | | | |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection System for Protection of special Risk, if any: | CO2 panel flooding for HT & LT and electrical panel. | Provided | MR |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/NDZ/4024 dated 25/09/2018 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC/NOC issued vide letter no. F6/DFS/MS/ 09/3823 dated 17/12/2009 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma
Designation: - ADO (LN)

Dy. CEO/NDZ

OCHO)