112

FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/EH/2021/SZ/ 3\1

.]

3C

0

ru L1

 Π

d

t

Ī

2

3

Dated: 7 /10 /2021

FIRE SAFETY CERTIFICATE

Certified that the M/s KFC Restaurants (A unit of Sapphire Foods India Pvt. Ltd.), BG-06, Ground Floor, Ansal Plaza, Hudco Place, Andrews Ganj, New Delhi-110049, building comprised of two tier Basements, Ground, Mezzanine plus three upper floors, but restaurant is running at Ground Floor only owned / occupied by (A unit of Sapphire Foods India Pvt. Ltd.), have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officers concerned of this department on 18/10/2021 in the presence of Sh. Silvestor (Manager) and found that the building / premises is fit for the occupancy class "Assembly" (Group-D) / Eating House with effect from 27/1.6(2.1... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 27/10/21 at New Delhi by

(ATUL GARG DIRECTOR. of so

Copy to:-

1. Addl. Commissioner, Licensing Unit, 1st Floor, Police Station, Defence Colony, New Delhi-110024.

2. Sh. Madhur Sharma (Dy. Manager, Legal), M/s KFC Restaurant (A unit of Sapphire Foods India Pvt. Ltd.), BG-06, Ground Floor, Ansal Plaza, Hudco Place, Andrews Ganj, New Delhi-110049.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on <u>WWW.dfs.Delhigovt.nic.in</u>

INSPECTION REPORT

Covered area of the restaurant is 103m² and as per NBC (Part-IV) the no. of occupants comes out to be Approx. 57 (103/1.8=57.22). Thus capacity of restaurant is 57 persons which is covered under DFS Act 2007, Rules 2010. Subsequently inspection of Eating House is carried out as per NBC (Part-IV).

- Name & address of the building: M/s KFC Restaurants (A unit of Sapphire Foods India Pvt. Ltd.), BG-06, Ground Floor, Ansal Plaza, Hudco Place, Andrews Ganj, New Delhi-110049.
- Type of Occupancy : Assembly (Group-D) (Eating House) (Two tier basements, Ground, Mezzanine and three upper floors. But restaurant is at ground floor only.
- Type of Case : New
- Details of previous NOC : Nil
- 5. Fire Safety directives Letter No.: Nil : 18/10/2021 6. Date of inspection
- 7. Name of the Inspecting Officer: D.O. (S.D.) & A.D.O. (S.J.)
- 8. Name and designation of Officer
 - : Sh. Silvestor (Manager) from the building side

S No 1.	U/R 33 Access	of building Road width Gate width	- 1	Requirement			Provided site		emarks IR/NMR	
1.	U/R 33	of building Road width Gate width								
	Access	of building Road width Gate width								
	•	Road width Gate width								
2.	•	Gate width		6m Pro		rovided M		MR	IR	
2.	•							MR		
2.	•	Width of internal	-	6m Pro		ovided M		MR	R	
2.		road								
	Numbe	er, width, Type & A	Arrai	ngements of	exit	S				
- 1	a.	Number of								
	staircases							1		
	•	Upper floors		NA NA				NA		
	•	2000		NA	NA		NA.	NA		
	b. Width of staircases		es					N	•	
	•	Upper floors		NA	NA			NA		
	•	Basements		NA	NA		IN A	NA		
	c. Protection of exits		S							
	•	Fire check door		Required	Provided			MR NA		
	•	Pressurization		NA	NA					
	d.			NA NA		A		IN.	NA	
		staircase to terrace		1.5m	1.5m		М	MR		
	e.	Width Of Corridor Door Size		1.5m x 2	2m & 1.5m (Final)		M	MR		
	f.			1.5111 × 2			EXIT	1		
3.	Compartmentation			Required	Provided		M	MR		
	•	Fire check door		Required	Provided		M	MR		
	•	Sealing of electrical shafts		Required	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
		Fire Rating of shaft door		Required	Provided		M	MR		
	•	Water Curtain		NA	NA		N	NA		
	•	Fire Dampers		NA	NA		N	NA		
4.		e managements								
4.	Syster									
	Byster	Basements 30		a/c per hour N		N/A	N/A		NA	
		Upper floors	1	a/c per hour		NA			NA	
5	Fire F	And the state of t								
5.	Fire Extinguishers • Total numbers		6		6 Nos. Provided		N	M/R		
	• Types					ABC, CO ₂ , Water		N	M/R	
				ABC, CO ₂ &		CO ₂	ABC, CO2, 11			
				WCO2		Provided		N	M/R	
	•	• ISI marking		Required		1000				
				All						

6.	First – Aid Hose Reels	(Fire Fighting	System is c	ommon for entire mal				
	• Total numbers on	02Nos. (Near		02Nos. (Near				
	each floor	restaurant)		restaurant)	MR	MR		
	 Length of hose reel hose 	30 Mtr.		30 Mtr.	MR			
	 Nozzle diameter 	5 mm		5 mm	-			
7.	Automatic fire detection and alarm • Type of detector	ming system	(Fire Fints)	3 111111	MR			
	 Type of detector 	Smoke & H	doat	g System is common for	entire mall bu	ilding)		
	 Location of Main 	N/A		Provided	11/14			
	Panel			Provided	rovided N/A			
	Location of Repeater Panel	N/A		Provided	N/A			
	Alternate source of power	Required		Provided	MR			
	Hooters' Location	Required		Provided	145			
8.	MOEFA	Required			MR			
9.	Public Address System	Required		Provided	MR	MR		
10.	Automatic Sprinkler System (F)	re Fighting S		Provided	MR			
	Basements	NA NA	is common fo					
	Upper Floor	NA		NA	NA	NA		
	 Sprinkler above false 	NA		NA	NA			
11.	ceiling			NA	NA			
11.	Internal Hydrants (Fire Fighting System	n is common for ent	ire mall buildi	ng)				
	comer	150mm		150mm Provided		MR		
	 Number of hydrants per floor 	02Nos. (Near restaurant)		02Nos. (Near re	02Nos. (Near restaurant)			
	 Hose Box 	02Nos. (Near restaurant) 02Nos. (N) 02Nos (Near ro	cto			
12.	Yard Hydrants (Fire Fighting System is common for entire mall building) MR							
	• Total number of	08 Nos		Provided	MAD			
	hydrants			···oviaca	IVIK	MR		
13.	• Hose Box	08 Nos		Provided	MR			
15.	Fire Fight	ing System is comm	on for entire n	nall building)				
-	Ground Level			_				
-	Discharge of main pumpHead of main pump			LPM Provided	MR	MR		
		Required 90 M			MR			
	Number of main pumpsJockey pump out put	Required 2nos.		-	MR			
-	> Jockey pump head	Required	450 L	-PM	MR			
	Standby Pump out put	Required	90m	LPM Provided	MR			
	Standby Pump Head	Required Required			MR	MR		
	➤ Auto Staring/Manual	-		dod				
	stopping	cquii eu	Provi	ueu	MR	MR		
	> Pump House Access	Required	Provi	ded	MR			
	Terrace level Disclared 6							
	Discharge of pump	NA		NA	NA			
	Head of the pump			NA	NA	NA		
Power supply				NA	NA	NA		
14	Auto starting of pump		NA		NA			
14	The storage for fire	fighting (Fire F	ighting System	n is common for entire mal	l building)			
	Underground tank capacity	4,50,000 ltr),000 ltr vided	NA			
	Draw of connection			ided	MR	MR		
	Fire service inlet	Required Provi			MR			
		Required Provi		idad	NAD	MR		
	Access to tankOverhead Tank	20,000 Lti s.		0 ltrs on AB Block &	MR			

1.5	F-'- G'	M/-3				
15	Exit Signage	Required Provided		MAD		
16.	Provision of Lifts		MR			
	Pressurization of	N/A	N/A			
	Lift Shaft		N/A	N/A		
	Pressurization of lift	N/A	N/A			
	lobby		N/A	N/A		
	Communication in	Required	Provided			
	lift Car		rrovided	MR		
	Fireman's	Required	Provided	1		
	Grounding Switch		- Tovided	MR		
	Lift Signage	Required	Provided	MD		
17.	Standby power supply	Do muita d		MR		
18.	Refuge Area	Required DG Set Provided		MR		
10.						
	, Total alca	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19.	9. Fire control room (Fire Fighting System is common for entire mall building)					
	Detector system	Required	Provided	MAD		
	panel			MR		
	Flow Switch Panel	N/A	N/A	N/A		
	PA System Panel	Required	Provided	MR		
	Battery backup	Required	Provided			
	➢ Building Floor	N/A	N/A	MR		
	Plans	•	14/A	N/A		
20.	Special Fire Protection	CO2 & ABC Type Fire Extinguishers Provided near				
	Systems for Protection of	Electric Panel=MR				
	special Risks, if any;					
	- ,,	,				

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer Name : S.K. Dua

Designation: D.O. (S.D.)

Signature of the Inspecting Officer Name : A.K. Jaiswal

Designation: A.D.O. (S.J.)