

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F6/DFS/MS/2021/ School/ 904

Dated: 29/10/2021

FIRE SAFETY CERTIFICATE

Certified that the Sarvodaya Kanya Vidyalaya (Rani Chennamma), (I.D No.1309256) located at D-Block, Jahangirpuri, Delhi-110033 comprised of (New block) ground and 03 upper floors owned/ occupied by the Sarvodaya Kanya Vidyalaya (Rani Chennamma) have complied with the fire prevention and safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and verified by the officer concerned of Fire Service on 14.10.2021 in the presence of Sh. Sanjay Chauhan and that the building/premises is fit for occupancy Class "Group B Educational" with effect from ..2.5.(.1.5.(.2.1....) for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 2. S. J. J. O. J. Z. J... at New Delhi

Director Ph:-011-23414000

Copy to: -

- 1. The Director, Education, Government of N.C.T of Delhi. Old Sectt. Delhi 110054.
- 2. The Assistance Engineer (E), PWD Sub-Division 4, Edu. Electrical Edn. 1 Division (N), Zakhira, Rama Road, Delhi-110015.

Conditions for the validity of Fire Safety Certificate:

- 1 All the means of escape/entry/exit shall be kept free from any obstruction.
 - 2 All the fire safety arrangements provided therein shall be maintained in good working condition
 - at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
 - 3 All the staff members must know the correct method of operation of firefighting system.
 - 4 The owner / occupier shall submit a declaration every year in Form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on http://delhi.gov.in./wps/wcm/connect/doit fire/FIRE/Home/Forms.
 - 5 This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
 - 6 "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

Noll

INSPECTION REPORT

Name & address of the building	: Sarvodaya Kanya Vidyalaya, D-Block, Jahangirpuri, Delhi-110033 (1D No 1309356)
Type of Occupancy	: Educational
Type of Case	: New Case (New blocks, Ground + 03 upper floors)
Details of previous NOC	: Nil
Fire Safety directives letter No	: NBC Part-4
Date of inspection	: 14.10.2021
Name of the Inspecting Officers	: ADO (RN)
Name and designation of officers	
from the building side	: Sh. Sanjay Chauhan (Attendant)
ear of Construction	: 2020
Applicant's letter No.	: Online E-Mail I.D dated: 08.10.2021
	Type of Occupancy Type of Case Details of previous NOC Fire Safety directives letter No Date of inspection Name of the Inspecting Officers Name and designation of officers from the building side ear of Construction

Plot /	Area: 11808Sqm Covered Area:	Sqm No. of	Student: 4500 NO. of	Class Room:					
	Minimum Standards on fire prevention fire safety U/R 33	and NBC Requirement	Provided at site	Remarks MR/NMR					
	Access to building	access to building							
	Road width	06m	06m	MR					
	Gate width	0 6 m	06m	MR					
	Width of internal road	NA	NA	NA					
	Number, Width, Type & Arrangement of Exits								
	a. Number of staircases								
	Upper Floors	02	05	MR					
	• Basements	NA	NA	NA					
	b. Width of staircases	1.50m	1.60m each	MR					
	Upper Floors	NA	NA	NA					
	Basements c. Protection of exits			annell 20 k					
	Fire check door	NA	NA	NA					
	Pressurization	NA	NA	NA					
	d. No. of continuous staircases to terrace	02	02						
	e. Width of Corridor			MR					
	f. Door Size	1.5m	1.60	MR					
	Compartmentation.	1.20m	1.20m double door	MR					
	Compartmentation.								
	• Fire check door	NA	NA	NA					
	Sealing of electrical shafts	NA	NA	NA					
	• Fire Rating of shaft door	NΛ	NA	NA					
	Water Curtain	NA	NA	NA					
	Fire Dampers	NΛ	NA	NA					
	Smoke Management System.								
	• Basements	12 a/c per hour	NA	NΔ					
	Upper floors	12 a/c per hour	Natural Ventilation	MR					
	Fire Extinguishers								
	Total numbers	45nos	50nos	MR					
	• Types	ABC/Co2	ABC-40 Co2-10	MR					

112

	 Total numbers on each floor 	06 each floor	Provided				
	Length of hose reel hose		1.10/1060	ММ			
	Nozzle diameter	30m	Join	МК			
		5mm	51010	MK			
7	Automatic fire detection and alarming system, NA NA						
	Type of detectors	NA	NA NA	NA			
	Location of Main Panel	NA		NA			
	Location of Repeater Panel	ner setter erstennerske eller de se	NA	NA			
	Alternate source of power	NA	NA	NA			
	Hooters' Location	NA	NA	NA			
8	MOEFA	NΛ	NA	NA			
9	Public Address System.	la petrola disconto in tractito a 97 cent 2 di tanzi i Contracio a 8 cm in tano					
10	Automatic Sprinkler System.	1	an a	kana ing pananana ang sana sa			
	Basement	NA	NA	NA			
	Upper Floor	NA	NA	NA			
	• Sprinkler above false ceiling	NA	NA	NA			
11	Internal Hydrants			and a second			
	Size of riser/down-comer	NΛ	NA	NA			
	• Number of hydrants per floor	ΝΛ	NA	NA			
	Hose Box	ΝΛ	NA	NA			
12	Yard Hydrants.						
	Total number of hydrants	NA	NA	NA			
	Hose Box	NA	NA	NA			
13	Pumping Arrangements						
	Ground Level			and the second of second second second			
	 Discharge of main Pump 	N/A	450lmp	N/A			
	 Head of Main pump 	N/A	40m	N/A			
	 Number of main pumps 						
	Jockey Pump out put	N/A	01	N/A			
	 Jockey pump head 	NA	NA	NA			
	Standby Pump out put	NA	450lmp	NA			
	Standby Pump Head	N/A	40m	N/A			
	Auto Starting/ Manual stopping	N/A	Provided	N/A			
	Pump House Access	N/A	Provided	N/A			
	Terrace level	4501pm	450 lpm x 02	MR			
	 Discharge of pump 		450 Ipm x 02 Provided	NIK			
	Head of the pump	40m	40m	MR			
	Power Supply	Required	Provided	MR			
	 Auto Starting of pump 	Required	Provided	MR			
4	Captive Water Storage for fire fighting						
	Underground tank capacity	ΝΛ	10000011	MΛ			
	 Draw-off connection 	NA	NA	NA			
	Fire service inlet	NA	NA	NA			
		1111					

P

15 Exit	• Overhead Tank capacity Signage.	10,000 ltr	10,000 ltr.	MR		
16 Prov	ision of Lifts.	Required	Provided	MR		
	Pressurization of Lift Shaft	N/A	N/A			
•	Pressurization of Lift lobby Communication In lift Car	N/A	N/A N/A	N/A N/A		
•	Fireman's Grounding Switch	N/A	N/A	N/A		
•	Lift Signage	N/A	N/A	N/A		
17 Standby	power supply	N/A	N/A	N/A		
18 Refuge A		N/A	N/A	N/A		
	Total Area					
	ocation	N/A	N/A	N/A		
19 Fire Cont	rol Room	N/A	N/A	N/A		
•	Detector System Panel					
	Flow Switch Panel	N/A	N/A	N/A		
	A System Panel	N/A	N/A	N/A		
	atter backup	N/A	N/A	N/A		
• Bı	iilding Floor Plans	N/A	N/A	N/A		
) Special Fire P	rotection Systems for	N/A	N/A	N/A		
opectarrace	pecial Risks, if any:	N/A	N/A	N/A		

N/3

The fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standard on fire prevention and fire safety requirements as stipulated under the circular issued by NBC Part-IV/Director of Education dated 01.03.2016, it is

DO (MM) Leque ON (WZ)101 2)

g

Billetter

6

Signature of the Inspecting Officer Name :- C.L. Meena Designation:- ADO/RN

ft ply [6] 20) 1

A.T.O