GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001

No F 6/DFS/MS/2021/WZ/School/93

Dated: 05/11/2021

FIRE SAFETY CERTIFICATE

Certified that the D A V Public School located at Sector-07, Rohini, Delhi-110085 comprised of Ground + Three Upper floors owned/ occupied by D A V Public School was issued Fire Safety Certificated vide this office letter no. F-6/DFS/MS/2018/School/7375 dated 17.07.2018. The premise was re-inspected by the officer concerned of this department on 26.10.2021 in the presence of Mr. Chiraj Chugh (Accountant) and observed that all the fire prevention and fire safety arrangements as provided in the premise found in good working condition. The premise have therefore deemed complied with the requirements under rule 33 of the Delhi Fire Service Rules, 2010 and the building premise is fit for occupancy under Educational "Group B" with effect from .05.11.2021. for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under rule 40, subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010,

Issued on .0.5 | 11 | 202 | at New Delhi

(Dhrampal Bhardwaj) Dy.Chief Fire Officer Tel;-01123414250

ole

Copy to:-

1. The Director, Education, Government of N.C.T of Delhi. Old Sectt. Delhi - 110054.

2. The Principal, DAV Public School, Sec-07, Rohini, Delhi-110085.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on **WWW.dfs.Delhigovt.nic.in**



INSPECTION REPORT

1. Name & address of the building

: D A V Public School, Sec-07, Rohini, Delhi-110085.

2. Type of Occupancy

: Educational

3. Type of Case

: Renewal (Ground + 03 Upper floor)

4. Details of previous NOC

5. Fire Safety directives letter No

: F-6/DFS/MS/2018/School/7375 dated 17.07.2018

: NBC Part-04

6. Date of inspection

: 26.10.2021

: A.K.Sharma ADO (Rohini)

7. Name of the Inspecting Officers 8. Name and designation of officers

: Mr. Chiraj Chugh (Accountant)

from the building side

: 1994-2006

9. Year of Construction

| 10. | Applic | ant's | letter | No. |
|-----|--------|-------|--------|-----|
|-----|--------|-------|--------|-----|

: Online e-mail dated 15.09.2021

| | Minimum Standards on fire prevention and fire safety U/R 33 | NBC Requirement | Provided at site | Remarks MR/NMF | | |
|---|--|--------------------|--------------------|-------------------|--|--|
| | Access to building | • | | | | |
| | 2 1 111 | Accessible | Accessible | MR | | |
| | | Accessible | 5 m | MR | | |
| | • Gate width | NA | NA | NA | | |
| | Width of internal road | | | | | |
| | Number, Width, Type & Arrangement of Exits | | | | | |
| | a. Number of staircases | 04 | 04 | MR | | |
| | • Upper Floors | NA | NA | NA | | |
| | • Basements | 1474 | | | | |
| | b. Width of staircases | | 1.75m,1.36m,1.41 | | | |
| | 77 | 1.50 | m, 1.80 m & | MR | | |
| | Upper Floors | 1.50m | 1.41- 142 | | | |
| | D. waste | NA | NA NA | NA | | |
| | Basements | INA | 7.4.2 | | | |
| | c. Protection of exits | NA | NA | NA | | |
| | • Fire check door | | NA | NA | | |
| | Pressurization | NA 02 | 2 | MR | | |
| | d. No. of continuous staircases to terrace | NA | NA | NA | | |
| | e. Width of Corridor | | | MR | | |
| | f. Door Size | 1 m | 1 m | TVIIC | | |
| 3 | Compartmentation. | | | | | |
| _ | • Fire check door | NA | NA | NA | | |
| | Sealing of electrical shafts | NA | NA | NA | | |
| | Fire Rating of shaft door | NA | NA | NA | | |
| | • Water Curtain | NA | NA | NA | | |
| | • Fire Dampers | NA | NA | NA | | |
| 4 | Smoke Management System. | | | | | |
| 7 | Basements | 30 a/c per hour | NA | NA | | |
| | Upper floors | 12 a/c per hour | Natural Ventilated | MR | | |
| 5 | Fire Extinguishers | | | | | |
| 5 | Total numbers | 30 nos | 30 nos | MR | | |
| | | ABC/Co2 | ABC-26 / Co2- 4 | MR | | |
| | • Types | ISI Marked | Yes | MR | | |
| 6 | ISI marking First-Aid Hose Reels. | | | | | |
| 0 | Total numbers on each floor | 03 each floor | 03 | MR | | |
| | | 30m | 30m | MR | | |
| | Length of hose reel hoseNozzle diameter | 5mm | 5mm | MR | | |
| | Automatic fire detection and alarming s | | | | | |
| 7 | Type of detectors | NA | NA | NA | | |
| | Type of detectors Location of Main Panel | NA NA | NA | NA | | |
| | Location of Main Fanci Location of Repeater Panel | | NA NA | NA | | |
| | Location of Repeater Fanci | NA | NA | 1473 | | |

| | | , | NIA | NIA | |
|----|--|-------------|--------------------------------|------------|--|
| | Alternate source of power | NΛ | NΛ | NA | |
| | Hooters' Location | NΛ | NΛ | NA | |
| 3 | MOEFA | Required | Provided | MR | |
|) | Public Address System. | NΛ | NΛ | NA | |
| 0 | Automatic Sprinkler System. | | | | |
| | Basement | NΛ | NΛ | NA | |
| | Upper Floor | NΛ | NΛ | NA | |
| | Sprinkler above false ceiling | NA | NA | NA | |
| 1 | Internal Hydrants | | | | |
| | Size of riser/down-comer | 100mm | Provided | MR | |
| | Number of hydrants per floor | 03 | Provided | MR | |
| | Hose Box | 03 | Provided | MR | |
| 2 | Yard Hydrants. | | | | |
| | Total number of hydrants | 03 | 03 | MR | |
| | Hose Box | 03 | 03 | MR | |
| 3 | Pumping Arrangements. | | | - | |
| | Ground Level | | 27/4 | N/A | |
| | Discharge of main Pump | N/A | N/A | | |
| | Head of Main pump | N/A | N/A | N/A | |
| | Number of main pumps | N/A | N/A | N/A N/A | |
| | > Jockey Pump out put | N/A | N/A | | |
| | Jockey pump head | N/A | N/A | N/A N/A | |
| | Standby Pump out putStandby Pump Head | N/A | N/A | N/A N/A | |
| | > Auto Starting/ Manual | N/A | N/A | | |
| | stopping | N/A | N/A | N/A | |
| | Pump House Access | | | | |
| | Terrace level | 900 lpm | 900 lpm | MR | |
| | Discharge of pump | 36m | 36m | MR | |
| | Head of the pumpPower Supply | Required | Provided | MR | |
| | > Auto Starting of pump | Required | Provided | MR | |
| 4 | Captive Water Storage for fire fighting | | | | |
| • | Underground tank capacity | NA | NA | NA | |
| | > Draw-off connection | NA | NA | NA | |
| | Fire service inlet | NA | NA | NA | |
| | > Access to tank | NA | NA | NA | |
| | Overhead Tank capacity | 10,000 ltrs | 20,000ltrs | MR | |
| 5 | Exit Signage. | Required | Provided | MR | |
| 6 | Provision of Lifts. | | | | |
| | Pressurization of Lift Shaft | N/A | N/A N/A | N/A N/A | |
| | Pressurization of Lift lobby | N/A | N/A N/A | N/A N/A | |
| | Communication In lift Car | N/A | | N/A | |
| | Fireman's Grounding Switch | N/A | N/A N/A | N/A N/A | |
| | Lift Signage | N/A | 125 KVA | MR | |
| 7 | Standby power supply | N/A | 123 K V A | 14117 | |
| 8 | Refuge Area. | N/A | N/A | N/A | |
| | > Total Area | N/A N/A | N/A | N/A | |
| | > Location | 11/73 | 14/17 | 1 1/1 1 | |
| 19 | Fire Control Room Detector System Panel N/A N/A | | | | |
| | Detector System Panel | N/A N/A | N/A N/A | N/A N/A | |
| | Flow Switch Panel | N/A N/A | N/A N/A | N/A | |
| | PA System Panel | | N/A | N/A | |
| | Batter backup | N/A | 1 N / <i>F</i> 1 | 14/17 | |

| | | | N/A | N/A |
|----|--------------------------------------|-----|----------------|----------|
| | Building Floor Plans | N/A | N/A | N/A |
| 20 | Special Fire Protection Systems for | N/A | IN/A | |
| | Protection of special Risks, if any: | | test checked a | nd found |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F-6/DFS/MS/2018/School/7375 dated 17.07.2018 is recommended for renewal under rule 37 of the Delhi Fire Service rules 2010.

> Signature of the Inspecting Officer Ajay Kumar Sharma Name Designation ADO (Rohini)

المحدادة الع

Fi letter is put up for lind pennsal and signature please.