GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE <u>NEW DELHI</u>

No. F6/DFS/MS/EH/WZ/2021/333

Dated: 1 / 1 /2021

FIRE SAFETY CERTIFICATE

Director Delhi Fire Service

Copy to: -

(

- The Owner/occupier Dhaba Restaurant (A Unit of Hotel Mugal Palace) located at A5, First ogli floor, Vishal Enclave, Rajori Garden, New Delhi-110027 (Reference: - ID No. 2019122701132 dated: - 15/04/2021)
- The Joint Commissioner of Police, Licensing Unit, 1st floor, Police Station, Defence Colony, New Delhi. (<u>addlcp.lic-dl@nic.in</u>).
- 3. The Dy. Health Officer, SDMC, West Zone, Vishal Enclave, Rajouri Garden, New Delhi 110027. (dhowest zone@gmail.com)

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. This NOC is valid for Ground floor only.

| | | 46 | | | | | |
|--------------------|--|--|--|-----------------------------|--|--|--|
| | INSPI | ECTION REPORT | | | | | |
| | | aba Restaurant (A Uni 5. First floor, Vishal Er 0027. | t of Hotel Mugal Palac nelave, Rajori Garden, | e) located at New Delhi- | | | |
| - | 2. Type of Occupancy : Class | D (Assembly) | | | | | |
| | 3. Type of Case :New | | | | | | |
| | Nil | | | | | | |
| | n o can directives letter No : Nil | | | | | | |
| | Date of inspection : 27/10/2021 | | | | | | |
| | | | | | | | |
| | 1 Indianation of officers | 5 | | | | | |
| 8 | from the building side : Sh. | Bhupender Singh Nara | ang | | | | |
| 0 | Year of Construction :1980 | (As per MHA portal) | | | | | |
| | | ine application No. 201 | | 5/04/2021 | | | |
| | The Said Restaurant is running at Grou | and Floor in a building | comprised at Ground | + Two uppe | | | |
| * | | | | | | | |
| Floor S. No. | Minimum Standards on fire prevention and fire safety U/R 33 | BBL /NBC/ Requirement/As per pre.Ins.Rep dt11/05/2018 | Provided at site | Remarks MR/NMR | | | |
| 1 | Access to building | | | | | | |
| | Road width | 09 mts | Provided | MR | | | |
| | Gate width | 4.5 mts | On Main Road | MR | | | |
| | • Width of internal road | NR | NR | NR | | | |
| 2 | Number, Width, Type & Arrangeme | nt of Exits | | | | | |
| 2 | a. Number of staircases | | | | | | |
| | Upper Floors | NA (G.F.) | NA | NA | | | |
| | Basements | NA | NA | NA | | | |
| | b. Width of staircases | | NA | NA | | | |
| | • Upper Floors | NA (G.F.) NA | NA NA | NA | | | |
| | • Basements | 1971 | | | | | |
| | c. Protection of exits | NA | NA | ΝΛ | | | |
| | • Fire check door | NA | NA | NA | | | |
| | Pressurization | 01 | Provided | MR | | | |
| | e. No. of continuous staircases to terrace | NA | NA | NA | | | |
| | f. Width of Corridor | 1.5 mts each | provided | MR | | | |
| , | g. Door Size | | 1 | | | | |
| 3 | Compartmentation. | NA | NA | NA | | | |
| | • Fire check door | NA | NA | NΛ | | | |
| | Sealing of electrical shaftsFire Rating of shaft door | NA | NA | NA | | | |
| | Fire Rating of shaft doorWater Curtain | NA | NA | NA | | | |
| | Fire Dampers | NA | NA | NA | | | |
| 1 | Smoke Management System. | | 1111 | | | | |
| 1 | Basements | NA | NA | NA | | | |
| | BasementsUpper floors | Required | Provided | MR | | | |
| | - Opper moors | Required | | | | | |
| 5 | Fire Extinguishers | | | | | | |
| 5 | Fire Extinguishers | | Duovidad | MP | | | |
| 5 | Fire Extinguishers • Total numbers • Types | 10 CO ₂ , ABC type | Provided | MR MR | | | |

X

| | | NZ | | MR | | |
|-----|--|--------------------------------------|--|----------------------|--|--|
| | IS marking | ISI marked | Provided | MR | | |
| 6 | First-Aid Hose Reels. | | | | | |
| 0 | Total numbers on each floor | 1 | Provided | MR | | |
| | Length of hose reel hose | 30m | Provided | MR | | |
| | Nozzle diameter | 5mm | Provided | MR | | |
| | | | | | | |
| 7 | Automatic fire detection and alarming system. | | | | | |
| | • Type of detectors | NR | NR | NR | | |
| | Location of Main Panel | NR | NR | NR | | |
| | • Location of Repeater Panel | NR | NR | NR | | |
| | • Alternate source of power | NR | NR | . NR | | |
| | Hooters' Location | NR | NR | NR | | |
| 8 | MOEFA | Required | Provided | MR | | |
| 9 | Public Address System. | NA | NA | NA | | |
| 10 | Automatic Sprinkler System. | | | | | |
| 10 | Basement | NA | NA | NA | | |
| | DasementUpper Floor | NR | Provided | | | |
| | Sprinkler above false ceiling | NA | NA | NA | | |
| 1 1 | • | 117 | | | | |
| 11 | Internal Hydrants | 100mm | Provided | MR | | |
| | • Size of riser/down-comer | | Provided | MR | | |
| | • Number of hydrants per floor | 1 | Provided | MR | | |
| | Hose Box I Hovided | | | | | |
| 12 | Yard Hydrants. | | NID | NR | | |
| | • Total number of hydrants | NR | NR | NR | | |
| | Hose Box | NR | NR | THE | | |
| 13 | Pumping Arrangements. | | | | | |
| | Ground Level | | | ND | | |
| | Discharge of main Pump | NR | NR | NR NR | | |
| | Head of Main pump | NR | NR | NR | | |
| | Number of main pumps | NR | NR | NR | | |
| | Jockey Pump out put | NR | NR | NR | | |
| | Jockey pump head | NR | NR | NR | | |
| | Standby Pump out put | NR | NR | NR | | |
| | Standby Pump Head | NR | NR | NR | | |
| | > Auto Starting/ Manual stopping | NR | NR | NR | | |
| | Pump House Access | NR | NR | INK | | |
| | | | | | | |
| | • Terrace level | 450 have | Provided | MR | | |
| | Discharge of pump | 450 lpm | Provided Provided | MR MR | | |
| | Discharge of pumpHead of the pump | 30 m | Provided | | | |
| | Discharge of pump Head of the pump Power Supply | 30 m Required | Provided Provided | MR | | |
| | Discharge of pump Head of the pump Power Supply Auto Starting of pump | 30 m Required Required | Provided | MR MR | | |
| 14 | Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting of pump | 30 m Required Required | Provided Provided Provided | MR MR | | |
| 14 | Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting of the pump Underground tank capacity | 30 m Required Required ing. | Provided Provided Provided NR | MR MR MR | | |
| 14 | Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting of pump | 30 m Required Required | Provided Provided Provided | MR MR MR NR | | |

8P}

Con and

1

(

•

• ie c

ı ec rv

)' 7

K V



| 15 | Exit Signage. | Required | Provided | MR | | |
|----|---|----------|----------|----|--|--|
| 16 | Provision of Lifts. | | | | | |
| | Pressurization of Lift Shaft | NA | NA | NA | | |
| | Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch | NA | NA | NA | | |
| | | NA | NA | NA | | |
| | | NA | NA | NA | | |
| | • Lift Signage | NA | NA | NA | | |
| 17 | Standby power supply | Required | Provided | MR | | |
| 18 | Refuge Area. | | | | | |
| | > Total Area | NR | NR | NR | | |
| | > Location | NR | NR | NR | | |
| 19 | Fire Control Room | | | | | |
| | Detector System Panel | NR | NR | NR | | |
| | Flow Switch Panel | NR | NR | NR | | |
| | PA System Panel | NR | NR | NR | | |
| | Batter backup | NR | NR | NR | | |
| | Building Floor Plans | NR | NR | NR | | |
| 20 | Special Fire Protection Systems for Protection of special Risks, if any: | NR | NR | NR | | |

N 8

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

291 ADO MN 02 Signature of the Inspecting Officer (Sarabject Singh) Asst. Divisional Officer (MN) 01 11 62 1/11/202 D W2 2021 11 5 tentaun uplouder .