GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

No. F.6/DFS/MS/EH/2021/SZ/ 335

Dated: 16 11 2021

DELHI FIRE SERVICE

(-20

FIRE SAFETY CERTIFICATE

Certified that the **M/s Gola Restaurant** (previously known as Bounce), running at ground floor only in a building comprised of ground floor plus one upper floor located at Unit No. A-1, J-1/164, Rajouri Garden, New Delhi-110027, owned/occupied by M/s A unit of Gola Sizzler. The building was inspected by the officers concerned of this department on 29/10/2021 in the presence of Sh. Bijender (Manager) and found that the building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises (Ground floor only) is fit for occupancy class Group D "Assembly Building" w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010

Copy to:-

- The Deputy Health Officer, West Zone (SDMC), Public Health Department, Vishal Enclave, New Delhi.
- The Manager, M/s Gola Restaurant (a unit of Gola Sizzler), Plot No.J-1/164, Unit No. Λ-1. Rajouri Garden, New Delhi-110027.

Following fire safety directives must be adhered to:-

- 1. This NOC is valid only for ground floor.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 3. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 4. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 5. The trained staff should be available round the clock.
- Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 7. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <u>www.dfs.delhigovt.nic.in</u>.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.



		IN	SPECTION REPORT
1.	Name	& address of the building:	M/s Gola Restaurant (previously known as Bounce), Unit No. A-1,
			J-1/164, ground floor, Rajouri Garden, New Delhi-110027
		ng is comprised of :	G+1 (Restaurant is running at GF Only) First floor is vacant.
		of Occupancy :	Group D (Assembly Building)
		of Case :	Renewal
		s of Previous NOC :	F.6/DFS/MS/EH/2020/SZ/05 dated 03/01/2020 (for Bounce)
6.	Fire S	afety directives letter No :	Ν/Λ
			27/10/2021
8.	Name		A.D.O. R.K.Yadav
9.	Name	and designation of officers	
			: Sh. Bijender (Manager)
10.	Year c	of Construction	: 2019
11.	Applic	ant's letter No.	: 2021090620411 dated 11/09/2021

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR				
1.	Access to building							
	Road width	09 m 4.5 m	Directly accessible					
	• Gate width	4.5 m N/A	from road	N/A				
	Width of internal road	IN/A	N/A					
2.	Number, Width, Type & Arrangement of Exits							
	a. Number of staircases							
	• Upper Floors	N/A	N/A	N/A				
	• Basements	N/A	N/A	N/A				
	b. Width of staircases	N/A	N/A	N/A				
	Upper Floor	N/A	N/A	N/A				
	Basements c. Protection of exits							
	Fire check door	N/A	N/A	N/A				
	Pressurization	N/A	N/A	N/A				
	d. No. of continuous staircases to	N/A	N/A	N/A				
	e. Width of Corridor	2.0 m	Opening in	MR				
	e. Width of Corridor	210 111	hall					
	f. Door Size	2.0 m each	2.0 & 2.0 m	MR				
3.	Compartmentation							
	Fire check door	N/A	N/A	N/A				
	 Sealing of electrical shafts 	N/A	N/A	N/A				
	• Fire Rating of shaft door	N/A	N/A	N/A				
	Water Curtain	N/A	N/A	N/A				
	• Fire Dampers	N/A N/A	N/A	N/A				
4.	Smoke Management System							
		N/A	N/A	N/A				
	• Basements	1N/A	11//1	11/71				
	Ground floor	Required	Provided	MR				
5.	Fire Extinguishers							
	Total numbers and 1.0	04 No.'s	06 no.'s Provided	MR				
	Total numbers on each floorTypes	ABC/CO ₂	Provided	MR				
	• IS marking		ISI marked	MR				
		ISI marked	151 marked	IVIIX				

	K	2				
	First-Aid Hose Reels					
		One	Provided	MR		
	 Total numbers on ground floor 	30 m	Provided	MR		
	 Length of hose reel hose 	5 mm	Provided	MR		
	Nozzle diameter	5 11111				
	Automatic fire detection and alarming system	NI/A	N/A	N/A		
	• Type of detectors	N/A N/A	N/A	N/A		
	 Location of Main Panel 	N/A	N/A	N/A		
	 Location of Repeater Panel 	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooters' Location		Provided	MR		
	MOEFA with talk back system	Required	N/A	N/A		
	Public Address System	N/A				
0.	Automatic Sprinkler System					
		N/A	N/A	N/A		
	• Basement	N/A	N/A	N/A		
	Ground Floor Grine asiling	N/A	N/A	N/A		
	Sprinkler above false ceiling	1.17.				
11.	Internal Hydrants					
	• Size of riser/down-comer	100 mm	Provided	MR MR		
		01 No.	Provided	MR		
	Number of hydrants	01 No.	Provided	IMIC		
	Hose Box					
12.	Yard Hydrants	N/A	N/A	N/A		
	Total number of hydrants	N/A	N/A	N/A		
	Hose Box					
13.	Pumping Arrangements			1		
	Ground Level			N/A		
	 Discharge of main Pump 	N/A	N/A			
	 Head of Main pump 	N/A	N/A	N/A		
	 Number of main pumps 	N/A	N/Λ	N/A		
	 Jockey Pump out put 	N/A	N/A	N/A		
	 Jockey pump head 	N/A	N/A	N/A		
	 Standby Pump out put 	N/A	N/A	N/A		
	 Standby Pump Head 		N/A	N/A		
	 Auto Starting/Manual Stopping 	N/A	N/A N/A	N/A		
		N/A		N/A N/A		
	> Pump House Access	N/A	N/A	19/74		
	 Terrace level 			1.00		
	• Terrace level \succ Discharge of pump	450 LPM	Provided	MR		
	 Final of the pump 	30 m	Provided	MR		
	> Power Supply	Required	Provided	MR		
	Auto Starting of pump	Required	Provided	MR		
14.	Captive Water Storage for fire fighting					
		N/A	N/A	N/A		
	• Underground tank capacity	N/A	N/A	N/A		
	 Draw-off connection Fire service inlet 					
	Access to tank	Required	Provided	MR		
	 Overhead Tank capacity 	N/Λ	N/A	N/A		
		20,000 ltrs	Provided	MR		

N17

15.	Exit Signage.						
16.	Provision of Lifts.	Required	Provided	MD			
	Pressurization of Lift Shaft			MR			
	ricssurization of Lift lobby	N/A	N/A	NI/A			
	Communication in E.C. C	N/A	N/A	N/A			
	Fireman's Grounding Spilest	N/Λ	N/A	N/A N/A			
	Lift Signage	N/Λ	N/A	N/A			
17.	Standby power supply	N/A	N/A	N/A			
		Required	Provided	MR			
18.	Refuge Area.						
	Total Area	N/A	NI/A				
	Location		N/A	N/A			
		N/A	N/A	N/A			
19.	Fire Control Room						
	Detector System Panel						
	Flow Switch Panel	N/A	N/A	N/A			
	• PA System Panel	N/A	N/A	N/A			
	 Battery backup 	N/A	N/A	N/A			
	Building Floor Plans	N/A	N/A	N/A			
		N/A	N/A	N/A			
20.	Special Fire Protection System for Protection of special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. The fire safety certificate was issued vide letter no. F6/DFS/MS/EH/2020/SZ/05 dated 03/01/2020 for Bounce.

Keeping in view of the above substantial compliance of the minimum standards of fire prevention and fire safety measures as required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of Inspecting Officer Name:- R.K.Yadav Designation:- Asstt. Divisional Officer

D.O.(South West)

121

0311112021 52)

And