

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

No.F.6/DFS/MS/EH/2021/SZ/ 338

Dated: 24/11/21

FIRE SAFETY CERTIFICATE

Certified that the M/s KFC Restaurant (A unit of sapphire foods), Shop No.-8 to 11, Plot No.-19, Satyam Complex, District Centre, Janakpuri, New Delhi-110058, is running at ground floor was issued FSC by this department vide letter no. F6/DFS/MS/EH/2018/SZ/2307 dated 12/10/2018 owned/occupied by M/s KFC Restaurant (A unit of sapphire foods) was reinspected by the officers concerned of this department on 11/11/2021 in the presence of Sh. Amit Kumar (Manager) and found that the restaurant building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises (Ground Floor Only) is fit for occupancy class Group-D "Assembly Building" w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on..... 24 at New Delhi.

(SUNIL CHAWDHARY) DY.CHIEF FIRE OFFICER

Copy to:-

1. The Manager,

M/s KFC Restaurant (A unit of sapphire foods), Shop No.-8 to 11, Plot No.-19, Satyam Complex, District Centre, Janakpuri, New Delhi-110058

The Dy. Health Officer,
 S.D.M.C, Public Health Department, West Zone,
 Vishal Enclave, Rajouri Garden, New Delhi-110027

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per the building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

N

| | | | N/17 | | |
|-----|--|--------------------------------------|------------------------------------|--|---------------------------------------|
| | | INSPECTION | REPORT | | |
| | 1. Name 8 | address of the building: M/s KFC R | estaurant (A unit of | sapphire foods), S strict Centre, Janak | Shop No8 to 11, puri, New Delhi-58 |
| | | Restaurant | is running at ground | i noor in satyant | omplex building |
| | 2. Buildin | Group D (| Assembly Building) | | |
| | Type of Type of | Occupancy | S/EH/2018/SZ/230 | | |
| | 5 Details | | S/EH/2018/SZ/230 | / duted / la | |
| | 6 Fire Saf | fety directives letter No : 19/2 | 1 | | |
| | 7 Date of | inspection | K.Yadav | | |
| | 8. Name o | in hispecting of afficers | | | |
| | 9. Name a | he building side | Kumar (Manager) | | |
| | 10. Year of | Construction : 2010 | 25201 dated 28/10/ | 21 | |
| | 11 Applica | t's letter No. 20211027 | 25291 dated 28/10/2 Requirement | Provided at | Remarks |
| S. | Minimum S | tandards on fire prevention and life | Kequitement | site | MR/NMR |
| No. | safety U/R 3 | 3 | | | |
| 1. | Access to bu | lilding | | 10 m | MR |
| | P. P | 1 width | 09 m | 12 m Directly accessible | MR |
| | | width | 4.5 m 06 m | from internal road | MR |
| | Widt | th of internal road | 00 111 | Provided | |
| | | : 14. True & Arrangement of Exits | | | |
| 2. | a. Number, Wi | idth, Type & Arrangement of Exits | | | (restaurant at G |
| | a. Number o | per Floors | N/A | N/A | (restaurant at o only) |
| | | ements | | N/A | N/A |
| | | | N/A | 11/71 | |
| | b. Width of s | | | N/A | (restaurant at G |
| | | ber Floor | N/A | IN/A | only) |
| | | ements | N/A | N/A | N/A |
| | c. Protection | check door | IN/A | | |
| | | surization | | N/A | N/A |
| | | | N/A | N/A | N/A |
| | d. No. of co | ntinuous staircases to | N/A | 14/7 | |
| | terrace | | 27/4 | One | M/R |
| | e. Width of | Corridor | N/A | Opening in | M/R |
| | | | N/A | hall | |
| | f. Door Size | | 02 m | 2.0 & 1.05 m | MR |
| | | | 02 | | (restaurant at C |
| 3. | Compartmen | ntation | | | only) |
| | | | N/A | N/A | N/A |
| | • Fire c | check door | N/A | N/A | N/A |
| | • Sealin | ng of electrical shafts | N/A | N/A | N/A |
| | • Fire F | Rating of shaft door r Curtain | | | N/A |
| | | r Curtain Dampers | N/A | N/A N/A | N/A N/A |
| | | - | N/A | 11/7 | |
| 4. | Smoke Mana | agement System | | (R | estaurant at GF or |
| | | | N/A | N/A | N/A |
| | | | Required | Provided | MR |
| | • Upper | r floors | Required | | |
| 5. | Fire Extingui | ishers | | Provided | MR |
| | | numbers | 04 No.'s ABC/CO ₂ | Provided | MR |
| | • Types | | | | |
| | • IS ma | | ISI marked | ISI marked | MR |

| 6. | First-Aid Hose Reels | | | |
|-----|--|--|---|--|
| | The following have an anound floor | One | (Restau Provided | rant at GF only) MR |
| | • Total numbers on ground floor | | | |
| | Length of hose reel hose | 30 m | Provided | MR |
| | Nozzle diameter | 5 mm | Provided | MR |
| 7. | Automatic fire detection and alarming system | | | |
| | Type of detectors | Smoke & Heat | Provided | MR |
| | Location of Main Panel | Required | G Floor | MR |
| | Location of Repeater Panel | N/A | N/A | N/A |
| | Alternate source of power | Required | Provided | MR |
| | Hooters' Location | Required | At exit | MR |
| 8. | MOEFA | Required | Provided | MR |
| 9. | Public Address System | N/A | Provided | N/A |
| 10. | Automatic Sprinkler System | | | nt at GF only) |
| | • Basement | N/A | N/A | N/A |
| | Ground Floor | Required | Provided | MR |
| | Sprinkler above false ceiling | N/A | N/A | N/A |
| 11. | Internal Hydrants | | | nt at GF only) |
| | Size of riser/down-comer | 100 mm | Provided | MR |
| | • Number of hydrants | 01 No. | Provided | MR |
| | Hose Box | 01 No. | Provided | MR |
| 12. | Yard Hydrants | | | |
| 12. | Total number of hydrants | N/A | N/A | N/A |
| | Hose Box | N/A | N/A | N/A |
| 13. | Pumping Arrangements | | Common with saty | |
| 13. | | | | |
| 13. | Pumping Arrangements Ground Level | ((| Common with saty | am Complex) |
| 13. | Pumping Arrangements ● Ground Level > Discharge of main Pump | 2280 LPM | Common with saty Provided | am Complex) MR |
| 13. | Pumping Arrangements ● Ground Level > Discharge of main Pump > Head of Main pump | 2280 LPM 60 m One | Common with saty Provided Provided | am Complex) MR MR |
| 13. | Pumping Arrangements ● Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps | 2280 LPM 60 m One 220 LPM | Common with saty Provided Provided Provided Provided | am C omplex) MR MR MR MR |
| 13. | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put | (2280 LPM 60 m One 220 LPM 60 m | Common with saty Provided Provided Provided Provided Provided | am Complex) MR MR MR MR MR MR |
| 13. | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put | 2280 LPM 60 m One 220 LPM 60 m 2280 LPM | Common with saty Provided Provided Provided Provided Provided Provided | am C omplex) MR |
| 13. | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head | (2280 LPM 60 m One 220 LPM 60 m | Common with saty Provided Provided Provided Provided Provided | am Complex) MR MR MR MR MR MR MR MR MR |
| 13. | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping | 2280 LPM 60 m One 220 LPM 60 m 2280 LPM 60 m | Common with saty Provided Provided Provided Provided Provided Provided Provided | am Complex) MR |
| 13. | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Auto Starting/Manual Stopping > Pump House Access | 2280 LPM 60 m 0ne 220 LPM 60 m 2280 LPM 60 m Required | Common with saty Provided Provided Provided Provided Provided Provided Provided Provided N/A | am Complex) MR |
| 13. | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level | 2280 LPM 60 m 0ne 220 LPM 60 m 2280 LPM 60 m Required | Common with saty Provided Provided Provided Provided Provided Provided Provided Provided | am Complex) MR N/A N/A |
| 13. | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump | 2280 LPM 60 m 0ne 220 LPM 60 m 2280 LPM 60 m Required N/A N/A | Common with saty Provided Provided Provided Provided Provided Provided Provided Provided N/A N/A N/A | am Complex) MR N/A N/A |
| 13. | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump | 2280 LPM 60 m 0ne 220 LPM 60 m 2280 LPM 60 m Required N/A N/A N/A N/A | Common with saty Provided Provided Provided Provided Provided Provided Provided Provided N/A N/A N/A N/A | am Complex) MR N/A N/A N/A N/A N/A |
| 13. | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump | 2280 LPM 60 m 0ne 220 LPM 60 m 2280 LPM 60 m Required N/A N/A | Common with saty Provided Provided Provided Provided Provided Provided Provided Provided N/A N/A N/A | am Complex) MR N/A N/A |
| | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply | 2280 LPM 60 m 0ne 220 LPM 60 m 2280 LPM 60 m Required N/A N/A N/A N/A N/A | Common with saty Provided Provided Provided Provided Provided Provided Provided Provided N/A N/A N/A N/A N/A N/A N/A | am Complex) MR N/A N/A N/A N/A |
| | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump | 2280 LPM 60 m 0ne 220 LPM 60 m 2280 LPM 60 m Required N/A N/A N/A N/A | Common with saty Provided Provided Provided Provided Provided Provided Provided Provided N/A N/A N/A N/A N/A N/A N/A 90,000 ltrs | am Complex) MR MR MR MR MR MR MR N/A N/A N/A N/A N/A N/A |
| | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump | 2280 LPM 60 m 0ne 220 LPM 60 m 2280 LPM 60 m Required N/A N/A N/A N/A N/A | Common with saty Provided Provided Provided Provided Provided Provided Provided Provided N/A N/A N/A N/A N/A N/A N/A | am C omplex) MR N/A N/A N/A N/A |
| | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump • Underground tank capacity > Draw-off connection > Fire service inlet | 2280 LPM 60 m One 220 LPM 60 m 2280 LPM 60 m Required N/A N/A N/A N/A N/A N/A N/A N/A N/A | Common with saty Provided Provided Provided Provided Provided Provided Provided Provided N/A N/A N/A N/A N/A N/A N/A 90,000 ltrs | am Complex) MR MR MR MR MR MR MR N/A N/A N/A N/A N/A N/A |
| | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump • Underground tank capacity > Draw-off connection | 2280 LPM 60 m One 220 LPM 60 m 2280 LPM 60 m Required N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A | Common with saty Provided Provided Provided Provided Provided Provided Provided Provided N/A N/A N/A N/A N/A N/A N/A N/A Provided | am Complex) MR MR MR MR MR MR MR MR N/A N/A N/A N/A N/A N/A N/A MR, being old ca |
| 4. | Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > Jockey Pump out put > Jockey pump head > Standby Pump out put > Standby Pump Head > Auto Starting/Manual Stopping > Pump House Access • Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump • Underground tank capacity > Draw-off connection > Fire service inlet | 2280 LPM 60 m One 220 LPM 60 m 2280 LPM 60 m Required N/A N/A N/A N/A N/A N/A N/A N/A N/A | Common with saty Provided Provided Provided Provided Provided Provided Provided Provided N/A N/A N/A N/A N/A N/A N/A N/A N/A Provided Provided Provided | am Complex) MR MR MR MR MR MR MR MR N/A N/A N/A N/A N/A N/A N/A MR, being old ca MR MR |

The second s

L

١

b?

ge

>>

re

's KFC Restaurant (A unit of sapphire foods), Shop No.-8 to 11, Plot No.-19, Satyam Complex, District Centre Janakpuri, New Delhi-58

INOT INU

| | | v | (Restaura | nt at GF only) |
|-----|---|-------------|----------------------|----------------|
| 6. | Provision of Lifts. | N/A | N/A | N/A |
| | Pressurization of Lift Shaft Pressurization of Lift lobby | N/Λ | N/A | N/A MR |
| | Communication In lift Car | Required | Provided | MR |
| | Fireman's Grounding Switch | Required | Provided Provided | MR |
| | Lift Signage | Required | | MR |
| 17. | Standby power supply | Required | Provided | |
| | Refuge Area. | | | |
| 8. | | N/A | N/A | N/A |
| | Total Area Location | N/A | N/A | N/A |
| | Fire Control Room | | N/A | N/A |
| 19. | Detector System Panel | N/A | N/A | N/A |
| | Flow Switch Panel | N/A | | N/A |
| | PA System Panel Battery backup Building Floor Plans | N/A | N/A | N/A |
| | | N/A | N/A | N/A |
| | | N/A | N/A | |
| | | N/A | N/A | N/A |
| 20. | Special Fire Protection System for Protection of special Risks, if any: | | | |

NIS

The fire protection systems provided in the building were checked and found functional at the time

of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/DFS/MS/EH/2018/SZ/2307 dated 12/10/2018, renewal under rule 37 of the Delhi Fire Service

16/1)

rules 2010 is recommended.

2021

Signature of Inspecting Officer

Divisional Officer (South West)

2/11/202 0

ADO AC(JXP)