## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F6/DFS/MS/Bnqt/2021/NDZ/

Dated: 06 | 12 | 2021

## **FIRE SAFETY CERTIFICATE**

Certified that the Shree Shyam Palace (Banquet Hall) located at PD area of Mansarovar Park Metro Station, Shahdara, Delhi-110032, comprised of ground plus two upper floor owned/occupied by AVG Logistic Pvt. Ltd. was issued FSC vide letter No-F6/DFS/MS/Bnqt/2019/NDZ/1911 dated- 07/10/19 (Ground floor). The premises was inspected by the officer concerned of this department in the presence of Sh. Sanjay Aggarwal, owner and found that the building have complied with the fire prevention and fire safety requirements in accordance with rules 33 of the Delhi Fire Service Rules, 2010 and observed that the banquet hall building is fit for ground plus one upper floor occupancy class "D" 'Assembly Building' (Banquet Hall) Ground plus one floor with effect from Object 12 2022 for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on O.6 12 2021 at New Delhi by

Director
Delhi Fire Service

To.

Sh. Sanjay Aggarwal, M/s Shree Shyam Palace (Banquet Hall) PD Area at Mansarovar Park Metro Station, Shahdara. Delhi-110032

## Application ID No.-2021020310109

## Conditions for the validity of Fire Safety Certificate

All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

- 3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form `J` [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

1. Name & address of the building

: M/s Shree Shyam Palace banquet Hall

PD Area at Mansarovar Park Metro Station,

Shadhara, Delhi-110032

2. Building is comprised of

Type of Occupancy

4. Type of Case

5. Details of Previous NOC letter

6. Fire Safety directive letter No

7. Date of Inspection

8. Name of the Inspecting officers

9. Name and designation of Officer from the building side

10. Year of Construction

11. Applicant's letter No

: Ground plus two upper floors

: Assembly (Banquet Hall)

:Addition/Alteration

:F6/DFS/Ms/Bnqt/2019/NDZ/1911 dt 07/10/19 (For G Floor)

: 10/03/2021 & 21/06/2021

: ADO Mehmood

: Sh. Sanjay Aggarwal (Owner)

: 2019 & 2020

: 2021020310109 dated 05/02/21

١١.	Applicant's letter No	: 202102031	0109 dated 05/02/21				
Sr.	Minimum Standards on fire	NBC Part-IV	Provided at Site	Remark			
No.	prevention and fire safety U/R33	Requirement		MR/NM			
01	Access to building.			1011 (71410)			
	Road width	09 mtr.	28 mtr	MR			
	<ul> <li>Gate width</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Width of internal road</li> </ul>	N/A	N/A	N/A			
02	Number, Width, Type and Arrangement of Exits.						
	a. Number of Staircases						
	Upper Floor	02 nos	03 nos	MR			
	Basement	N/A	N/A	N/A			
	B. Width of Staircases			14//			
	Upper Floor	02 mtr	02 mtr, 02 mtr, & 1.70 mtr	MR			
	<ul> <li>Basement</li> </ul>	N/A	N/A	N/A			
	c. Protection of exits			14// \			
	Fire check door	Required	Provided	MD			
	<ul> <li>Pressurization</li> </ul>	N/A	N/A	MR			
	d. No. of continuous staircases	N/A		N/A			
	to terrace	IN/A	N/A	N/A			
	e. Width of Corridor	02 mtr	02 mtr	MR			
	f. No. of Doors	04 nos.	07 nos.	MR			
	g. Door Size	02 mtr.	02 mtr, 02 mtr, 02 mtr02 mtr, 1.50 mtr, 1.50mtr, 1.17 mtr, 1.17 mtr, 1.13 mtr,	MR			
)3	Compartmentation.						
	Fire check door	Required	Provided	MR			
	<ul> <li>Sealing of electrical</li> </ul>	Required	Sealed	MR			
	shafts	N/A	N/A	N/A			
	<ul> <li>Fire rating of shaft door</li> </ul>	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
_	Fire Dampers			IN/A			
4	Smoke Management System.						
	Basement	N/A	N/A	N/A			
	<ul> <li>Upper floor</li> </ul>	N/A	N/A	N/A			
5.	Fire Extinguishers.			14// \			
	Total numbers	16 nos.	22 nos.	MR			
	• types	ABC /CO <sub>2</sub>	ABC /CO <sub>2</sub>	MR			
+	IS marking	ISI marked	ISI marked				
		. S. Markou	ioi markeu	MR			
Reels	S.						

	Total number						
	Total numbers on each floor	04 No.	04 No.	MR			
	<ul><li>Length of hose reel hose</li><li>Nozzle diameter</li></ul>	30 mtr.	30 mtr.	MR			
7 /		05 mm	05 mm	MR			
	Automatic fire detection and alarming a	system.					
	<ul> <li>Type of detectors</li> </ul>	Heat & Smoke	Provided	MR			
	<ul> <li>Location of main panel</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Location of repeater panel</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Alternate source of power</li> </ul>	Battery & DG Set	Provided	MR			
	, p ,	Different	N/A	N/A			
	<ul> <li>Hooter's location</li> </ul>	Location					
-	MOEFA	Required	Provided	MR			
9	Public address System.	Required	Provided	MR			
0 /	Automatic Sprinkler System.	•					
	Basement	N/A	N/A	N/A			
				MR			
-	upper floor	N/A	Provided	-			
1	sprinkler above false ceiling     Internal Hydronte	N/A	Provided	MR			
'	Internal Hydrants						
	<ul> <li>size of riser/down-comer</li> </ul>	150 mm	150 mm	MR			
	<ul> <li>Number of hydrants per floor</li> </ul>	02 no	02 no	MR			
	<ul> <li>Hose Box</li> </ul>	02 no	02 no	MR			
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements. Provided for entire metro building						
	<ul><li>Ground Level</li><li>Discharge of main Pump</li></ul>	N/A	1800 lpm	MR			
	Head of Main Pump	N/A	70 mtrs	MR			
	> Number of main pumps	N/A	01 nos	MR			
	> Jockey pump out put	N/A	225 lpm	MR			
	> Jockey pump head	N/A	70 mtr	MR			
	Standby pump out put	N/A	1800 lpm	MR			
		N/A	70 mtrs	MR			
,	<ul><li>Standby pump Head</li><li>Auto Starting /Manual</li></ul>	N/A	Provided	MR			
	stopping						
1	> Pump House Access	N/A	Provided	MR			
	Terrace Level						
	Discharge of pump	900 Lpm.	900 Lpm.	MR			
	Head of the Pump	60 mtr	60 mtr	MR			
	Power supply	Required	Provided	MR			
	Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for Fire Fighting.	h					
	<ul> <li>Underground tank capacity</li> </ul>	N/A	1,00,000 Ltrs.	MR			
	> Draw-off connection	N/A	Provided	MR			
	Fire service inlet	N/A	Provided	MR			
	Access to tank	N/A	Provided	MR MR			
	<ul> <li>Overhead Tank capacity</li> </ul>	25,000 Ltrs.	25,000 Ltrs. Provided	MR			
15	Exit Signage.	Required	Provided	IVIT			
16							
	5 of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift Johny	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication in lift car  Time also recognized switch.	N/A	N/A	N/A			
	<ul> <li>Firemen's grounding switch</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Lift Signage</li> </ul>	1 477 1	-				

17	Standby power supply	Required	Provided	MR		
18	Refuge Area.	Hodanoa				
	Total area	N/A	N/A	N/A		
	<ul> <li>Location</li> </ul>	N/A	N/A	N/A		
19	Fire Control Room					
	Detector system panel	N/A	N/A	N/A		
	<ul> <li>Flow switch panel</li> </ul>	N/A	N/A	N/A		
	<ul> <li>PA system panel</li> </ul>	N/A	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection systems for protection of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were tested/checked at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rule, it is recommended to issue Fire Safety Certificate.

Signature of the Inspecting Officer

Please revenly Pt. no. 14 USAH Panie) capain from

DMAL.

Spoken droely Gf is 185med NOC NOW he arkey the Por reginal NOC, the 6VH - hormood tarm 2812 047 Dyco LNO22

Director My DIPAN NO 906/
NO 906/
ADDITION
ADDITION