### 0

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2021/SZ/ しつしら

Dated: 17/12/2021

# FIRE SAFETY CERTIFICATE

Certified that **Shahi Public School**, located at 3313, Street No 37, Tughlakabad Extension, New Delhi – 110019 comprised of Basement, Ground plus Two upper floor was issued Fire Safety Certificate by this department vide letter No: F6/MS/DFS/School/2017/SZ/1140 Dated 31-07-2017. The said premise was re-inspected by officer concerned of this department on 10/12/2021 in presence of Mr. Chander Rijhwani (Manager) of the school and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education Circular No 262-362 dated 17/01/2005 issued by Director of Education, Govt. of NCT of Delhi and that the building is fit for occupancy class "Educational Building Group – B" with effect from 17/12/2021 for a period of Three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on 17/122021 at New Delhi by

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER (SZ)

Copy to: -

- 1. The Principal, Shahi Public School, located at 3313, Street No 37, Tughlakabad Extension, New Delhi 110019
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054.

## Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 2. All the staff members must know the correct method of operation of firefighting system.
- 3. This certificate cannot be treated as regularization of unauthorized construction, if any.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="http://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

C-22

	INSPECTIO	<b>DN REPORT</b>			
1	Name & Address of the Building Shahi Public School, 3313, Street No 37,				
		Tughlakabad Extension, New Delhi = 110019			
2	Type of Occupancy	Educational, Group-B (School)			
3	Building Comprised of	Basement, Ground + Two upper floors			
4	Type of Case	Renewal			
5	Details of Previous NOC	F6/MS/DFS/Scl	hool/2017/SZ/1140 Dated	131-07-201	
6	Fire Safety Directives Letter No	DOE Circular 1	7/01/2005		
7	Date of Inspection	10/12/2021			
8	Name of the Inspecting Officers	Sh. Rajesh Kumar ADO (BCP)			
9	Name & Designation of Officers	Mr. Chander Rijhwani (Manager)			
	from the building side				
10	Year of construction	2005-2006			
11 C N	Applicant letter No.	Gmail dated 25/11/2021			
S. No.	Minimum standards on Fire Prevention and Fire Safety U/R 33	Old NOC requirements	Provided at Site	Remarks MR/NMR	
1.	Access to Building.				
	Road width	Required	6 mtr	MR	
	Gate width	NA	4.5 mtr	NA	
	<ul> <li>Width of internal road</li> </ul>	-NA-	=NA=	-NA-	
2.	Number, width, type & arrangement of ex	its.	1		
	a) Number of Staircase				
	Upper floors.	02 Nos	Provided	MR	
	Basement floor.	02 Nos	Provided	MR	
	b) Width of Staircase				
	Upper floors	Required	1.20m & 1.28m	MR	
	Basement floor	Required	0.93m & 1.05m	MR	
		l		(old case)	
	c) Protection of exits			()	
	Fire check door	-NA-	-NA-	-NA-	
	Pressurization	-NA-	-NA-	-NA-	
	d) No. of continuous staircase to terrace	Required	02 Provided	MR	
	e) Width of corridor	-NA-	-NA-	-NA-	
3.	f) Door size	-NA-	-NA-	-NA-	
э.	Compartmentation.		1		
	• Fire check door.	-NA-	-NA-	-NA-	
	<ul> <li>Sealing of electrical shafts.</li> <li>Fire rating of shaft door</li> </ul>	-NA-	-NA-	-NA-	
	<ul><li>Fire rating of shaft door.</li><li>Water curtain</li></ul>	-NA-	-NA-	-NA-	
	<ul> <li>Fire dampers.</li> </ul>	-NA-	-NA-	-NA-	
4.	Smoke Management system.	-NA-	-NA-	-NA-	
	Basement	Denis			
	Upper floors	Required	Exhaust fan Provided	MR	
5.		12 ACPH	NA	NA	
5.	Fire Extinguishers.				
	Total numbers	Required	08 Nos	MR	
	• Types	ABC / CO2	ABC & CO2	MR	
	ISI Marking	ISI marked	Provided		
6.	First Aid Hose Reels.			MR	
	• Total numbers on each floor.	01 No	Dros 1 1		
	• Length of hose-reel hose.	30m	Provided	MR	
		5011	Provided	MR	
	<ul> <li>Nozzle Diameter</li> </ul>	5 mm	Provided		

(

#### 1 · 1

	Location	-NA-	-11/7-	
	Total area		-NA-	-NA
18.	Refuge Area	-NA-	-NA-	-NA-
17.	Standby Power Supply	-NA-	-11/1-	1471
			-NA-	-NA
	<ul> <li>Lift signage.</li> </ul>	-NA-	-NA-	-NA
•	<ul> <li>Fireman's switch.</li> </ul>	-NA-	-NA-	-NA
	<ul> <li>Communication in lift car.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Pressurization of lift lobby.</li> </ul>	-NA-	-NA-	-NA-
16.	Provision of Lifts.     Pressurization of lift shaft.	-NA-	-NA-	-NA-
15.	Exit Signage. Provision of Lifts.	Required		
	Overhead tank capacity.	Required	Provided	MR
	Access to tank.	5,000 ltr	Provided	MR
	<ul> <li>Fire Service Inlet.</li> </ul>	-NA- -NA-	-NA- -NA-	-NA-
	<ul> <li>Draw-off connection.</li> <li>Diagonal provides the last</li> </ul>	-NA- -NA-	-NA- -NA-	-NA- -NA-
	Underground tank capacity.	-NA-	-NA-	-NA-
14.	Captive water storage for fire fighting.		NT A	<b></b>
	> Auto starting of pump.	-NA-	-NA-	-NA-
	Power supply.	Required	Provided	MR
	Head of pump.	40 m	Provided	MR
	Discharge of pump.	450 LPM	450 & 180 LPM	MR
	Terrace Level			
	Pump house access.	-NA-	-NA-	-NA-
	Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	<ul> <li>Standby Pump output.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Jockey Pump head.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Jockey Pump output.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Number of main pumps.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Head of main pump.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Discharge of main pump.</li> </ul>	-NA-	-NA-	-NA-
10,	Ground Level			
13.	Pumping arrangements.	1121	111.	
	<ul> <li>Hose box.</li> </ul>	-NA-	-NA-	-NA-
	Total number of hydrants.	-NA-	-NA-	-NA-
12.	Vard Hydrants.	-11/12-	UI	-11/1-
	<ul><li>Number of Hydrant per floor</li><li>Hose box.</li></ul>	-NA- -NA-	01	-NA-
	Size of Riser/Down-comer	Required -NA-	Provided 01	MR -NA-
11.	Internal Hydrants.	Den 1	D	
1.	Sprinkler above false ceiling	-NA-	-NA-	-NA-
	• Upper floors	-NA-	-NA-	-NA-
	• Basement	Required	Provided	MR
10.	Automatic Sprinkler System			
9.	Public Address System	-NA-	-NA-	-NA-
8.	MOEFA	-NA-	-NA-	-NA-
	Hooter's location			-NA-
		-NA-	-NA-	
	Alternate source of power	-NA-	-NA-	-NA-
	Location of Repeater Panel	-NA-	-NA-	-NA-
	<ul> <li>Location of Main Panel</li> </ul>	-NA-	-NA-	-NA-
		the second se	-NA-	-NA-



	<ul> <li>Flow switch panel.</li> </ul>			
20,	<ul> <li>PA system panel.</li> <li>Battery backup.</li> <li>Building floor plan.</li> </ul>	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
20.	Special Fire Protection System for the Protection of special Risk, if any.			-NA-

The fire protection systems provided in the premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/MS/DFS/School/2017/SZ/1140 Dated 31-07-2017, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar Design: ADO (BCP)

DO (SØ

DU

As approved, F.T. retter fore signature BI

-11

Dy Gollsz