GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE CONNAUGHT PLACE: NEW DELHI-110001

F.6/DFS/MS/2021/SZ/ 625

FIRE SAFETY CERTIFICATE

Certified that the Staff Quarters (Type-I, II & III) & Community Centre for Reserve Bank of India at Hauz Khas, New Delhi, having four residential blocks each comprised of Ground plus five upper floors and Community Hall (Block A) comprised of Ground plus one upper floor was inspected by officer concerned of this department on 14/12/2021 in presence of Mr. Pratyush Kr. Singh (JE/SDMC), Mr. Vineet Goel and found that the said residential blocks and community centre have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises [Resdl. Blocks Type-I, II, III] is fit for occupancy class Residential-Group 'A' and [Community Centre (Block A)] Assembly-Group 'D' with effect from the date of issue of this certificate for a period of Five years (Resdl. Blocks) and Three years (Community Centre) in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 17 12 /2021 at New Delhi by

Delhi Fire Service

Dated: 7/12/2021

Copy to: -

- 1. The Executive Engineer (Bldg), HQ, South Delhi Municipal Corporation, 9th Floor, Civic Centre, Minto Road, New Delhi-110002
- 2. Authorized Signatory, M/s Reserve Bank of India. Sansad Marg, New Delhi-110001

Conditions for the validity of Fire Safety Certificate

- 1. The FSC issued by this department vide letter no. F.6/DFS/MS/2021/SZ/562 dated 16/11/2021 for residential blocks only stands null and void.
- 2. All the means of escape/entry/exit shall be kept free from any obstruction.
- 3. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.
- 4. All the staff members must know the correct method of operation of fire fighting system.
- 5. The owner/occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in
- 6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

		INSPECTION	REPORT				
1	Na	me & Address of the Building	Staff Quarters (Type-I, II & III) & Community Centre for Reserve Bank of India at Hauz				
,	r		Khas, New Del		2.119.45		
2	17	pe of Occupancy	Group 'A' (Residential Flats)				
,,	100	llding Comprised of	Type=1 (01 Blk), Type=II (02 Blk) & Type III (01 Blk)= Each Ground + 05 Upper Floors and Community Centre (Block A): G + 01				
4	Tv	pe of Case	AND THE RESIDENCE OF THE PARTY	ntre	(Block A): O + G	1	
5		tails of Previous NOC	New Nil				
6		e Safety Directives Letter No		016/	DD/212 dated 31/	08/2016	
7		te of Inspection	F.6/DFS/MS/2016/BP/213 dated 31/08/2016				
8		me of the Inspecting Officers	14/12/2021				
()	Na	me & Designation of Officers	DO (SD) Mr. Drotyarch Kr. Singh (IE/SDMC)				
	from the building side		Mr. Pratyush Kr. Singh (JE/SDMC). Mr. Vincet Goel				
10		ar of construction	2021				
11		plicant letter No.	Online ID: 10093907 dated 08/12/2021				
S.	M	nimum standards on Fire Prevention	NBC/UBBL	1	Provided at	Remarks	
No.	an	d Fire Safety U/R 33	Requirements		Site	MR/NMI	
1	Ac	cess to Building.	requirements		Site		
		Road width	12m		24m	MR	
		Gate width	6m		Provided	MR	
		 Width of internal road 	6m & 9m T/C		Provided	MR	
2	Nı	mber, width, type & arrangement of ex-	vite		Trovided	1111	
	a)	Number of Staircase					
		△ Upper floors.	Resdl. Blk: 02 No	os	Provided	MR	
		Basement floor.	Com. Ctr: 04 No:	S			
	b)	Width of Staircase	-NA-		-NA-	-NA-	
	0)	- Upper floors	Resdl. Blk: 1.35r Com. Ctr: 2m, 1.5		Resdl. Blk: 1.35m ea Com. Ctr: 1 of 2m, 2	of	
		➤ Basement floor	-NA-		1.5m & 1.5m (spira -NA-	-NA	
	c)	Protection of exits	1111		-1477-	-11/1	
		Fire check door	-NA-		-NA-	-NA-	
		Pressurization	-NA-		-NA-	-NA-	
	d)	No. of continuous staircase to terrace	02 each Blk		Provided	MR	
	e)	Width of corridor	-NA-		-NA-	-NA-	
	f)	Door size	Required		Provided	MR	
3	Co	mpartmentation.					
		 Fire check door. 	Required		Provided	MR	
		 Sealing of electrical shafts. 	Required		Provided	MR	
		 Fire rating of shaft door. 	Required		Provided	MR	
		Water curtain	-NA-		-NA-	· -NA-	
		Fire dampers.	-NA-		-NA-	-NA-	
4	Sn	noke Management system.					
		Basement	30 ACPH		-NA-	-NA-	
		Upper floors	12 ACPH	Na	ıtural Ventilation	MR	
5	Fi	re Extinguishers.					
		Total numbersTypes	ISI marked	(esdl. Blk: 20 Nos Com. Ctr: 12 Nos	MR	
		ISI Marking		F	ABC & W.CO2	MR	
6	E:				Provided	MR	
U	Г	rst Aid Hose Reels. Total numbers on each floor.	Resdl. Blk: 02 1 Com. Ctr: 03 N		Provided	MR	
	1	 Length of hose-reel hose. 			-		
		Length of hose-reel hose.Nozzle Diameter	30m		Provided	MR	

7	Automatic fire detection & alarming system.					
	Type of detectors	-ΝΛ-	-NA-	-NA-		
	Location of Main Panel	-NA-	-NA-	-NA-		
	Location of Repeater Panel	-NA-	-NA-	-NA-		
	Alternate source of power	-ΝΛ-	-ΝΛ-	-NA-		
	Hooter's location	-ΝΛ-	-NA-	-NA-		
8	MOEFA	Required	Provided	MR		
9	Public Address System	-NA-	-NA-	-NA-		
10	Automatic Sprinkler System	1471				
	Basement	-NA-	-NA-	-NA-		
	Upper floors	-NA-	-NA-	-NA-		
	 Sprinkler above false ceiling 	-NA-	-NA-	-NA-		
11	Internal Hydrants.	-11/71-	-11/1-	-1471-		
11	Size of Riser/Down-comer	100mm	Provided	MR		
		Resdl. Blk: 02 Nos		MR		
	 Number of Hydrant per floor 	Com Ctr: 03 Nos	Provided	IVIK		
	Hose box.	Resdl. Blk: 02 Nos Com Ctr: 03 Nos	Provided	MR		
12	Yard Hydrants.	20 21. 05 1405	-1			
	Total number of hydrants.	-NA-	-NA-	-NA-		
	Hose box.	-NA-	-NA-	-NA-		
13	Pumping arrangements.		1 47 %	1471		
	Ground Level					
	 Discharge of main pump. 	-NA-	-NA-	NA-		
	Head of main pump.	-NA-	-NA-	-NA-		
	Number of main pumps.	-NA-	-NA-	-NA-		
	Jockey Pump output.	-NA-	-NA-	-NA-		
	 Jockey Pump head. 	-NA-	-NA-	-NA-		
	 Standby Pump output. 	-NA-	-NA-	-NA-		
	Standby Pump head.	-NA-	-NA-	-NA-		
	Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-		
	Pump house access.	-NA-	-NA-	-NA-		
	Terrace Level					
	 Discharge of pump. 	900 LPM	900 LPM each Bl	k MR		
	 Head of pump. 	40m .	Provided	MR		
	Power supply.	Required	Provided	MR		
	Auto starting of pump.	Required	Provided	MR		
14	Captive water storage for fire fighting.					
	Underground tank capacity.	-NA-	-NA-	-NA-		
	Draw-off connection.	-NA-	-NA-	-NA-		
	Fire Service Inlet.	Required	Provided			
	Access to tank.	-NA-	-NA-	-NA-		
	 Overhead tank capacity. 	Resdl. Blk: 25,00		l MR		
15		Com. Ctr: 15,000	Ltr	17110		
16		Required	Provided	MR MR		
10	Pressurization of lift shaft.	Required	Provided			
		-		MR		
	i ressurization of the loody.	-NA-	-NA-	-NA-		
	• Communication in lift car.	Required	Provided	MR		
	• Fireman's switch.	Required	Provided	MR		
	Lift signage.	Required	Provided	MR		
1'	The supply	Required	Provided			
18			, and a	MR		
	Total area	-NA-	-NA-	NI A		
	 Location 	-NA-	-NA-	-NA		
-			-1 A \-/-\	-NA		

19	Fire Control Room.			
	 Detector system panel. 	-NA-	-NA-	-NA-
	 Flow switch panel. 	-NA-	-NA-	-NA-
	 PA system panel. 	-NA-	-NA-	-NA-
	 Battery backup. 	-NA-	-NA-	-NA-
	 Building floor plan. 	-NA-	-NA-	-NA-
20	Special Fire Protection System for the Protection of special Risk, if any.	04 Nos ABC type fire extinguishers provided for electrical panel		MR

The Fire protection systems provided in the premises were checked, tested at random and found functional at the time of inspection.

Keeping in view of the substantial satisfactory compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, it is recommended to issue Fire Safety Certificate under Rule 35 of the Delhi Fire Service Rules, 2010.

Accordingly. DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: S.K. Dua Designation: DO (SD)

DCFO (SZ)

CFO- D. Off Oisecto Mills/n

7.7. letter is put up for sty plea

Mobile ctory Mygu

mu