1

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/EH/2021/SZ/ 384

Dated: 29/12/2021

## FIRE SAFETY CERTIFICATE

Certified that M/s Andreas Bistro (A unit of Eatinc Food and Beverages Pvt. Ltd) located at Property No. 307, Second Floor, DLF Promenade Mall, Nelson Mandela Marg, Vasant Kunj, New Delhi-110070 in a building comprised of Two Tiers Basement, Lower Ground, Upper Ground floor and First Floor & Projection room owned/ occupied by Mr. Andrea Aftab Pauro have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Delhi Fire Service on 15/04/2021 in the presence of Mr. Prashant Khurana and that the premise is fit for occupancy class Group—D Assembly Building (Restaurant running at Second floor only) with effect from 29 / 2021 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 29/12 /2021 at New Delhi by

(ATUL SANG) PIRECTOR / DFS

Copy to: -

- 1. The Joint Comm. of Police (Lic.), First floor, P.S. Defence Colony, New Delhi-110049
- 2. The DHO, (South Zone), SDMC, Public Health Department, Aurobindo Marg, Green Park, New Delhi-110016. (Ref. MHA Portal ID 2021102625125 dated 19/11/2021)
- 3. M/s Andreas Bistro (A unit of Eatinc Food and Beverages Pvt. Ltd) Situated at Pro. 307 Second Floor, DLF Promenade Mall, Nelson Mandela Marg, Vasant Kunj, New Delhi-110070

## Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire-fighting system.
- 4. The owner/occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

			ON 222				
1	N		ON REPORT	D' 4 (A '4 CE 4' E			
1	142	me & Address of the Building	M/s Andreas Bistro (A unit of Eatinc Food and Beverages Pvt. Ltd) Situated at Pro. 307 Second Floor, DLF Promenade Mall, Nelson Mandela Marg, Vasant Kunj, New Delhi-110070				
2	Ty	pe of Occupancy		ding "Group-D" Restaura	nt		
3	-	ilding Comprised of	_	nent, LGF, UGF, 1 <sup>st</sup> Floo			
4	-	pe of Case		name Namak Mandi			
5	-	tails of Previous NOC	Nil				
6	-	e Safety Directives Letter No	UBBL-2016				
7	-	te of Inspection	14/12/2021				
8	-	me of the Inspecting Officers	Sh. Rajesh Kumar ADO (BCP)				
9	-	me & Designation of Officers	Mr. Prashant Khurana				
		om the building side	nurana				
10		ar of construction	2005 Restaurant running at 2 <sup>rd</sup> Floor in DLF Promenade Mall building.				
11	Ap	plicant letter No.	MHA Portal ID	2021102625125 dated 1			
S. No.	an	nimum standards on Fire Prevention d Fire Safety U/R 33	Requirement/ Existing Fire Protection	Provided at Site	Remarks MR/NMR		
1	Access to Building. FSC No.F.6/DFS/MS/Mall/2020/SZ/58 Dated 22/01/2020 of DLF Promenade Ma						
		Road width	Restaurant	As above	MR		
		Gate width	within Mall	As above	N/A		
		<ul> <li>Width of internal road</li> </ul>		As above	N/A		
2	Nu	mber, width, type and arrangements of	fexits.				
	a.	Number of Staircase	T	<b>Maintained by DLF Pron</b>	renade Mall		
		Upper floors	02 Nos	As above	MR		
		Basement floor	N/A	As above	N/A		
	b.	Width of Staircase		Taintained by DLF Pron	1		
		Upper floors	Required	As above	MR		
		Basement floor	N/A	As above	N/A		
	c.	Protection of exits		Iaintained by DLF Prom			
		Fire check door	Required	As above			
		Pressurization	N/A		MR		
	d.	No. of continuous staircase to terrace		As above	N/A		
	e.	Width of corridor	Required	As above	MR		
	f,	Door size	N/A	N/A	N/A		
	• •	5001 8120	02 Exits 1.50 mtr each	1.50 m & 1.50 m	MR		
3	Co	mpartmentation.					
		Fire check door.	Provided & M	laintained by DLF Prom			
,			Required	As above	MR		
		Sealing of electrical shafts.  Five ration of the Colors	N/A	As above	N/A		
		Fire rating of shaft door.  Water custoin	N/A	N/A	N/A		
		Water curtain     Fine demonstrates	N/A	N/A	N/A		
1	C	• Fire dampers.	N/A	N/A	N/A		
4.	Sm	oke Management system.	Provided & M	laintained by DLF Prom	enade Mall		
		Basement	N/A	As above	N/A		
		• Upper floors	Required	Exhaust fans provided	MR		
5.	Fir	e Extinguishers.					
		Total numbers	06 Nos	06 Nos.	MR		
		• Types		ABC-04, W.CO <sub>2</sub> -02	MR		
		ISI Marking	ISI marked	Provided	MR		
6.	Fir	st Aid Hose Reels.	Provided & M	laintained by DLF Prom	IVIK		
		Total numbers on each floor.		One in Restaurant			
		Length of hose-reel hose.	Hose Reel	30m	MR		
		Nozzle Diameter		5mm	MR		
	_			Simm	MR		

	Automatic Fire Detection and Alarming s	ystem. ( Provided &	Maintained by DLF Prom	enade Mali
	Type of detectors	Required	Smoke & Heat	MK
	Location of Main Panel	Required	As above	MR
	<ul> <li>Location of Repeater Panel</li> </ul>	N/A	N/A	N/A
	Alternate source of power	Required	As above	MR
	Hooter's location	Required	As above	MR
8.	MOEFA	Required	As above	MR
9.	Public Address System	Required	As above	MR
0.	Automatic Sprinkler System	Provided & M	aintained by DLF Pror	nenade Ma
	Basement	Required	As above	MR
	Upper floors	Required	Provided in Restt.	MR
	Sprinkler above false ceiling	N/A	N/A	N/A
	•		aintained by DLF Pron	nenade Ma
11.	Internal Hydrants.	Required	As above	MR
	Size of Riser/Down-comer  Size of Riser/Down-comer	Required	As above	MR
	Number of Hydrant per floor	Required	As above	MR
	Hose box.	Dussided & M	aintained by DLF Pron	enade Ma
12.	Yard Hydrants.	N/A	As above	N/A
	Total number of hydrants.	N/A N/A	As above	N/A
	• 2. Hose box.	IN/A	113 40010	
13.	Pumping arrangements.	Duoridad 0. M	aintained by DLF Pron	enade Ma
	Ground Level		As above	MR
	Discharge of main pump.	4500 LPM	As above	MR
	Head of main pump.	70 mtrs	As above	MR
	Number of main pumps.	Two	As above	MR
	Jockey Pump output.	70 mtrs	As above	MR
	Jockey Pump head.	4500 LPM	As above	MR
	> Standby Pump output.	70 mtrs	As above	MR
	> Standby Pump head.	Required	As above	MR
	Auto Starting / Manual Stopping.	Required	As above	MR
	> Access to pump house		aintained by DLF Prom	enade Ma
	Terrace Level	N/A	N/A	N/A
	Discharge of pump.	N/A	N/A	N/A
	Head of pump.	N/A	N/A	N/A
	> Power supply.	N/A	N/A	N/A
	<ul><li>Auto starting of pump.</li><li>Captive water storage for Fire Fighting.</li></ul>		aintained by DLF Prom	enade Mal
14.	Confive water storage for Fire righting.	I I U VILLE CO CO		
14.	Captive water storage		As above	MR
14.	<ul> <li>Underground tank capacity.</li> </ul>	5,00,000 Ltrs	As above As above	MR MR
14.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> </ul>	5,00,000 Ltrs Required		MR
14.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> </ul>	5,00,000 Ltrs Required Required	As above	MR MR
14.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> </ul>	5,00,000 Ltrs  Required  Required  Required	As above As above	MR MR MR
14.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> </ul>	5,00,000 Ltrs Required Required Required 20,000 Ltrs	As above As above As above	MR MR MR MR
15.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> </ul> Exit Signage.	5,00,000 Ltrs Required Required Required 20,000 Ltrs Required	As above As above As above As above Provided	MR MR MR MR MR MR
15.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> </ul>	5,00,000 Ltrs Required Required Required 20,000 Ltrs Required Provided & M	As above As above As above As above Provided aintained by DLF Pron	MR MR MR MR MR MR
15.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> </ul>	5,00,000 Ltrs Required Required 20,000 Ltrs Required Provided & M N/A	As above As above As above As above Provided aintained by DLF Prom	MR MR MR MR MR MR
15. 16.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift lobby.</li> </ul>	5,00,000 Ltrs Required Required 20,000 Ltrs Required Provided & M N/A N/A	As above As above As above As above Provided aintained by DLF Prom N/A N/A	MR MR MR MR MR MR MR enade Ma
15.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift lobby.</li> <li>Communication in lift car.</li> </ul>	5,00,000 Ltrs Required Required 20,000 Ltrs Required Provided & M N/A N/A N/A	As above As above As above As above Provided aintained by DLF Prom N/A N/A N/A	MR MR MR MR MR MR MR MR N/A
15.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift lobby.</li> <li>Communication in lift car.</li> <li>Fireman's switch.</li> </ul>	5,00,000 Ltrs Required Required 20,000 Ltrs Required Provided & M N/A N/A N/A N/A	As above As above As above As above Provided aintained by DLF Prom N/A N/A N/A N/A N/A	MR MR MR MR MR MR N/A N/A
15. 16.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift lobby.</li> <li>Communication in lift car.</li> <li>Fireman's switch.</li> <li>Lift signage.</li> </ul>	5,00,000 Ltrs Required Required 20,000 Ltrs Required Provided & M N/A N/A N/A N/A N/A N/A N/A	As above As above As above As above Provided aintained by DLF Prom N/A N/A N/A N/A N/A N/A N/A	MR MR MR MR MR MR MR N/A N/A N/A N/A
15.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift lobby.</li> <li>Communication in lift car.</li> <li>Fireman's switch.</li> <li>Lift signage.</li> <li>Standby Power Supply</li> </ul>	5,00,000 Ltrs Required Required 20,000 Ltrs Required Provided & M N/A N/A N/A N/A	As above As above As above As above Provided aintained by DLF Prom N/A N/A N/A N/A N/A	MR MR MR MR MR MR enade Ma N/A N/A N/A N/A
15. 16.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift car.</li> <li>Fireman's switch.</li> <li>Lift signage.</li> <li>Standby Power Supply</li> <li>Refuge Area</li> </ul>	5,00,000 Ltrs Required Required 20,000 Ltrs Required Provided & M N/A N/A N/A N/A N/A N/A N/A Required	As above As above As above As above Provided aintained by DLF Prom N/A N/A N/A N/A N/A N/A Provided (DG Set)	MR MR MR MR MR MR MR MR N/A N/A N/A N/A N/A
15. 16.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift lobby.</li> <li>Communication in lift car.</li> <li>Fireman's switch.</li> <li>Lift signage.</li> <li>Standby Power Supply</li> </ul>	5,00,000 Ltrs Required Required 20,000 Ltrs Required Provided & M N/A	As above As above As above As above Provided aintained by DLF Prom N/A	MR MR MR MR MR MR MR MR N/A N/A N/A N/A N/A N/A N/A
15. 16.	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> <li>Access to tank.</li> <li>Overhead tank capacity.</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of lift shaft.</li> <li>Pressurization of lift car.</li> <li>Fireman's switch.</li> <li>Lift signage.</li> <li>Standby Power Supply</li> <li>Refuge Area</li> </ul>	5,00,000 Ltrs Required Required 20,000 Ltrs Required Provided & M N/A	As above As above As above As above Provided aintained by DLF Prom N/A N/A N/A N/A N/A N/A Provided (DG Set)	MR MR MR MR MR MR MR MR N/A

	The state of the s	N/A	As above	N/A
	Flow Switch Panel.  Panel	N/A	As above	N/A
	PA system Panel.  Party backup	N/A	As above	N/A
	Battery backup     Building floor plan	N/A	As above	N/A
20.	Special Fire Protection System for the	N/A	As above	N/A

Protection of special Risk, if any: The Fire protection systems provided in the building were test checked at random and found functional at the

Further, the party has complied all the observation / Shortcoming already issued & communicated by this department vide letter of even no 934 dated 30/12/2020 for the name of M/s Namak Mandi Restaurant.

Keeping in view of the substantially satisfactory compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, it is recommended to issue Fire Safety Certificate under rule 35 (3) of the Delhi Fire Service Rules, 2010.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Rajesh Kumar

Designation: ADO / BCP