GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / 2019 / Schal / 1516

Dated: 24/07/2019

C-56

FIRE SAFETY CERTIFICATE

Certified that the New Green Valley Public School, located at B-Block, Street no. 111, Sant Nagar, Burari, Delhi comprised of ground & 02 upper floor(School is running on ground & first floor only) owned/ occupied by the New Green Valley Public School was issued fire safety certificate vide this office letter no. F.6/DFS/MS/2016/380 dated 10/03/2016. The premises was re-inspected by the officer concerned of this department on 28.06.2019 in the presence of Mrs. Prerna Rautela, Principal and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition. The premises have deemed complied with requirements of circular issued by Director of Education letter no 3298-3398 dated 01.03.2011and the building/ premise is fit for occupancy Group B Educational with effect from M_1 for a period of three years, subject to compliance of the conditions mentioned below:

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>
- 8. School Management has given an undertaking that the school will only be run on ground and first floor only.

Chief Fire C Ph:-011-23414

Copy to : -

- 1. The Director, Education, Government of N.C.T of Delhi. Old Sectt. Delhi 54.
- 2. The Principal, New Green Valley Public School, B-Block, Street no. 111, Sant Nagar, Burari, Delhi.

		<u>INSPEC</u>	TION REPORT			
1	Name & address of the building		reen Valley Public School, Gali No. 111, B- Block, Sant,			
2	Type of Occupancy	Nagar, Burari, Delhi. : Educational- (Ground & 02 upper floor)				
3	Type of Case		: Renewal			
4	Details of previous NOC	vious NOC :F6/DFS/MS/2016/380 Dated: 11.06.2019				
 5 Fire Safety directives letter No 6 Date of inspection : 28/06/2019 				Letter dated 01.03.201	1	
7	Name of the Inspecting Officers					
8	Name and designation of officer					
	from the building side	: Sh. N	1rs Prerna Rautela	, Principal		
9.	Year of Construction	: 2009/	/2014	· · · · ·		
10	. Applicant's letter No.	: Nil da	ated 11.06.2019		1	
	lot Area- 1880 sq.y Covered Area:22		class rooms –)8 nos stud	ients – 250nos	
1				Provided at site	Domonic	
	Minimum Standards on fire pre- and fire safety U/R 33	vention	Dir. Of Education	Provided at site	Remarks MR/NMR	
	Access to building			đ.		
-	· · · · · · · · · · · · · · · · · · ·		бт	6m	MR	
	Road width					
	Gate width Width of internal road		Directly Accessible	Directly Accessible	MR	
			NA	NA	NA	
I	Number, Width, Type & Arrangement of Exits					
a	; Number of staircases		1			
	Upper Floors		02	02	MR	
		Basements			NA	
•	• Basements		NA	NA		
b	• Basements Width of staircases	-	NA	NA		
b.		-	NA 1.50m	0.77 to 0.88m, 0.90	MR(old case	
b	Width of staircases	-		0.77 to 0.88m, 0.90 to 0.99m	`	
-	Width of staircasesUpper Floors	-	1.50m NA	0.77 to 0.88m, 0.90	MR(old case NA	
-	 Width of staircases Upper Floors Basements 		1.50m NA	0.77 to 0.88m, 0.90 to 0.99m	`	
-	 Width of staircases Upper Floors Basements Protection of exits 		1.50m NA NA	0.77 to 0.88m, 0.90 to 0.99m NA	NA	
c.	 Width of staircases Upper Floors Basements Protection of exits Fire check door 	ace	1.50m NA	0.77 to 0.88m, 0.90 to 0.99m NA NA	NA	
c.	 Width of staircases Upper Floors Basements Protection of exits Fire check door Pressurization 	ace	1.50m NA NA NA	0.77 to 0.88m, 0.90 to 0.99m NA NA NA	NA NA	

2)26

R

Ĉ s

w/22



	e. Width of Corridor	NA	NA			
	f. Door Size	1.0m	NA Immultiple Cont	NA		
3	Compartmentation.	1.011	1m with door fittings	MR		
	• Fire check door					
		NA	NA	NA		
	• Sealing of electrical shafts	NA	NA	NA		
	• Fire Rating of shaft door	NA	NA	NA		
	• Water Curtain	NA	NA	NA		
	• Fire Dampers	NA	NA	NA		
4	Smoke Management System.					
	Basements	NA	NA	NA		
	• Upper floors	NA	NA			
5	Fire Extinguishers			NA		
	Total multiple in the second s					
		6nos	8 nos	MR		
	• Types	ABC/Co2	ABC8	MR		
6	ISI marking	Yes	Yes	MR		
6	First-Aid Hose Reels.					
	• Total numbers on each floor	- 01	01	MR		
	• Length of hose reel hose	30m	30m	MR		
	Nozzle diameter	5mm	5mm	MR		
7	Automatic fire detection and alarming system					
	• Type of detectors	NA	NA	NA		
	Location of Main Panel	NA	NA	NA		
	Location of Repeater Panel	NA	NA	NA		
	Alternate source of power	NA	NA	NA		
	Hooters' Location	NA	NA	NA		
8	MOEFA	NA	NA	NA		
9	Public Address System.	NA	NA	NA		
10	Automatic Sprinkler System.					
	Basement	NA	NA	NA		
	Upper Floor	NA	NA	NA		
	• Sprinkler above false ceiling	NA	NA	NA		
11	Internal Hydrants					
	(4					

M/28

1	• Size of riser/down-comer	NA	NA	NA		
	 Number of hydrants per floor 	NA	NA	NA		
	 Hose Box 	NA	NA	NA		
2	Yard Hydrants.			1		
-	Total number of hydrants	NA	NA	NA		
	 Hose Box 	NA	NA	NA		
3	Pumping Arrangements.					
	Ground Level		27/4	N/A		
	Discharge of main Pump	N/A	N/A			
	Head of Main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	> Jockey Pump out put	N/A	N/A	N/A		
	> Jockey pump head	N/A	N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
	> Standby Pump Head		N/A	N/A		
	> Auto Starting/ Manual stopping	N/A		N/A		
	Pump House Access	N/A	N/A	IN/A		
	• Terrace level					
	Discharge of pump	450 lpm	450 lpm	MR		
	Head of the pump	40m	40m	MR		
	> Power Supply	Required	Provided	MR		
	> Auto Starting of pump	Required	Provided	MR		
1	Captive Water Storage for fire fighting.					
4		NA	NA	NA		
	Underground tank capacity	NA	NA	NA		
	Draw-off connection	NA	NA	NA		
	Fire service inlet	NA	NA	NA		
	Access to tank	10000 ltr	Provided	MR		
	 Overhead Tank capacity 	Required	Provided	MR		
	Exit Signage.	Kequireu	11011000			
5	Provision of Lifts.	N/A	N/A	N/A		
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby		N/A	N/A		
	 Communication In lift Car 	N/A	11/71			

R

N/29

,		
N/A	N/A	N/A
N/A	N/A	N/A
N/A	N/A	N/A
N/A	N/A	N/A ·

18	Refuge Area.			
	Total Area	N/A	N/A	N/A
	Location	N/A	N/A	N/A
19	Fire Control Room			
	Detector System Panel	N/A	N/A	N/A ·
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	
	Building Floor Plans	N/A		N/A
20	Special Fire Protection Systems for	N/A N/A	N/A N/A	N/A
	Protection of special Risks, if any:	11/7	IN/A	N/A

Fireman's Grounding Switch

Lift Signage

Standby power supply

•

17

10

The fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in Director of Education Circular dated 17.01.2005 the FSC issued vide letter of even no 380 dated 10.03.2016 renewal under rule 35 of the Delhi Fire Service Rules, 2010 is recommended

1577/19

Signature of the Inspecting Officer Name :- Rajesh Kumar

Designation:- ADO/RN

Kny abm

Undertaking by Brincipal of school is actained and puttip on opposite on file. Accordingly, F.J. is prepared and puttip for your signature Plink [10] MX/ 1.0