GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/Metro/2021/SZ/ OS

FIRE SAFETY CERTIFICATE

Certified that "Ghitorni Metro Station of Qutab Minar-Gurgaon Corridor, New Delhi comprised of Ground + Concourse & platform floor was issued Fire Safety Certificate by this department vide letter no F6/DFS/MS/2010/1244 dated 29.04.2010. The premise was reinspected by the officer concerned of this department on 21/12/2021 in the presence of Mr. Ashish (Fire-inspector) and found that the said metro station building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class-D "Assembly Occupancy Metro railway" as above with effect from __OS_/_O_/_/202\text{Q} for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on _05-/ 61 /2029 at New Delhi by

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER (SZ)

Dated: 05 / 01 /202

Copy to: -

1. Mr. Vivek Srivastava, (JGM/E&M) Delhi Metro Rail Corporation, Metro Bhawan, 13, Fire Brigade Lane, New Delhi-110001.

Conditions for the validity of Fire Safety Certificate: -

- 1. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 2. All the staff members must know the correct method of operation of fire fighting system.
- 3. The basement shall be used strictly as per the provision of Building Bye Laws.
- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

45

INSPECTION REPORT

1. Name & address of the building: Ghitorni Metro Station, of Qutab Minar-Gurgaon Corridor, New Delhi.

2. Type of Occupancy : Assembly D-7 (Metro Station)

3. Type of Case :Renewal (Ground Level + Concourse + Platform Level)

Details of previous NOC : F6/DFS/MS/2010/1244 dated 29.04.2010
 Fire Safety directives letter No : F6/DFS/MS/BP/2009/856 dated 25.03.2009

6. Date of inspection : 21.12.2021

7. Name of the Inspecting Officers : Sh. Rajesh Kumar, ADO (BCP)

8. Name and designation of officers

from the building side : Mr. Ashish, Fire Inspector

9. Year of Construction :2010

10. Applicant's letter No. :Gmail Dated: 09.12.2021

io		nimum Standards on fire prevention fire safety U/R 33	NBC Requirement		Remarks MR/NMR					
	Access to building									
		Road width	As per PWD	Provided	MR					
		Gate width	Required	Approx 06 mtr	MR					
		Width of internal road	As per NBC	6 mtr	MR					
	Number, Width, Type & Arrangement of Exits									
a. Number of staircases										
		Upper Floors	04nos Concourse to platform 02 nos ground to Concourse	Provided	MR					
		Basements Width of staircases	NA	NA.	NA					
		Upper Floors concourse to								
		platform	As per NBC	PF to CC- 3.35 mtr (02 Nos) 1.90 m + 1 m escalator (02 Nos) CC- to Ground 2.35 mtr (02 Nos) 1 mtr escalator (02 Nos)						
		Basements	NA	NA	NA					
	c.	Protection of exits								
		Fire check door	Required	Provided	MR					
		Pressurization	NA	NA	NA					
	d	No of continuous staircases to terrace	02	Provided	MR					
	e.	Width of Corridor	2 m	2 m	MR					
	f.	Door Size	Required	1.9m	MR					
	Compartmentation.									
		Fire check door	Required	Provided	MR					
		 Sealing of electrical shafts 	Required	Provided	MR					
		 Fire Rating of shaft door 	Required	Provided	MR					
		Water Curtain	NA	NA	NA					
		• Fire Dampers	N/A	N/A	N/A					
	Smoke Management System.									
-		 Basements 	30АСРН	NA	NA					
		 Upper floors 	12ACPH	NA	NA					

5	Fire Extinguishers								
-	Total numbers	20nos	20nos	MR					
	• Types	ISI marked	Provided	MR					
	TS marking		D						
_	First-Aid Hose Reels.	Required	Provided	MR					
5	Total numbers on each floor	04 – platform level	04 – platform level	MD					
	Total numbers on each noor	02 – concourse level	02 – concourse level	MR					
	Length of hose reel hose	45m	45m	MR					
	Nozzle diameter	5mm	5mm	MR					
7	Automatic fire detection and alarming syste	em.							
	Type of detectors	Smoke	Provided	MR					
	Location of Main Panel	Required	Provided	MR					
	Location of Repeater Panel	NA	NA	NA					
	Alternate source of power Hooters' Location	Required	Provided	MR					
		Required	Provided	MR					
8	MOEFA	Required	Provided	MR					
9	Public Address System.	Required	Provided	MR					
10	Automatic Sprinkler System.								
	Basement	NA	NA	NA					
	Upper Floor	NA	NA	NA					
	Sprinkler above false ceiling	NA	NA	NA					
11	Internal Hydrants								
	Size of riser/down-comer	150mm	Provided	MR					
	Number of hydrants per floor	Required	Platform each-02	MR					
	Hose Box	Required	Concourse - 02 Platform each-02 Concourse - 02	MR					
12	Yard Hydrants.								
	Total number of hydrants	02 Nos	02 Nos	MR					
	Hose Box	02 Nos	02 Nos	MR					
13	Pumping Arrangements.	1	,						
	> Ground Level								
	 Discharge of main Pump 	1800 Lpm	1800 LPM	MR					
	➤ Head of Main pump	60 mtr	60m	MR					
	> Number of main pumps	01	01	MR					
	> Jockey Pump out put	180 LPM	180 LPM	MR					
		60 m	60m	M/R					
	>	1800LPM	1800 LPM	MR					
	Standby Pump out put	60 mtr	60m	MR					
	Standby Pump HeadAuto Starting/ Manual stopping	Required	Provided	MR					
	> Pump House Access	Required	Provided	MR					
	Terrace level								

Discharge of pump	NA	NA	NA				
Head of the pump	NA	NA	NA				
Power Supply	NA	NA	NA				
➢ Auto Starting of pump	NA	NA	NA				
Captive Water Storage for fire fighting.							
Underground tank capacity	50,000ltrs	50,000ltrs	MR				
> Draw-off connection	Required	Provided	MR				
Fire service inlet	Required	Provided	MR				
> Access to tank	Required	Provided	MR				
Overhead Tank capacity	NA	NA	NA				
xit Sign age.	Required	Provided	MR				
Provision of Lifts.							
Pressurization of Lift Shaft	NA	NA	NA				
Pressurization of Lift lobby	NA	NA	NA				
Communication In lift Car	Required	Provided	MR				
• Fireman's Grounding Switch	Required	Provided	MR				
• Lift Signage	Required	Provided	MR				
Standby power supply	Required	Provided	MR				
Refuge Area.							
➤ Total Area	NA	NA	NA				
> Location	NA	NA	NA				
Fire Control Room							
Detector System Panel	Required	Provided	MR				
Flow Switch Panel	NA	NA	NA				
PA System Panel	Required	Provided	MR				
Battery backup	`						
Building Floor Plans		Provided	MR				
	NA	NA	NA				
Special Fire Protection Systems for	Required	Provided	MR				
S R	> Head of the pump > Power Supply > Auto Starting of pump Draw-off connection > Fire service inlet > Access to tank Overhead Tank capacity Communication of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage tandby power supply Refuge Area. > Total Area > Location Total Area > Location Detector System Panel PA System Panel PA System Panel Battery backup Building Floor Plans	➤ Head of the pump NA ➤ Power Supply NA ➤ Auto Starting of pump NA • Underground tank capacity 50,000ltrs • Underground tank capacity 50,000ltrs ➤ Preservice inlet Required ➤ Access to tank Required • Overhead Tank capacity NA • Pressurization of Lift Shaft NA • Pressurization of Lift lobby NA • Communication In lift Car Required • Fireman's Grounding Switch Required • Lift Signage Required • tandby power supply Required Refuge Area. NA ➤ Total Area NA ➤ Location NA NA NA PA System Panel Required • Flow Switch Panel NA • Battery backup Required • Building Floor Plans NA	➤ Head of the pump NA NA ➤ Power Supply NA NA ➤ Auto Starting of pump NA NA Power Supply NA NA ➤ Auto Starting of pump NA NA • Underground tank capacity 50,000ltrs 50,000ltrs ➤ Draw-off connection Required Provided ➤ Fire service inlet Required Provided ➤ Access to tank Required Provided • Overhead Tank capacity NA NA • NA NA NA • Pressurization of Lift Shaft NA NA • Pressurization of Lift lobby NA NA • Communication In lift Car Required Provided • Fireman's Grounding Switch Required Provided • Lift Signage Required Provided • Landby power supply Required Provided • Interpretation Required Provided • Interpretation NA NA • Detector System Panel Required Provided • Flow Switch Panel NA NA				

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/2010/1244 dated 29.04.2010, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)