GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2021/549

Dated: 39./. 18./2021

FIRE SAFETY CERTIFICATE

Certified that the Swiss Palace Guest House located at 7923/4, Arakashan Road. Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (01 guest room + Reception), 1st floor to 4th floor (02 guest rooms at each floor), total 09 guest rooms owned/occupied by Swiss Palace Guest House was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2018/1964 dated 27/08/18. Now, The premise was re-inspected by the officer concerned of this department on 23/12/21 in the presence of manager and found that the said guest house building comprises of ground and six upper floor and having given affidavit dated 11.12.2019 regarding not to use any floor above third floor, has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (01 guest room + Reception), 1st floor to 3rd floor (02 guest rooms at each period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

(Dr. S.K. Tomar) Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Commissioner, North MCD, New Delhi: to ensure the occupancy in the building as detailed above.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. Online id No. 2021062614269 dated 06.07.21 & mail id anildehal@gmail.com dated 09.12.2021.
- 3. The Manager,

Swiss Palace Guest House 7923/4, Arakashan Road, Pahar Ganj, New Delhi. Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
 - 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the The trained fire fighting staff should be available round the clock. 3.

 - 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if
 - The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi 6. Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
 - 7.
 - The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

No.		IN	SPECTION DE	DODT	-39				
	1	. Name & address of the build	SPECTION RE						
2. Type of occupancy:- Residential Sub Division A 1									
	Gr. + 06 Upper floors (total 07 Guest rooms) Ground floor (01 guest room + Reception), 1 st fl 3rd floor (02 guest rooms at each floor) and up								
			n use as per affidavit d	ated 11.12.2019 &					
	3	. Type of case:-	e-mail date Renewal	d 09.09.21	and the second sec				
	4.								
	10/21 0/21 0/11/10/2/2010/196								
5 Fire sector 11 11 12 27/08/18.									
	6. Date of inspection:- N/A 23/12/21								
	7.	Name of the inspecting office		der Church (ADO/GO	X.				
	8.	 Name of the inspecting officer:- Sh. Ravinder Singh (ADO/CC) Name & designation of officer 							
	From the heild's it								
	9. Year of construction:- 1991								
		Applicant's letter No:-		0 2021062614260 day	ad 0 (07 01 0				
	10. Applicant's letter No:-Online id No. 2021062614269 dated 06.07.21 & mail id anildehal@gmail.com dated 09.12.2021								
	~ ~ ~ ~				Old Case				
	S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks				
		Prevention and fire safety U/R 33	Existing fire safe arrangements	ty	MR/NMR				
	1.	Access to Building	arrangements						
		1) Road width	N/A	2.10 mtr.	N/A				
		2) Gate width	N/A	N/A	N/A				
		3)Width of internal road	N/A	N/A	N/A				
	2.	Number, Width Type & Ar							
		A. Number of staircases							
		1. Upper floors	01 Nos.	01 Nos.	MR				
		2. Basements	N/A	N/A	N/A				
		B. Width of staircase							
		1. Upper floors	0.80 mtr.	1.08 mtr.	MR				
		2. Basements	N/A	N/A	N/A				
		C. Protection of exits							
		1. Fire check door	N/A	N/A	N/A				
		2. Pressurization	N/A	N/A	N/A .				
		D. No: of continuous staircase to terrace	N/A	N/A	N/A				
		E. Width of corridor	N/A	N/A	N/A				
		F. Door size	01 mtr.	01 mtr.	MR				
	3.	Compartmentation			IVIIC				
F		1) Fire check door	N/A	N/A	N/A				
		2) Sealing of electrical shafts	N/A	N/A	N/A				
+		3) Fire rating of shaft door	N/A	N/A	N/A				
	ł	4) Water curtain	N/A	N/A N/A	N/A				
	ŀ	5) Fire Dampers	N/A	N/A N/A	N/A N/A				
F	1.	11//1							
F		Smoke Management System 1) Basements N/A		N/A	N/A				
	ŀ	2) Upper floors	12 ACPH	Exhaust fan	MR				
4	5.	Fire Extinguishers	12 10111						
-		THE EXHIguishers							
		1) 00 - 1							
	-	1) Total numbers	08 Nos.	08 Nos.	MR				
		2) Types	ABC & CO2	ABC & CO2	MR				
	1	3) ISI marking	Required	Provided	MR				

			1			
	01	01	MR			
2) Length of hose reel hose	30 mtr.	30 mtr.	MR			
3) Nozzle diameter	05 mm	05 mm	MR			
Automatic Fire Detection & Alarming System						
1) Type of detectors CO	Required	Provided	MR			
Туре	_					
2) Location of main panel	Gr.	Provided	MR			
	N/A	N/A	N/A			
	Required	Provided	MR			
	Gr.	Provided	MR			
	Required	Provided	MR			
			MR			
	Required					
	N/A	N/A	N/A			
			N/A			
· · · ·			N/A			
	1 1/ 2 K					
	N/A	N/A	N/A			
	N/A		N/A			
floor						
3) Hose box	N/A	N/A	N/A			
Yard Hydrants						
1) Total number of hydrants	N/A	N/A	N/A			
2) Hose box	N/A	N/A	N/A			
Pumping Arrangement						
1) Ground level	N/A	N/A	N/A			
a) Discharge of main	N/A	N/A	N/A			
pump			,			
b) Head of main pump	N/A	N/A	N/A			
c) Number of main pump	N/A	N/A	N/A			
		N/A	N/A			
		N/A	N/A			
		N/A	N/A			
		N/A	N/A			
	N/A	N/A	N/A			
		225 LPM	MR			
		30 mtr.	MR			
		Provided	MR			
d) Auto starting of pump		Provided	MR			
Captive Water Storage for Fire	Fighting					
1) Under ground tank	NI/A	NI/A				
-) Shadi Bibullu talik	11/11	I IN/A	N/A			
	Automatic Fire Detection &1) Type of detectors COType2) Location of main panel3) Location of repeater panel4) Alternate source of power5) Hooter's LocationMOEFAPublic Address SystemAutomatic Sprinkler System1) Basement2) Upper floors3) Sprinkler above falseceilingInternal Hydrants1) Size of riser/down-comer2) Number of hydrants per floor3) Hose boxYard Hydrants1) Total number of hydrants2) Hose boxPublic Addrese of main pumpb) Head of main pumpc) Number of main pumpd) Jockey pump out pute) Jockey pump outputg) Stand by pump outputg) Stand by pump headh) Auto starting/Manual stopping2) Terrace levela) Discharge of pumpb) Head of pumpc) Power supplyd) Auto starting of pump	1) Total number of eachfloor012) Length of hose reel hose30 mtr.3) Nozzle diameter05 mmAutomatic Fire Detection & Alarming Sy1) Type of detectors CORequiredType2) Location of main panelGr.3) Location of repeater panelN/A4) Alternate source of powerRequired5) Hooter's LocationGr.MOEFARequiredPublic Address SystemRequired1) BasementN/A2) Upper floorsN/A3) Sprinkler above falseN/AceilingInternal Hydrants1) Size of riser/down-comerN/A2) Number of hydrants per floorN/A3) Hose boxN/A2) Hose boxN/A1) Total number of hydrantsN/A2) Hose boxN/A1) Ground levelN/A1) Ground levelN/A1) Ground levelN/A2) Number of main pumpN/A4) Jockey pump outputN/A6) Head of main pumpN/A6) Jockey pump nutputN/A7) Stand by pump nutputN/A9) Stand by pump headN/A1) Auto starting/Manual stoppingN/A2) Terrace levela)Discharge of pump2) Terrace levela)Discharge of pump2) Terrace levela)Discharge of pump3) Head of pump30 mtr.c) Power supplyRequiredAuto starting of pumpRequiredAuto starting of pumpRequired <td>1) Total number of eachfloor 01 01 2) Length of hose reel hose 30 mtr. 30 mtr. 3) Nozzle diameter 05 mm 05 mm Automatic Fire Detection & Alarming System 1) Type of detectors CO Required Provided 2) Location of main panel Gr. Provided 3) Location of repeater panel N/A N/A 4) Alternate source of power Required Provided 5) Hooter's Location Gr. Provided MOEFA Required Provided Public Address System Required Provided Automatic Sprinkler System 1) Basement N/A 1) Basement N/A N/A N/A 2) Upper floors N/A N/A N/A 3) Sprinkler above false N/A N/A N/A 1) Size of riser/down-comer N/A N/A N/A 2) Number of hydrants per floors N/A N/A N/A 1) Size of riser/down-comer N/A N/A N/A 2) Number of hydrants per floor N/A N/A N/A 1) G</td>	1) Total number of eachfloor 01 01 2) Length of hose reel hose 30 mtr. 30 mtr. 3) Nozzle diameter 05 mm 05 mm Automatic Fire Detection & Alarming System 1) Type of detectors CO Required Provided 2) Location of main panel Gr. Provided 3) Location of repeater panel N/A N/A 4) Alternate source of power Required Provided 5) Hooter's Location Gr. Provided MOEFA Required Provided Public Address System Required Provided Automatic Sprinkler System 1) Basement N/A 1) Basement N/A N/A N/A 2) Upper floors N/A N/A N/A 3) Sprinkler above false N/A N/A N/A 1) Size of riser/down-comer N/A N/A N/A 2) Number of hydrants per floors N/A N/A N/A 1) Size of riser/down-comer N/A N/A N/A 2) Number of hydrants per floor N/A N/A N/A 1) G			

-

N-40



	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	 d) Over head tank capacity 	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A .	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System any:	N/A		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. safety F6/DFS/MS/GH/NDZ/2018/1964 dated 27/08/18, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval up to third floor only.

Signature of the Inspecting Officer Name: - Ravinder Singh Designation ADO (CC)

el co

28/12/21

(fo(m52)

tr.

η

ed

d

MR MR

MR

MR

MF N/ M \overline{M} M \mathcal{N}

N

(Ar croporus Fri putup for Kenspensent ADD(cc)

29/12/21