GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELIII FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI - 110001

No. 16 DFS/MS/WZ/2022 23

Dated: /8 / 0 / /2022

FIRE SAFETY CERTIFICATE

Certified that the Aggarwal Millennium Tower-II, Located at, E-4, Netaji Subhash Place, Pitampura, Delhi – 110034 comprised of Basement +Ground + 13 Upper Floors was issued Fire Safety Certificate vide Letter No. F6/DFS/MS/WZ/2019/178 dated 24-01-2019. The said premises was re-inspected by the officer concerned of this department on 14.01.2022 in the presence of Sh. Ajay Chauhan (G.M) & Sh. Sanjay Kumar (Fire Officer) and found that the building/premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010, and that the premises/building is fit for occupancy class "Mercantile & Business Building" Group F & Group E with effect from 18/01/2022 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

(Atul Garg)

Director

Copy to:-

- 1. Sh. Sunil K Jain (Vice President), G-3, Aggarwal Corporate Tower, Plot No. 23, Rajendra Place, New Delhi-110008.
- 2. The Vice Chairman, DDA, INA, Vikas Sadan, New Delhi-110023.

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time. It should not bolt /locked.
- 2. 6 Mtrs. road for movement of fire tenders all around building shall be kept free from any hindrance.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any loss of life any property due to the non-functional of any fire safety measures, management shall be held responsible.
- 5. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 6. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 7. All comments / directions of building Department shall always be permitted and followed.
- 8. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 9. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.
- 10. The basement shall be used as per BBL.

INSPECTION REPORT

- 1. Name & address of the building: Aggarwal Millennium Tower-II, Located at, $\rm E=4$, Netaji Subhash Place, Pitampura, Delhi $\rm =110034$.
- 2. Type of Occupancy: Mercantile + Business (Mixed), (Basement+Ground + 13 Upper Floors)

3. Type of Case

4. Details of previous NOC: F6/DFS/MS/WZ/2019/178 dated 24-01-2019

: Renewal

5. Fire Safety directives Letter No. :F6/DFS/MS/BP/2005/1036 dated 18-05-05

6. Date of inspection : 14.01.2022

7. Name of the Inspecting Officer: S.P. Bhardwaj, DO

8. Name and designation of Officer

from the building side :Sh. Ajay Chauhan (G.M)

Sh. Sanjay Kumar (Fire Officer)

9. Year of Construction : 2007

10. Applicant's letter No. : email dated 27.12.2021

	10. Applicant's letter No.						
S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements/lett dated 24.01.2019	ter	Provided a site	at	Rema MR/N	
1.	Access of building • Road width	9 m		22.4m			IR
	Gate width	6 m	C	n open Ro	ad		IR
	 Gate width Width of internal road 	6 m As per	DD.	A approved	d drav	wing	MR
2	Number, width, Type & Arrangemen						
2.							
		2		Provided			1R
		2		Provided		M	IR
	AND C.						~ \
	b. Width of starreasesUpper floors	1.5m & 1.25m		0cm & 20cm	MI	R(Old (Case)
	• Basements	1.5m & 1.25m	11	8cm & 131cm	Ml	R(Old (Case)
	c. Protection of exits	Required		Provided	1	N	ЛR
	 Fire check door 	Required		Provided			ЛR
	Pressurizationd. No of continuous staircase	Required		Provided			ИR
	to terrace	1.7	+-	170cm		N	МR
	e. Width Of Corridor	1.5m	+	Provide			MR
	f. Door Size	1 m		Flovido		1	
3.	Compartmentation	Required		Provide	d d	l	MR
	Fire check door	Required		Provide		1	MR
	 Sealing of electrical shafts 	Required	+	Provide			MR
	 Fire Rating of shaft door 	NR	+	NR			NR
	 Water Curtain 	NR	-	NR			NR
	 Fire Dampers 	INIX	+				
4.	Smoke managements System	20 -/a non hou	-	Provide	ed		MR
	Basements	30 a/c per hou	r.	Provide			MR
	Upper floors	12 a/c per hou	11	110 110	-		
5.	Fire Extinguishers	27	-	Provid	ed		MR
	Total numbers	37 nos.	-	Provid	ed		MR
	• Types	CO ₂ &ABC	-	Provid	ed ed		MR
	IS marking	ISI marked		TTOVIG			2
,						S	1
-						/	•

(5. First – Aid Hose Reels) (P)		
	 Total numbers on each floor 	1	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	 Nozzle diameter 	5 mm	Provided	MR		
_7	- detection and that	ming system		•		
	• Type of detectors	Smoke & Heat	Provided	MR		
	 Location of Main Panel 	Required	Provided	MR		
	 Location of Repeater Panel 	Required	Provided	MR		
	 Alternate source of power 	. Required	Provided	MR		
	 Hooters' Location 	Required	Provided	MR		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
10	Springer Dystelli		11011404	TVIIC		
	 Basements 	Required	Provided	MR		
	Upper Floor	Required	Provided	MR		
	 Sprinkler above false 	Required	Provided	MR		
	ceiling		10.1304	1711		
11	- Tribin 11) di di di lo	-1				
	 Size of riser/down- comer 	150 mm	Provided	MR		
	 Number of hydrants per 	1	Provided	MR		
i	floor		15	1411		
	 Hose Box 	Required.	Provided	MR		
12.	Yard Hydrants	•				
	 Total number of hydrants 	Required	Provided	MR		
	 Hose Box 	Required	Provided	MR		
13.	Pumping Arrangements: All the fire pumps are connected with DG set					
	 Ground Level 					
	 Discharge of main pump 	2850 lpm	Provided	MR		
	> Head of main pump	100 m	Provided	MR		
	Number of main pumps	2	Provided	MR		
	Jockey pump out put	180 lpm	Provided	MR		
	Jockey pump head	100 m	Provided	MR		
	Standby Pump out put	2850 lpm	Provided	MR		
	Standby Pump Head	100 m	Provided	MR		
	Auto Staring/Manual	Required	Provided	MR		
	stopping					
	Pump House Access	Required	Provided	MR		
	• Terrace level					
	Discharge of pump	450 lpm	Provided	MR		
	Head of the pump	40 m	Provided	MR		
	Power supply	Required	Provided	MR		
	Auto starting of pump	Required	Provided	MR		
14.	Captive water Storage for fire fight					
	 Under ground tank 	1,00,000	Provided	MR		
	capacity	litres				
	Draw of connection	Required	Provided	MR		
	Fire service inlet	Required	Provided	MR		
	Access to tank	Required	Provided	MR		
	 Overhead Tank capacity 	50, 000 litres	Provided	MR		
15	Exit Signage	Required	Provided	MR		
16.	Provision of Lifts					
	 Pressurization of Lift Shaft 	Required	Provided	MR		
	Pressurization of lift lobby	Required	Provided	MR		
	Communication in lift Car	Required	Provided	MR		
i	Fireman's Grounding	Required	Provided	MR		
	Switch	Required	Provided	MIN		
ĺ	Lift Signage	Required	Provided	MR /		
	/ Lift Signage	Required	Trovided	IVIIC		

17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area					
	► Lotal area	Required	Provided	MR		
	Location	5^{th} , 6^{th} , 8^{th} and	Provided,	MR		
		12 th Floor	5,7,10,11,&12th			
19.	Fire control room					
	 Detector system panel 	Required	Provided	MR		
	➤ Flow Switch Panel	Required	Provided	MR		
	➢ PA System Panel	Required	Provided	MR		
	 Battery backup 	Required	Provided	MR		
	➢ Building Floor Plans	Required	Provided	MR		
20.	Special Fire Protection Systems for	CO ₂ Flooding	Provided	MR		
	Protection of special Risks, if any:	for DG, HT &				
		LT Panel				

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety requirements under the rules, renewal of FSC issued vide letter no. F6/DFS MS/WZ/2019/178 dated 24-01-2019 is recommended under rule 37 of the Delhi Fire Service Rules 2010.

181/27

D