C51

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No.F.6/DFS/MS/School/WZ/2021 53

Dated: |8/0|/2021

FIRE SAFETY CERTIFICATE

(Sunil Choudhary) **Dy.Chief Fire Officer**

Copy to:-

ole

- 1. The Director, Education, Government of N.C.T of Delhi. Old Sectt. Delhi 110054.
- 2. The Principal, Mother Divine Public School, B-Block, Sec-03, Rohini, Delhi-110085.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.Delhigovt.nic.in

INSPECTION REPORT

: Mother Divine Public School, B-Block, Sec-03, Rohini, 1. Name & address of the building

Delhi-110085.

2. Type of Occupancy

: Educational

3. Type of Case

: Renewal (Ground plus 02 upper floors)

4. Details of previous NOC

: F-6/DFS/MS/2018/WZ/2735 dated 19.12.2018.

5. Fire Safety directives letter No

: NBC Part-IV

6. Date of inspection

: 27.12.2021

7. Name of the Inspecting Officers

: A.K.Sharma ADO (Rohini)

8. Name and designation of officers

from the building side

: Mr. K. K Sharma (President)

9. Year of Construction

: 2005

10. App		licant's letter No. : OD No.4824 dated 30.11.2021 Remarks Remarks					
		Minimum Standards on fire evention and fire safety U/R 33	NBC Requirement	Provided at site	MR/NMR		
	Acce	ss to building	J		MD		
	•	Road width	Accessible	Accessible	MR MR(old case)		
		Gate width	4.5m	3.5m	NA NA		
	•	Width of internal road	NA	NA	INA		
	Number, Width, Type & Arrangement of Exits						
	a. Nu	mber of staircases		00	MR		
	•	Upper Floors	02	02			
	•	Basements	NA	NA	NA		
	b. Wi	dth of staircases					
	•	Upper Floors	1.50m	1.35m & 1.06m	MR(old case		
	•	Basements	NA	NA	NA		
	c. Pro	tection of exits					
	•	Fire check door	NA	NA	NA		
		Pressurization	NA	NA	NA		
	d No	of continuous staircases to terrace	NA	NA	NA		
		th of Corridor	NA	NA	NA		
	f. Doo		1 m	1m including door fitting (less than 45 student in a class)	MR(old case		
	Comp	Compartmentation.					
	•	Fire check door	NA	NA	NA		
	•	Sealing of electrical shafts	NA	NA	NA		
	•	Fire Rating of shaft door	NA	NA	NA		
	•	Water Curtain	NA	NA	NA		
	•	Fire Dampers	NA	NA	NA		
	Smok	Management System.					
	•	Basements	30 a/c per hour	NA	NA		
	•	Upper floors	12 a/c per hour	Natural Ventilated	MR		
	Fir	e Extinguishers					
	•	Total numbers	06nos	06nos	MR		
	•	Types	ABC/Co2	ABC06	MR		
	•	ISI marking	ISI Marked	Yes	MR		
	First-Aid Hose Reels.						
	•	Total numbers on each floor	01	Provided	MR		
	•	Length of hose reel hose	30m	Provided	MR		
	•	Nozzle diameter	5mm	Provided			
		atic fire detection and alarming sy		TTOTIUCU	MR		

.	/ '	-/	
7		-	

			NA	NA
	Type of detectors	NA	NA	NA
	Location of Main Panel	NA	NΛ	NA
	Location of Repeater Panel	NA	NA	NA
	Alternate source of power	NA	NA	NA
	Hooters' Location	NA	NA	NA
3	MOEFA	NA	NA	NA
)	Public Address System.	NA	NA	1112
0	Automatic Sprinkler System.		NTA .	NA
	Basement	NA	NA	NA
	Upper Floor	NA	NA NA	NA
	 Sprinkler above false ceiling 	NA	NA	1 11 2
1	Internal Hydrants	100	100mm	MR
	Size of riser/down-comer	100mm	100mm 01	MR
	 Number of hydrants per floor 	01	01	MR
	Hose Box	01	UI	1144
2	Yard Hydrants.	N7.4	NA	NA
	 Total number of hydrants 	NA	NA NA	NA
	Hose Box	NA	INA	11.4
3	Pumping Arrangements.	T		
	Ground Level Discharge of main Pump	27/4	N/A	N/A
	Discharge of main PumpHead of Main pump	N/A	N/A	N/A
	> Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A NA	NA NA	NA
	Jockey pump head	NA NA	NA NA	NA
	Standby Pump out putStandby Pump Head	N/A	N/A	N/A
	Standby Pump HeadAuto Starting/ Manual	N/A N/A	N/A	N/A
	stopping stopping	N/A N/A	N/A	N/A
	> Pump House Access	IN/A	- 1/ - 2	
	Terrace level	450lpm	450lpm	MR
	Discharge of pump	430lpin 40m	40m	MR
	> Head of the pump	Required	Provided	MR
	Power SupplyAuto Starting of pump	Required	Provided	MR
1.4	Captive Water Storage for fire fighting			
14	Underground tank capacity	NA NA	NA	NA
	 Onderground tank capacity Draw-off connection 	NA	NA	NA
	> Fire service inlet	NA	NA	NA
	> Access to tank	NA	NA	NA
	Overhead Tank capacity	5,000ltrs	5,000ltrs	MR
15	Exit Signage	Required	Provided	MR
16	Provision of Lifts.			
10	Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
	Cintion In lift Car	N/A	N/A	N/A
		N/A	N/A	N/A
	Fireman's Grounding Switch Life Signage	N/A	N/A	N/A
	Lift Signage	N/A	N/A	N/A
	Standby power supply	14/13	14/17	11/21
	70.0		· · · · · · · · · · · · · · · · · · ·	
17 18	Refuge Area. > Total Area	N/A	N/A	N/A

19	Fire Control Room					
	Detector System Panel	N/A	N/A	N/A		
	Flow Switch Panel	N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Batter backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection Systems for	N/A	N/A	N/A		
	Protection of special Risks, if any:					

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F-6/DFS/MS/2018/WZ/2735 dated 19.12.2018 is recommended for renewal under rule 37 of the Delhi Fire Service rules 2010.

> Signature of the Inspecting Officer Ajay Kumar Sharma Name Designation ADO (Rohini)

FT letter 6 port up for kind forward and signature please.

DCFO (wy/