GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / 2022 /School/WZ/ 13

Dated 03 02 2022

FIRE SAFETY CERTIFICATE

Certified that the Sarvodaya Kanya Vidyalaya (New Building) located at Khera Khurd, Delhi-110082 comprised of Ground+Three upper floors owned/ occupied by Sarvodaya Kanya Vidyalaya have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and verified by the officer concerned of Fire Service on 17.01.2022 in the presence of Sh. Sanjay Chauhan and found that the building is fit for occupancy class Group B Educational with effect from $03 02 202^{2}$ for a period of <u>03 (Three) years</u> in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .03 02 2022 at New Delhi by

-40

Director Delhi Fire Service

OCL

Copy to:-

0

- 1. The Director, Education, Government of NCT of Delhi. Old Sect. Delhi-110054
- 2. Principal, Sarvodaya Kanya Vidyalaya, Khera Khurd, Delhi-110082.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

		~13			1.			
6								
3. 4. 5. 6. 7. 8. 9.	Name & address of the buildin Type of Occupancy Building Comprised Type of Case Details of Previous NOC Fire Safety directives letter No Date of inspection Name of Inspecting Officer Name and designation of office From the building side Year of Construction Applicant's letter No.	g : Sarvodaya Kar Delhi-110082 : Educational : Ground + Thre : New Case : Nil : NBC Part-IV : 17/01/2022 : ADO, R.K.Sin rs	Delhi-110082 : Educational : Ground + Three Upper Floors (05 Blocks interconnected) : New Case : Nil : NBC Part-IV : 17/01/2022 : ADO, R.K.Sinha : : Sh. Sanjay Chauhan					
8. No.	Minimum Standards on fire fire safety U/R 33	prevention and	NBC Requirement	Provided at site	Remarks MR/NMR			
•	Access to building							
	 Road width Gate width 		6.0 m	6.0 m	MR			
	Gate widthWidth of internal road		4.5 m	4.5 m	MR			
	Number Wildle The State		NΛ	NA	NA			

	Gate width							
	Width of internal road	4.5 m	4.5 m	MR				
2.		NΛ	NA	NA				
	Number, Width, Type & Arrangement of Exits a. Number of staircases							
	Upper Floors							
	Basements	03	03	MR				
	b. Width of staircases	NA	NA	NA				
	Upper Floor	1.50 m each	1.70 m each	MR				
		NA	NA	. NA				
	Basements	NA	NA	NA				
	c. Protection of exits	NA	NA	NA				
	 Fire check door Pressurization 	NA	NA	NA				
		NA	NA	NA				
	d. No. of continuous staircases to	NA	NA	NA				
	terrace	02	03	MR				
	e. Width of Corridor	1.50 m	1.70 m	MR				
	f. Door Size	1.20 m	1.20 m (Double Door)	MR				
	Compartmentation							
	Fire check door	NA	NA	NA				
	Sealing of electrical shafts	NA	NA	NA				
	 Fire Rating of shaft door Water Curtain 	NA	NA	NA				
		NA	NA	NA				
	Fire Dampers	NA	NA	NA				
	Smoke Management System							
	• Basements	30 a/c per hour	NA	NA				

	• Upper floors	12 a/c per hour	Natural Ventilated	MR				
	Fire Extinguishers							
	Total numbers	30	48	MR				
	• Types	ABC/CO2	ABC/Co2	- MR				
	IS marking	Yes	Yes	MR				
5.	First-Aid Hose Reels							
	Total numbers on each floor	04 Nos.	04 Nos.	MR				
	Length of hose reel hose	30 m	Provided	MR				
	Nozzle diameter	5 mm	Provided	MR				
7.	Automatic fire detection and alarming system							
•	Type of detectors	NΛ	ΝΑ	NΛ				
	 Location of Main Panel 	NΛ	ΝΛ	NA				
	Location of Repeater Panel		ΝΑ	ΝΛ				
	Alternate source of power		ΝΛ	ΝΛ				
			ΝΛ	ΝΛ				
	Hooters' Location	NΛ						
3.).	MOEFA Public Address System	ΝΛ	NΛ	NA				
0.	Public Address System Automatic Sprinkler System	NΛ	ΝΛ	NA				
	Basement	NΛ	NΛ	NΛ				
	Ground Floor	NΛ	NΛ	NΛ				
	 Sprinkler above false ceiling 	NΛ	NΛ	NA				
1.	Internal Hydrants							
	• Size of riser/down-comer	NΛ	ΝΑ	NA				
	• Number of hydrants per floor	·NA	NΛ	NA				
	Hose Box	NΛ	ΝΛ	NΛ				
2.	Yard Hydrants							
	• Total number of hydrants	ΝΛ	ΝΛ	NA				
	 Hose Box 	ΝΛ	ΝΛ	NA				
3.	Pumping Arrangements							
	Ground Level	·····	[· · · ·]					
	\sim Discharge of main Pump	NΛ	NΛ	NA				
	 Head of Main pump 	ΝΛ						
	Number of main pumps		NA	ΝΛ				
	Jockey Pump out put	NA	NΛ	NΛ				
	Jockey pump head	NΛ	ΝΛ	NA				
	Standby Pump out putStandby Pump Head	NΛ	ΝΛ	NΛ				
	> Standby Fump Field	NΛ	ΝΛ	NΛ				
	Auto Starting/Manual Stopping	NΛ	NΛ	NΛ				
		NΛ	ΝΛ	NΛ				

NIS Pump House Access NΛ NΛ NA Terrace level . 450 lpm 450 lpm×2 Discharge of pump MR 40 m Head of the pump 40 m MR Power Supply Required Provided MR , **-**Auto Starting of pump Required Provided MR Captive Water Storage for fire fighting 14. Underground tank capacity NΛ NA NA Draw-off connection NΛ NA NA Fire service inlet NA Access to tank NA NA NA NA NA Overhead Tank capacity 10,000 ltrs 10,000 ltrs MR Required Provided MR 15. Exit Signage. 16. Provision of Lifts. Pressurization of Lift Shaft • NA NA NA Pressurization of Lift lobby • NA NA NA Communication In lift Car NA NA NA Fireman's Grounding Switch NΛ NA NA Lift Signage NA NA NA NΛ NA NA 17. Standby power supply 18. Refuge Area. Total Area 7 NA NA NΛ Location NΛ NA NA 19. **Fire Control Room** Detector System Panel NA • NΛ NA Flow Switch Panel . NΛ NA NΛ PA System Panel • NΛ NA NA NA Battery backup NΛ NA . **Building Floor Plans** • NA NΛ NΛ 20. Special Fire Protection System for Protection of NA NA NΛ special Risks, if any:

Q.

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the above compliance of the minimum standards of fire prevention and fire safety measures required under rule 35 of the Delhi Fire Service Rules 2010 it is recommended to grant Fire Safety Certificate.

Docarwi in orbett Dycets (wz)

Signature of Inspecting Officer

Name : Rajeev Kumar Sinha Designation : ADO/B.W.

No of starian Not the houisenest therefore W F. T letter i puter fisquipleop

be checked as there can Are blocker.

1902

Director COA

Number of statements may