DFA.

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/School/WZ/2022/ 139

Dated: 10/2/2022

FIRE SAFETY CERTIFICATE

Certified that the New Block, Govt. Girls Sr. Sec. School (ID-1411046), Located at Kohat Enclave, Anandvas, Pitampura, Delhi-110034 comprised of Ground + 03 Upper Floors & MP Hall owned/ occupied by Govt. Girls Sr. Sec. School (ID-1411046) have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officers concerned of Fire Service on 04.02.2022 in the presence of Ms. Nisha Tyagi (Vice-Principal) & Sh. Deepak Tyagi Site Engineer (SPG Infra Pvt. Ltd.) and that the building/premises is fit for occupancy class "Educational Building" Group B with effect from for a period of three years, in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on . l.o. l. at New Delhi by.

Copy to:-

- 1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi 110054
- 2. The Assistant Engineer (E), PWD Sub Division 2, Edu. Elect. Edn. 1 Div (N), Sector 16, Rohini, Delhi-110089.
- 3. The Principal, New, Govt. Girls Sr. Sec. School, Kohat Enclave, Anandvas, Pitampura (ID-1411046), Delhi-110034.

Following fire safety directives must be adhered to:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

 Name & address of the building: Govt. Girls Sr. Sec. School (ID-1411046) Located at Kohat Enclave, Anandvas, Pitampura, Delhi-110034

: Nil

2. Type of Occupancy

: Educational,

3. Type of Case: New Block=G+03 Upper Floor & M.P. Hall

4. Details of previous NOC

5. Fire Safety directives Letter No. : as per UBBL/NBC Part-IV

6. Date of inspection

: 04.02.2022

7. Name of the Inspecting Officer : S.P. Bhardwaj, Divisional Officer

8. Name and designation of Officer

from the building side

: Ms. Nisha Tyagi (H.O.S)

Sh. Deepak Tyagi, Site engineer (SPG infra pvt. Ltd.)

9. Year of Construction

: 2021-22

10. Applicant's letter No.

: email dated 01.02.2022

S	Minimum standards on fire	UBBL/NBC	Provided at site	Remarks		
No	prevention and fire safety U/R 33	Requirement		MR/NMR		
1.	Access of building					
	 Road width 	06 mtrs.	Provided	MR		
	 Gate width 	4.5 mtrs.	Provided	MR		
	 Width of internal road 	NA	NA	NA		
2.	Number, width, Type & Arrangements of exits					
	 a. Number of staircases 					
	 Upper floors 	04	04 & 01	MR		
	 Basements 		ramp			
	 b. Width of staircases 	NA	NA	NA		
	 Upper floors 					
	 Basements 	1.5 mtrs.	Provided	MR		
	c. Protection of exits	NA	NA	NA		
	 Fire check door)))))))))))))))))))	37.4		
	 Pressurization 	NA	NA	NA		
	d. No of continuous staircase	NA	NA NA	NA		
	to terrace	04	Provided	MR		
	e. Width Of Corridor	1.5 mtrs.	Provided	MR		
	f. Door Size	1.2 mtrs.	Provided	MR		
3.	Compartmentation					
5.	Fire check door	NA	NA	NA		
	 Sealing of electrical shafts 	NA	NA	NA		
	 Fire Rating of shaft door 	NA	NA	NA		
	Water Curtain	NA	NA	NA		
	Fire Dampers	NA	NA	NA		
1	Smoke managements System					
4.	Basements	NA	NA	NA		
	0	NA	NA	NA		
E	Upper floors Fire Extinguishers					
5.		38 nos.	Provided	MR		
		ABC & CO ₂	Provided	MR		
	• Types	ISI marked	Provided	MR		
	IS marking First – Aid Hose Reels					
6.	- 1 1	04	Provided	MR		
	Total numbers on each floor					
	 Length of hose reel hose 	30m	Provided	MR		
	Nozzle diameter	5mm	Provided	MR		
	• INOZZIE GIAITICICI			(/		

0.	Special Fire Protection Systems for Protection of special Risks, if any	r Required	CO ₂ type fire ext.	MR
		NA	NA	NA
	Building Floor Plans	NIA	NA	` NA
	Battery backup	NA NA	NA NA	NA
	PA System Panel	NA NA	NA	NA
	Flow Switch Panel	NA NA	NA NA	NA
	Detector system panel	NA	NT A	
).	Fire control room	NA	NA	NA
	> Location	NA NA	NA	NA
	> Total area	NT A		
3.	Refuge Area	NA	NA	NA
7.	Standby power supply	NA		NA
	Lift Signage	NA	NA NA	
	Fireman's Grounding Swi	ch NA	NA	NA NA
	Communication in lift Car	NΙΔ	NA	NA NA
	Pressurization of lift lobby	NΑ	NA	NA NA
	Pressurization of Lift Shat	t NA	NA	NA
١.	Provision of Lifts			.,,,,
) ó.	Exit Signage	Required		MR
5	Overhead Tank capacity Evit Signage	10,000Ltrs	s. 20,000 Ltrs.	MR
	1 100000 to tails	NA	NA	NA
	Fire service inlet Access to tank	NA	NA	NA
	Draw off connection	NA	NA	NA
	• Under ground tank capaci		NA	NA
۲.	Captive water Storage for fire fig	nting:		
4.	_	Required	Provided	MR
	Auto starting of pump	Required		MR
	Power supply	40Mtr	Provided	MR
	Head of the pump	450 lpm	Provided (2 nos.)	MR
	Discharge of pump			
	• Terrace level	NA	NA	NA
	Pump House Access	1171	NA	NA
	Auto Staring/Manual stop	NA NA	NA	NA
	Standby Pump Head	NA	NA	NA
	Standby Pump out put	NA	NA	NA
	Jockey pump head	NA	NA	NA
	Jockey pump out put	NA	NA	NA
	Number of main pump	NA	NA	NA
	Discharge of main pumpHead of main pump	NA	NA NA	NA
٥.	Ground Level			
3.		NA NA	NA	NA
	Hose Box	NA NA	NA	NA
	Total number of hydrants	NT A	774	
2.		IVA	NA	NA
	Hose Box	NA NA	NA NA	NA
	 Number of hydrants per f 		NA	NA
١.	Size of riser/down- come:			
1.	 Sprinkler above false ceil Internal Hydrants: 	ing NA	NA	NA
	• Upper Floor	NA	NA	NA
		NA NA	NA	NA
U,	Basements			
10.	Public Address System Automatic Sprinkler System	NA	NA	NA
3 9.		NA	NA	NA
8.	MOEFA Location	NA	NA	NA
	Alternate source of poweHooters' Location		NA	NA
			NA	NA
	 Location of Walli Panel Location of Repeater Panel 		NA	NA
	 Type of detectors Location of Main Panel	NA NA	NA NA	NA
			INA	NA

M.3

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Note: - Management has constructed a separate M. P. Hall having seating capacity of 300 persons (18x30 m) & have provided 04 nos. exit doors (03 Nos. 1.5m wide & 01 No. 2 m wide) & protected with hose reels & hydrant.

Keeping in view substantial compliance of the minimum standards on fire prevention and fire safety requirements under the rules, grant of Fire safety Certificate is recommended under rule 35 of the Delhi Fire service Rules 2010 under the DFS Act 2007.

S.P Bhardwaj Divisional Officer

port up for Signatu

Sefor MZ

ALL OTHER

Son Majorin

Wy yan

pm

Smi Hour