

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2022/ 9 2

Dated: - 9/02/22

FIRE SAFETY CERTIFICATE

Certified that the Star Palace Guest House located at 4590, Main Bazar, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (07 guest rooms + reception), 1st floor to 3rd floor (08 guest rooms at each floor), total 31 guest rooms owned/occupied by Star Palace Guest House was earlier granted FSC by this department vide letter No. F6/DFS/MS/GH/2019/NDZ/231 dated 29/01/19 & no. F6/ DFS/ MS/ GH/ 2019/ NDZ/2596 dated 03.05.19. Now, the premises was re-inspected by the officer concerned of this department on 04/02/22 in the presence of Sh. Pawan Mittal (Prop.) and found that the said guest house building comprises of ground and three upper floor & staff room & DG/storeroom at terrace and having given an affidavit dated 19.11.2019 regarding not to use any floor above third floor, has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A- Ground floor (07 guest rooms + reception), 1st floor to 3rd floor (08 guest rooms at each floor), up to 3rd floor only with effect from value of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued Osl-12-at New Delhi by.

(Dr. S.K.Tomar) Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Commissioner, North Delhi Municipal Corporation, Civic Centre, New Delhi: to ensure the occupancy as detailed above.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID no. 2022012981331 dated 27.01.22.
- 3. The Manager, Star Palace Guest House at 4590, Main Bazar, Pahar Ganj, New Delhi. Condition for the validity of Fire Safety Certificate
 - 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
 - 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
 - 3. The trained fire fighting staff should be available round the clock.
 - 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
 - 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
 - The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
 - The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
 - The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
 - 9. Use of any flammable material shall strictly be prohibited.

INSPECTION REPORT

1.30

1. Name & address of the building:- Star Palace Guest House at 4590, Main Bazar,

Pahar Ganj, New Delhi

2. Type of occupancy:- Residential, Sub Division-A-1

Gr. + 03 Upper floors (total 31 Guest rooms) Ground floor (07 guest rooms + reception), 1st floor to 3rd floor (08 guest rooms at each floor) & 01 staff room & DG/store rooms at terrace not in use as per

affidavit dated 19.11.2019

3. Type of case:- Renewal

4. Details of previous FSC:- No. F6/DFS/MS/GH/2019/NDZ/231 dated 29/01/19 & F6/ DFS/ MS/ GH/ 2019/ NDZ/

2596 dated 03.05.19

5. Fire safety directives No.-6. Date of inspection:-04/02/22

7. Name of the inspecting officer:- Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer

From the building side:- Sh. Pawan Mittal (Prop.)
9. Year of construction:- 2001

9. Year of construction:- 2001

10. Applicant's letter No:- ID no. 2022012981331 dated 27.01.22

C Na	Minimum Ct., 1, 1, C	ln ·	I	Old Case	
S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks	
	Prevention and fire safety	Existing fire safety		MR/NMR	
	U/R 33	arrangements			
1.	Access to Building	arrangements			
	1) Road width	N/A	6 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arr				
	A. Number of staircases				
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	0.80 mtr.	1.17 to 1.25 mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	N/A	N/A	N/A	
	staircase to terrace				
	E. Width of corridor	N/A	N/A	N/A	
•	F. Door size	1 mtr.	1 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 a/c per	Natural	MR	
			Ventilation/exhaust	1411	

1-31

5.	Fire Extinguishers					
O.	1) Total numbers	08 Nos.	08 Nos.	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
0.	1) Total number of eachfloor	01	01	MR		
	2) Length of hose reel hose	30 m	30 m	MR		
	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & Alarming System					
7.	1) Type of detectors CO type	Required	Provided	MR		
	2) Location of main panel	Gr. Floor	Provided	MR		
	3) Location of repeater panel	Required	Provided	MR		
	4) Alternate source of power	Required	Provided	MR		
	5) Hooter's Location	Gr. Floor	Provided	MR		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System	Required	Tiovided			
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling	11/71	11/71			
11.	Internal Hydrants					
11.	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor	14/11	14/12	1 11.		
		N/A	N/A	N/A		
12.	Yard Hydrants	A 11 / A	A 11 4 K	1 - 11 - 1		
		N/A	N/A	N/A		
		N/A	N/A	N/A		
13.	Pumping Arrangement	1				
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump		- "	1 1/1		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump		N/A	N/A		
	d) Jockey pump out put	N/A				
	-, paint out but	IN/A	l N/A	N/A		
	e) Jockey pump head	N/A	N/A N/A	N/A N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	e) Jockey pump head	N/A N/A	N/A N/A	N/A N/A		
	e) Jockey pump headf) Stand by pump outputg) Stand by pump head	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A		
	e) Jockey pump headf) Stand by pump output	N/A N/A	N/A N/A	N/A N/A		
	e) Jockey pump headf) Stand by pump outputg) Stand by pump headh) Auto starting/Manual	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A		
	e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A		
	e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump	N/A N/A N/A N/A 450 LPM	N/A N/A N/A N/A 450 LPM	N/A N/A N/A N/A		
	e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump	N/A N/A N/A N/A 450 LPM 30 mtr	N/A N/A N/A N/A 450 LPM 30 mtr	N/A N/A N/A N/A MR		
	e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	N/A N/A N/A N/A 450 LPM 30 mtr Required	N/A N/A N/A N/A A50 LPM 30 mtr Provided	N/A N/A N/A N/A MR MR MR		
	e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump	N/A N/A N/A N/A 450 LPM 30 mtr	N/A N/A N/A N/A 450 LPM 30 mtr	N/A N/A N/A N/A MR MR		
14.	e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	N/A N/A N/A N/A A50 LPM 30 mtr Required Required	N/A N/A N/A N/A A50 LPM 30 mtr Provided	N/A N/A N/A N/A MR MR MR		
14.	e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for F 1) Under ground tank	N/A N/A N/A N/A A50 LPM 30 mtr Required Required	N/A N/A N/A N/A A50 LPM 30 mtr Provided	N/A N/A N/A N/A MR MR MR		
14.	e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	N/A N/A N/A N/A 450 LPM 30 mtr Required Required	N/A N/A N/A N/A A50 LPM 30 mtr Provided Provided	N/A N/A N/A N/A MR MR MR MR MR		

	b) Fire service inlet	N/A	N/A	N/A
	e) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2019/NDZ/231 dated 29/01/19 & F6/ DFS/ MS/ GH/ 2019/ NDZ/2596 dated 03.05.19, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended up to third floor only.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

DO/CE

Asola) Arappoous, son putopforces forces of ad lip agtoni Alace 10 "

Whoudred MAH online Portul