## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

Fax No. 011-23412593, Ph. 011-23412225

No. F.6 DFS/MS/School/2019/SZ/ \ \\ \\ 3

Dated: [.8.1.].].5.

## FIRE SAFETY CERTIFICATE

Certified that the Govt. Boys. Sr, Sec. School No-4 located at Sarojini Nagar, New Delhi-110023, comprised of ground plus two upper floor was inspected by the officer concerned of this department on 08/01/2019 in presence of Mr. Hitender Yadav (Vice-Principal) of the school and found that said premises have complied with the fire prevention and fire safety requirements in accordance with Directorate of Education circular F.16//Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 issued by Director of Education, Govt. of NCT of Delhi and that the school building is fit for occupancy class "Educational Building" Group-B, as above with effect from the date of issue of this certificate for a period of Three years, in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on \_\_\_\_ at New Delhi by

(Vipin Kental) Chief Fire Officer

## Copy to: -

- 1. The Manager, Govt. Boys. Sr, Sec. School No-4, Sarojini Nagar, New Delhi-110023
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi.

## Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

		INSPECTI	ON REPORT				
1	Na	me & Address of the Building	Govt. Boys. Sr, Sec. School No-4, Sarojini Nagar.				
			New Delhi-110023				
2	Ty	be of Occupancy	Educational, Group	D-B (School)			
3	- 2	ilding Comprised of	G+2				
4	-	pe of Case	New				
5		tails of Previous NOC	Nil				
6	Fire	e Safety Directives Letter No	F.16//Estate/CC/Fire Safety/2011/3298 to 3398 dated				
			01.03.2011				
7		te of Inspection	08/01/2019				
8	Na	me of the Inspecting Officers	Mehmood, ADO (SJ)				
9		me & Designation of Officers	Mr. Hatinder Yada	v (Vice-Principal)			
	from the building side						
10		ar of construction		1962			
11		plicant letter No.	GBSSS/04/SN/2018/465 dated 29/11/2018				
S. No.		nimum standards on Fire Prevention	AS Per DOE	Provided at Site	Remarks		
		d Fire Safety U/R 33	Circular		MR/NMF		
1	Ac	cess to Building.	( - 1 -	7 mtr	MR		
		Road width	6 mtr		-NA-		
		Gate width	-NA-	-NA-			
_		Width of internal road	-NA-	-NA-	-NA-		
2	-	mber, width, type & arrangement of ex	cits.				
	a)	Number of Staircase		00.21.1	1.40		
		Upper floors.	1 No's	02 No's	MR		
		Basement floor.	-NA-	-NA-	-NA-		
	<b>b</b> )	Width of Staircase					
		Upper floors	1.50m/0.75m	1.60mtr each	MR		
		Basement floor	-NA-	-NA-	-NA-		
	c)	Protection of exits					
		> Fire check door	-NA-	-NA-	-NA-		
		Pressurization	-NA-	-NA-	-NA-		
	d)	No. of continuous staircase to terrace	01 No	Provided 02nos	MR		
	e)	Width of corridor	1.5m	Provided	MR		
	/	Door size	1 m	Provided	MR		
3		mpartmentation.		4 4 4 4			
		• Fire check door.	-NA-	-NA-	-NA-		
		<ul> <li>Sealing of electrical shafts.</li> </ul>	-NA-	-NA-	-NA-		
		<ul><li>Fire rating of shaft door.</li></ul>	-NA-	-NA-	-NA-		
		Water curtain	-NA-	-NA-	-NA-		
		• Fire dampers.	-NA-	-NA-	-NA-		
4.	Cm	ooke Management system.		PAC 50.00 PAC			
4.	SII	Basement	30 ACPH	-NA-	-NA-		
		<ul><li>Upper floors</li></ul>	12 ACPH	-NA-	-NA-		
5.	172	1.1	12/10111	1 1/2 K	. 12 1		
3.	I'I	re Extinguishers.  • Total numbers	20 Nos	22 Nos	MR		
	\(\mathbf{v}_1\)	And the state of t	ABC / CO2	ABC & Co2	MR		
		• Types	ISI marked	Provided	MR		
	-	ISI Marking	131 markeu	TTOVIGE	1711		
	Fi	rst Aid Hose Reels.	Two	Provided at each floor	MR		
6.		<ul> <li>Total numbers on each floor.</li> </ul>	Two				
6.			2000	Drowided	1/11/2		
6.		Length of hose-reel hose.	30m 5mm	Provided Provided	MR MR		

7 4	utomatic fire detection & alarming system.			
7. Au	Type of detectors	-NA-	-NA-	-NA-
	Location of Main Panel	-NA-	-NA-	-NA-
	Location of Repeater Panel	-NA-	-NA-	-NA-
	A La Construction	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
0 74		-NA-	-NA-	-NA-
	IOEFA	-NA-	-NA-	-NA-
	ublic Address System utomatic Sprinkler System			
10. A		-NA-	-NA-	-NA-
	Basement	-NA-	-NA-	-NA-
	Upper floors     Control of the	-NA-	-NA-	-NA-
	Sprinkler above false ceiling		P .	
11. In	nternal Hydrants.	-NA-	-NA-	-NA-
	Size of Riser/Down-comer	-NA-	-NA-	-NA-
	Number of Hydrant per floor		-NA-	-NA-
	Hose box.	-NA-	-11/7-	147.
12. Y	ard Hydrants.	NIA	-NA-	-NA-
-	<ul> <li>Total number of hydrants.</li> </ul>	-NA-	-NA-	-NA-
	Hose box.	-NA-	-IVA-	-14/7-
13. P	Pumping arrangements.			
	Ground Level		211	NIA
	Discharge of main pump.	-NA-	-NA-	-NA-
	➤ Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	> Jockey Pump output.	-NA-	-NA-	-NA-
	> Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	> Standby Pump head.	-NA-	-NA-	-NA-
	> Auto Starting / Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level			MD
	Discharge of pump.	450 Lpm	450 LPM X 2	MR
-	Head of pump.	40m	Provided	MR
	> Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.			NIA
A 60	Underground tank capacity.	-NA-	-NA-	-NA-
	> Draw-off connection.	-NA-	-NA-	-NA-
	> Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	<ul> <li>Overhead tank capacity.</li> </ul>	10,000Liter	Provided	MR
15.	Exit Signage.	Required	Provided	MR
	Provision of Lifts.			NIA
10.	Pressurization of lift shaft.	-NA-	-NA-	-NA
	<ul> <li>Pressurization of lift lobby.</li> </ul>	-NA-	-NA-	-NA
	• Communication in lift car.	-NA-	-NA-	-NA
	• Fireman's switch.	-NA-	-NA-	-NA
	Lift signage.	-NA-	-NA-	-NA
17	Standby Power Supply	-NA-	-NA-	-NA
17.	Refuge Area			,
18.	Total area	-NA-	-NA-	-NA
		-NA-	-NA-	-NA
	• Location	1 14 8		

19.	Fire Control Room.	X	NIA	-NA-
17.	1	-NA-	-NA-	
	Flow switch panel.	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA
	PA system panel.	-NA-	-NA-	-NA
	Battery backup.		-NA-	-NA
	Building floor plan.	-NA-		
20.	Special Fire Protection System for the	-NA-	-NA-	-NA
	D 4 tien of angoigh Dick if any		a checked / operated	1

The Fire protection systems provided in the premises were checked / operated at random and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety measures as required under the rule, it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules, 2010

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Mehmood Design: ADO (SJ)

Gost miscell 1571

A G-1 Jehr Pun up ten Signature Shease

A G-1 Jehr Pun up ten Signature Shease

A G-1 Jehr Pun up ten Signature Shease