GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/Assembly/SZ/2022/ 59

Dated:09/09/2022

FIRE SAFETY CERTIFICATE

Certified that Auditorium Building Situated at Inter University Accelerator Centre, Aruna Asaf Ali Marg, New Delhi 110067 comprised of Ground and First Floor was issued FSC by this department vide letter no. F6/DFS/MS/Assembly/SZ/2019/210 dated 28/01/2019. The premise was re-inspected by the officer concerned of this department on 02.02.2022 in the presence of Mr. Harshwardhan Singh and found deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building is fit for occupancy Group "D" Assembly Building (Auditorium 263 Seats)" with effect 69 / 2 /2022 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

Issued on .09/0.2/2022 at New Delhi by

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER (SZ) δ_{NA}

Copy to:-

- 1. Sh. Bishwambhar Datt (Senor Administrative Officer) Auditorium Building at Inter University Accelerator Centre, Aruna Asaf Ali Marg, New Delhi 110067.
- 2. The Executive Engg. (Bldg.), SDMC, Jal Vihar, Laipat Nagar, New Delhi-110024.

Conditions for the validity of fire safety certificate:

- 1. The owner/occupier shall occupy the auditorium only after issue of license by the Dy. Commissioner of concerned revenue District of NCT of Delhi as notified by revenue department, Govt. of NCT of Delhi vide Delhi Gazette notification dated 09/01/2015.
- 2. All the means of escape/entry/exit shall be kept free from any obstruction.
- 3. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 4. All the staff members must know the correct method of operation of firefighting system.
- 5. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on http://delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms
- 6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in **Form 'J'** [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

INSPECTION REPORT

1. Name & address of the building: Auditorium Building at Inter University Accelerator Center

Aruna Asif Ali Marg, New Delhi- 110070.

2. Type of Φccupancy : Group "D" Assembly Building [Auditorium 263 Seats]

3. Type of Case : Renewal

4. Comprised of : Ground & First Floor

5. Details of Previous NOC : F6/DFS/MS/Assembly/SZ/2019/210 dated 28/01/2019

6. Fire Safety directives letter No : F6/DFS/MS/BP/2000/2112 dated 17/11/2000

7. Date of inspection : 02/02/2022

8. Name of Inspecting Officer : Sh. Rajesh Kumar ADO (BCP)

 Name and designation of officers from the building side : Mr. Harshwardhan Singh

10. Year of Construction : 2018

Applicant's letter No. : IUAC/Admn./14/1192 dated 13/01/2022 Remarks Provided at site S. No. Minimum Standards on fire prevention Old NOC MR/NMR and fire safety U/R 33 Requirement 1. Access to building Provided MR Road width 9m Provided MR 5m Gate width Provided MR 6m Width of internal road 2. Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors 03 Provided MR 2 Nos Basements -NA--NA--NAb. Width of staircases Upper Floor 1.5m 1.6m, 1.6m & 0.94 m MR Basements -NA--NA--NAc. Protection of exits Fire check door Required Provided MR Pressurization -NA--NA--NAd. No. of continuous staircases to terrace Required 2 Nos MR Width of Corridor -NA--NA--NA-Door Size 1.9m, 1.92m, 1.7m 1.5m MR & 1.68 m Compartmentation 3. Provided Required MR Fire check door Provided Required MR Sealing of electrical shafts Provided Required MR Fire Rating of shaft door -NA--NA--NA-Water Curtain Required Provided MR Fire Dampers Smoke Management System 4. -NA--NA--NA-Basements 12 ACPH Provided MR Upper floors Fire Extinguishers 5. 10 No's Provided MR Total numbers ABC/W.CO₂/CO₂ 4/4/2 Types MR Required Provided IS marking MR First-Aid Hose Reels 6. Total numbers on each floor 02 Nos Provided MR 30m Length of hose reel hose Provided MR 5mm Nozzle diameter Provided MR Automatic fire detection and alarming system 7. Smoke & Heat Type of detectors Provided MR Required Location of Main Panel Ground Floor MR -NA-Location of Repeater Panel -NA--NA-

N/15

	Alternate source of power	Required	Provided All Floors	MR MR
	Hooters' Location	Required		MR
	MOEFA	Required	Provided	-NA-
	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System			27.4
	Basement	-NA-	-NA-	-NA-
	 Ground & Above Floors 	-NA-	-NA-	-NA-
	 Sprinkler above false ceiling 	-NA-	-NA-	-NA-
1.	Internal Hydrants			MR
	Size of riser/down-comer	100mm	Provided GF-4 No & FF-2 No	MR
	Number of hydrants per floor	2 Nos	GF-4 No & FF-2 No	MR
	Hose Box	2 Nos	GF-4 NO & FT-2 NO	IVIIX
	Yard Hydrants		O2 N - Drovided	-NA-
	Total number of hydrants	-NA-	02 Nos Provided 02 Nos Provided	-NA-
	Hose Box	-NA-	02 Nos Flovided	
	Pumping Arrangements			
	Ground Level	274	-NA-	-NA-
	Discharge of main Pump	-NA- -NA-	-NA-	-NA-
	➤ Head of Main pump	-NA- -NA-	-NA-	-NA-
	Number of main pumpsJockey Pump out put	-NA-	-NA-	-NA-
	Jockey Pump out putJockey pump head	-NA-	-NA-	-NA-
	Standby Pump out put	-NA-	-NA-	-NA-
	Standby Pump Head	-NA-	-NA-	-NA-
	Auto Starting/Manual Stopping	-NA-	-NA-	-NA-
	Terrace level			- 1 m
	 Terrace level Discharge of pump 	450 LPM	2 x 900 LPM	MR MR
	> Head of the pump	40m	Provided	MR
	➤ Power Supply	Required	Provided Provided	MR
	Auto Starting of pump	Required	Piovided	
4.	Captive Water Storage for fire fighting) TA
	Underground tank capacity	-NA-	-NA-	-NA-
	> Draw-off connection	-NA-	-NA-	
	Fire service inlet	Required	Provided	MR MR
	Access to tank	Required	Provided	MR
	Overhead Tank capacity	10,000 Lts.	Provided Provided	MR
5.	Exit Signage.	Required	Provided	IVIIX
	Provision of Lifts.			
ó.	Pressurization of Lift Shaft	-NA-	-NA-	-NA-
	Pressurization of Lift lobby	-NA-	-NA-	-NA-
	Pressurization of Lift lobby Lift Cor	-NA-	-NA-	-NA-
	Communication In lift Car	-NA-	-NA-	-NA-
	 Fireman's Grounding Switch 	-NA-	-NA-	-NA-
	Lift Signage	Required	Provided	MR
·	Standby power supply	Required		
	Refuge Area.			
3.		-NA-	-NA-	-NA-
	Total AreaLocation	-NA-	-NA-	-NA
).	Fire Control Room	NIA	-NA-	-NA
	Detector System Panel	-NA-	-NA-	-NA
	Flow Switch Panel	-NA-		-NA
	PA System Panel	-NA-	-NA-	
	Battery backup	-NA-	-NA-	-NA-
	Building Floor Plans	-NA-	-NA-	-NA

20. Special Fire Protection System for Protection of special Risks, if any:

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/Assembly/SZ/2019/210 dated 28/01/2019, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

DO (SD)

Liver

) (5))

ADD BC

grignatura Pl

As approved, F.T. tetter is proto for your

(14 Spor

Dy 16/152/

M.5, Ca