656

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2022/

Dated: 17/02/2022

FIRE SAFETY CERTIFICATE

Certified that the M/s Rama Deluxe Guest House located at 8488, Arya Nagar, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (Reception + 03 guest rooms), 1st floor to 3rd floor (07 guest rooms at each floor), and 4th floor (05 guest rooms + Pantry for staff), total 29 guest rooms owned occupied by M/s Rama Deluxe Guest House earlier granted **FSC** by this department No.F6/DFS/MS/GH/2018/NDZ/2672 dated 12/12/18. Now, the premises was re-inspected by the officer concerned of this department on 11/02/22 in the presence of Mr. Sohan (Manager) and found that the said guest house building having given an affidavit dated 18.12.2019 regarding not to use any floor above third floor, has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (Reception + 03 guest rooms), 1st floor to 3rd floor (07 guest rooms at each floor), total -24 guest rooms up to third floor only with effect from -12102 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued Delhi by.

(**Dr. S.K.Tomar**)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. The Commissioner, North MCD, Civic Centre, New Delhi: to ensure the occupancy as detailed above.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. 2021122729439 dated 27.12 21.
- The Manager, M/s Rama Deluxe Guest House at 8488, Arya Nagar, Pahar Ganj, Pahar Ganj, New Delhi.

Condition for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

MIN

INSPECTION REPORT

1. Name & address of the building M/S Rama Deluxe Guest House at 8488,

Arya Nagar, Pahar Ganj, Pahar Ganj, New Delhi. 2. Type of occupancy:-

Residential, Sub Division-A-1

Gr. + 04 Upper floors (total 24 Guest rooms) Ground floor (Reception + 03 guest rooms), 1st floor to 3rd floor (07 guest rooms at each floor), and 4th

floor (05 guest rooms + Pantry for staff) not in use

as per affidavit dated 18.12.2019

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2018/NDZ/2672 dated

12/12/18.

5. Fire safety directives No.-

N/A 6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter Nov

11/02/22

Sh. Ravinder Singh (ADO/CC)

Mr. Sohan (Manager)

2001

10.	Applicant's letter No:-	ID no. 2021	l122729439 dated 2	7.12 21 . Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	04 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arr				
	A. Number of staircases				
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	0.80 mtr.	1.20 Mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	N/A	N/A	N/A	
	staircase to terrace				
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	01 mtr.	01 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 a/c per hour	Natural/exhaust	MR	
5.	Fire Extinguishers				
	1) Total numbers	10 Nos.	10 Nos.		

M/22

	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
5.	First-Aid Hose Reel	required	TOVICC	IVI
0.	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &			1411
	1) Type of detectors CO type	Required	Provided	MR
	2) Location of main panel	Gr. floor	Provided	MR
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Gr. floor	Provided	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System		Trovided	1744
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	1771	1777	' '
11.	Internal Hydrants	1	8	
	1) Size of riser/down-comer	N/A	N/A	NA
	2) Number of hydrants per	N/A	N/A	NA
	floor			
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main	N/A	N/A	N/A
	pump	21/4	 NY/4	
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump	N/A	N/A	N/A
	output	N/A	N/A	N/A
	g) Stand by pump head	N/A N/A	N/A N/A	N/A N/A
	h) Auto starting/Manual	IN/A	IN/A	IV/A
	starting/Manual stopping			
	2) Terrace level			
		225 LPM	225 LPM	MR
	a) Discharge of pump b) Head of pump	25 mtr.	25 mtr.	MR
	,	Required	Provided	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of	Kequilea	Fiovided	IVIK
	pump			
	C 1' - TYI- Law Clawson for	Fire Fighting		
14.	Captive Water Storage for 1) Under ground tank	Fire Fighting N/A	N/A	N/A



	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 ltr.	2,500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	,		
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System Risk, if any:	N/A		

The fire protection systems provided in the guest house building were randomly

tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2018/NDZ/2672 dated 14/12/2018 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended up to third floor only.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

DØ/CD

spower, snipertup for Sypoling Please