0-20

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No. F.6/DFS/MS/School/2022/NDZ/170

Dated: 15/02/2022

FIRE SAFETY CERTIFICATE

Certified that the Motherhood Public School at B-43, Street No. 2, New Usmanpur Delhi-110053, comprised of ground plus three upper floors owned/occupied by Motherhood Public School was issued FSC vide letter no. F.6/DFS/MS/School/2018/NDZ/2354 dated 17/10/2018. The school building have complied with the fire prevention and fire safety requirements in accordance with circular No. F16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011 issued by Director of Education and verified by the officer concerned of this department on 07/12/2021 & 06/01/2022 in the presence of Sh. Vipul Tiwari, Manager and that the school building is fit for occupancy class "B" 'Educational Building' with effect from 15/22 PRES for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 & also conditions printed overleaf.

Issued on 15/02/2022 at New Delhi by

(Dr. S. K. Tomar) Dy. Chief Fire Officer

To.

The Principal,
Motherhood Public School,
B-43, Street No. 2,
New Usmanpur, Delhi-110053

Copy for information and necessary action, if any:-

- The Commissioner,
 EDMC, Headquarters,
 Udyog Sadan, Patparganj Industrial Area,
 New Delhi-110092
- 2. The Director of Education, EDMC, 19, Udyog Sadan, Patparganj Industrial Area, Delhi-110092

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities. This Fire Safety Certificate is valid only for permanent building structure as per plan.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land or activities, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

N/10

		SPECTION RI	EPORT				
 Name & address of the building Motherhood Public School, C-147, Street No.6, New Usmanpur, Delhi-110053 							
2. Building is comprised of : Ground plus three upper floors							
3. Type of Occupancy : Educational							
Lype of Case : Renewal Details of Previous NOC letter : F.6/DFS/MS/ 2018/ School/97							
(Fire Safety direction letter No						
7	. Date of Inspection						
8	. Name of the Inspecting officers						
()		r	gender Singi				
	from the building side		ıl Tiwari, Manager				
1	0. Year of Construction : 2017						
}	1. Applicant's email ID	: abc123copy@yahoo.com dated 08/10/2021					
Sr.	Minimum Standards on fire	NBC-IV	Provided at Site	Remarks			
No	prevention and fire safety U/R33	Requirement		MR/NMR			
)]	Access to building.						
	 Road width 	6 m	6 m.				
				MR(Accepted earlier) 01 length of hose			
	6.4	N/A	N/A	N/A			
	Gate widthWidth of internal road	N/A	N/A	N/A			
02	Number, Width, Type and Arrang	gament of Evita					
		gement of Exits	•				
	a. Number of Staircases						
	• Upper Floor	2 nos.	2 nos.	MR			
	Basement Width of Staircases	N/A	N/A	N/A			
	Upper Floor	1.50					
	- Оррег 1 тоог	1.50 m/ 0.75 m	1.51 m & 1.24 m	MR(accepted			
	 Basement 	N/A	N/A	earlier) N/A			
	c. Protection of exits	14/71	IN/A	IN/A			
	 Fire check door 	N/A	N/A	N/A			
	 Pressurization 	N/A	N/A	N/A			
	d. No. of continuous staircases	2 nos.	2 nos.	MR			
	to terrace						
	- Wide - CC - 11-						
	e. Width of Corridor	1.50 m	1.50 m	MR			
	f. Door Size	1.50 m	1.50 m 1 m	MR MR			
)3							
)3	f. Door Size Compartmentation.		1 m	MR			
03	f. Door SizeCompartmentation.Fire check door	1 m		MR N/A			
03	f. Door Size Compartmentation. • Fire check door	1 m	1 m	MR			
03	f. Door SizeCompartmentation.Fire check doorSealing of electrical	1 m N/A N/A	1 m N/A N/A	N/A N/A			
03	 f. Door Size Compartmentation. Fire check door Sealing of electrical shafts 	1 m N/A N/A N/A	1 m N/A N/A N/A	N/A N/A N/A			
03	 f. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door 	1 m N/A N/A N/A N/A	1 m N/A N/A N/A N/A	N/A N/A N/A N/A			
	 f. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain 	1 m N/A N/A N/A N/A	1 m N/A N/A N/A N/A	N/A N/A N/A N/A			
	 f. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers 	1 m N/A N/A N/A N/A	1 m N/A N/A N/A N/A	N/A N/A N/A N/A			
	f. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers Smoke Management System.	1 m N/A N/A N/A N/A N/A N/A	1 m N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A			
()4	f. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers Smoke Management System. Basement	1 m N/A N/A N/A N/A N/A N/A	1 m N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A			
()4	f. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers Smoke Management System. Basement Upper floor	1 m N/A N/A N/A N/A N/A N/A	1 m N/A N/A N/A N/A N/A N/A N/A N/	N/A N/A N/A N/A N/A N/A N/A N/A			
03	f. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers Smoke Management System. Basement Upper floor Fire Extinguishers.	1 m N/A N/A N/A N/A N/A N/A N/A	1 m N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A			

	• Latal mumbana 1 0	1					
	Total numbers on each floor	1 no.	1 no.	MR			
	• Length of hose reel hose	30 m	30 m	MR			
7	Nozzle diameter Automatic fire detection and alarming or	05 mm	05 mm	MR			
	Automatic fire detection and alarming system.						
	• Type of detectors	N/A	N/A	N/A			
	 Location of main panel 	N/A	N/A	N/A			
	 Location of repeater panel 	N/A	N/A	N/A			
	 Alternate source of power 	N/A	N/A	N/A			
	 Hooter's location 	N/A	N/A	N/A			
18	MOEFA	N/A	N/A	N/A			
10)	Public address System.	N/A	Provided	MR			
10	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	• Upper floor	N/A	N/A	N/A			
	Sprinkler above false	N/A	N/A	N/A			
	ceiling			13/17			
11	Internal Hydrants						
	Size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per	N/A	N/A	N/A N/A			
	floor	N/A	N/A	N/A			
	 Hose Box 		11/21	14/A			
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level	N/A	N/A	N/A			
	Discharge of main Pump	N/A	N/A	N/A			
	Head of Main Pump	N/A	N/A	N/A			
	 Number of main pumps 	N/A	N/A	N/A			
	 Jockey pump out put 	N/A	N/A	N/A			
	 Jockey pump head 	N/A	N/A	N/A			
	 Standby pump out put 	N/A	N/A	N/A			
	 Standby pump Head 	N/A	N/A	N/A			
	 Auto Starting /Manual 	N/A	N/A	N/A			
	stopping	N/A	N/A	N/A			
	 Pump House Access 						
	Terrace Level						
**	 Discharge of pump 	450 LPM	450 LPM	MR(accepte			
	 Head of the Pump 			earlier			
	Power supply	40 m	40 m	MR			
	 Auto Starting of pump 	Required	Provided	MR			
		Required	Provided	MR			
14	Captive Water Storage for Fire Fighting.	:					
	 Underground tank capacity 	N/A	N/A	N/A			
	 Draw-off connection 	N/A	N/A	N/A			
	 Fire service inlet 	N/A	N/A	N/A			
	 Access to tank 	N/A	N/A	N/A			
	 Overhead Tank capacity 	10,000 Ltrs.	10,000	MR			
15	Evit Siunous	D' - 1	Ltrs.) (D			
15	Exit Signage. Provision of Lifts.	Required	Provided	MR			
10	crovision of Luts.						
	 Pressurization of Lift Shaft 	N/A	N/A	N/A			
	1 1035th 12ation of Lift Shart		1	1 11/12			

17	Standby power supply	N/A	N/A	N/A		
18	Refuge Area.		•	2 1/12		
	Total area	N/A	N/A	21/4		
	• Location			N/A		
		N/A	N/A	N/A		
19	Fire Control Room					
	Detector system panel	N/A	N/A	N/A		
	 Flow switch panel 	N/A	N/A	N/A		
	 PA system panel 	N/A	N/A	N/A		
	 Battery backup 	N/A	N/A	N/A		
	 Building Floor Plans 	N/A	N/A	N/A		
20	Special Fire Protection systems for	N/A	N/A	N/A		
	protection of special Risks, if any:					

Keeping in view of the compliance of the minimum standards of fire prevention and ire safety measures required under the rules, it is recommended to renewal Fire Safety Certificate under rule 37 of Delhi Fire Service Rules, 2010.

Dy. CFO(NDZ) Pl. Apeax

ADO(stat) Epoken en 7/2/22 file is resubmitted after due corrections

PROCEYAN ET Letter es submitted for signalures please