GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No. F.6/DFS/MS/School/2022/NDZ//69

Dated: 15/02/2022

FIRE SAFETY CERTIFICATE

Certified that the Motherhood Public School at C-147, Street No. 6, New Usmanpur, Ist Pusta, Delhi-110053, comprised of ground plus three upper floors owned/occupied by Motherhood Public School was issued FSC vide letter no. F.6/DFS/MS/2018/School/97 dated 17/01/2018. The school building have complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and verified by the officer concerned of this department on 06/01/2022 & 12/01/2022 in the presence of Sh. Vipul Tiwari, Manager and that the school building is fit for occupancy class "B" 'Educational Building' with effect from Land for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 & also conditions printed overleaf.

Issued on 15/02/2022 at New Delhi by

(Dr. S. K. Tomar) Dy. Chief Fire Officer

To,

The Principal,
 Motherhood Public School,
 C-147, Street No. 6,
 New Usmanpur, Ist Pusta,
 Delhi-110053

Copy for information and necessary action, if any:-

- The Commissioner,
 EDMC, Headquarters,
 419, Udyog Sadan, Patparganj Industrial Area,
 New Delhi-110092
- The Dy. Director of Education, B-Block, Yamuna Vihar, Delhi-110053

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire
 equipments and method of smooth and speedy safe evacuation of occupants in case of
 emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities. This Fire Safety Certificate is valid only for permanent building structure as per plan.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land or activities, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

	INS	SPECTION R	EPORT				
1.	Name & address of the building	: Motherhood Public School, B-43, New					
2	D 3111	Usmanp	Usmanpur, Delhi-110053				
2. Building is comprised of : Ground plus three upper floors							
3.	Je o o o apanej	: Education	onal				
4.	The or ende	: Renewa	•				
5. Details of Previous NOC letter : F.6/DFS/MS/School/2018/NDZ/2354 dated- 17/10/2018							
6. Fire Safety direction letter No : F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011							
7.	. Date of Inspection		07/12/2021 & 06/01/2022 ADO Nagender Singh				
	. Name of the Inspecting officers						
	. Name and designation of Office						
,	from the building side		ol Timesi Managara				
1	0. Year of Construction	: Sh. Vipul Tiwari, Manager : 2005					
	1. Applicant's email ID		copy@yahoo.com dt- (09/10/2021			
Sr.	Minimum Standards on fire	Circular	Provided at Site	Remarks			
No	prevention and fire safety	Requirement	Flovided at Site	MR/NMR			
	U/R33	requirement		MICININ			
)1	Access to building.		L				
	Road width	6 m	6 m				
				MR(Accept earlier)			
				01 length of			
				hose			
	 Gate width 	N/A	N/A	N/A			
	 Width of internal road 	N/A	N/A	N/A			
)2	Number, Width, Type and Arrang	ement of Exits					
	a. Number of Staircases			T			
	Upper Floor	1 no.	2 nos.	MR			
	 Basement 	N/A	· N/A	N/A			
	b. Width of Staircases						
	Upper Floor	1.50 m/ 0.75 m	1.50 m & 1.30 m	MR			
	Basement	N/A	N/A	N/A			
	c. Protection of exitsFire check door	27/4	27/4	77/1			
	Pressurization	N/A N/A	N/A	N/A			
	d. No. of continuous staircases	1 no.	N/A 1 no.	N/A MR			
	to terrace	1 110.	i no.	WIIC			
	e. Width of Corridor	1.5 m	1.5 m	MR			
	f. Door Size	1 m	1 m	MR			
)3	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
	 Sealing of electrical 	N/A	N/A	N/A			
	shafts	N/A	N/A	N/A			
	 Fire rating of shaft door 	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
	Fire Dampers						
04	Smoke Management System.						
	Basement	N/A	N/A	N/A			
	Upper floor	N/A	N/A	N/A			
05	Fire Extinguishers.						
05	Fire Extinguishers. Total numbers	8 nos.	10 nos.	MR			

		NI						
	irst-aid-Hose Reels.							
	 Lotal numbers on each floor 	l no.	1 no.	MR				
	 Length of hose reel hose 	30 m	30 m	MR				
	Nozzle diameter	05 mm	05 mm	MR				
	Automatic fire detection and alarming							
			NI/A	N/A				
	 Type of detectors 	N/A	N/A	N/A				
	• 1 ocation of main panel	N/A	N/A					
	 Location of repeater panel 	N/A	N/A	N/A				
	 Alternate source of power 	N/A	N/A	N/A				
	 Hooter's location 	N/A	N/A	N/A				
	MOLEY	N/A	Provided	MR				
	Public address System.	N/A	Provided	MR				
	Automatic Sprinkler System.							
	• Basement	N/A	N/A	N/A				
	Upper floor	N/A	N/A	N/A				
	Sprinkler above false	N/A	N/A	N/A				
	ceiling	1 1/1 1						
1	Internal Hydrants							
		NT/A	100 mm	MR				
	Size of riser/down-comer	N/A		MR				
	Number of hydrants per	N/A	1 no.	MR				
	floor	N/A	1 no.	IVIIX				
	Hose Box							
1,7	Yard Hydrants.							
	 Total number of hydrants 	N/A	N/A	N/A				
	 Hose Box 	N/A	N/A	N/A				
13	Pumping Arrangements.							
		NI/A	N/A	N/A				
	- Ground Level	N/A	N/A N/A	N/A				
	 Discharge of main Pump 	N/A	N/A N/A	N/A				
	 Head of Main Pump 	N/A	N/A N/A	N/A				
	 Number of main pumps 	N/A N/A	N/A	N/A				
	 Jockey pump out put 	N/A N/A	N/A	N/A				
	 Jockey pump head 	N/A	N/A	N/A				
	 Standby pump out put 	N/A N/A	N/A	N/A				
	Standby pump Head	N/A	N/A	N/A				
	 Auto Starting /Manual 	N/A	N/A	N/A				
	stopping	14/71	14/11	1 1/11				
	Pump House Access							
	- Terrace Level	450 LPM	450 LPM	MR(accepte				
	 Discharge of pump 	450 LPM	430 LFWI	earlier)				
		40 m	40 m	MR				
	 Head of the Pump 	Required	Provided	MR				
	 Power supply 		Provided	MR				
	Auto Starting of pump	Required	Tiovided	IVIIX				
1.4.	Captive Water Storage for Fire							
	Fighting.	N T/A	NT/A	N/A				
	 Underground tank capacity 	N/A	N/A					
	 Draw-off connection 	N/A	N/A	N/A				
	 Fire service inlet 	N/A	N/A	N/A				
	 Access to tank 	N/A	N/A	N/A				
	 Overhead Tank capacity 	10,000 Ltrs.	10,000 Ltrs.	MR				
15	Exit Signage.	Required	Provided	MR				
16	Provision of Lifts.							
	Draganization of tie CL - C	N/A	N/A	N/A				
	Pressurization of Lift Shaft Pressurization of Lift Johny							
	Pressurization of Lift lobby Communication in lift com	N/A	N/A	N/A				
	 Communication in lift car Firemen's grounding switch 	N/A	N/A	N/A				
	Firemen's grounding switchLift Signage	N/A	N/A	N/A				
	" Lut Signage	N/A	N/A	N/A				

N/13

17	Standby power supply	N/A	N/A	N/A	
18	Refuge Area.				
	Total area	N/A	N/A	N/A	
	Location	N/A	N/A	N/A	
19	Fire Control Room				
	Detector system panel	N/A	N/A	N/A	
	 Flow switch panel PA system panel Battery backup 	N/A	N/A	N/A	
		N/A	N/A	N/A	
		N/A	N/A	N/A	
	Building Floor Plans	N/A	N/A	N/A	
20	Special Fire Protection systems for protection of special Risks, if any:	N/A	N/A	N/A	

Keeping in view of the compliance of the minimum standards of fire prevention and fire safety measures required under the NBC Part-IV, it is recommended to renewal Fire Safety Certificate under rule 37 of Delhi Fire Service Rules, 2010.

> (Nagender (Singh) ADO (Shahdara)

Dy. CFO (NDZ)

Recd on \$12/22

ADO(Shan) 1. The delay was due to COVID-19 restriction.

2. FT letter is placed for signatures plein

M.

8/2

MS