

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2022/ 84

Dated: 24/02/2022

FIRE SAFETY CERTIFICATE

Certified that the 54 Janpath, Connaught Place, New Delhi comprises of Basement + Ground + 03 Upper floor was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/2019/61 dated 08/01/19. Now, the premises was re-inspected by the officer concerned of this department on 17/02/22 in the presence of Mr. Amit Sangwan (Manager) and found that the said premises has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Offices/Mercantile as above B + Gr. + 03 Upper floor with effect from for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued $\frac{24/02/2012}{\text{at New Delhi by}}$.

(**Dr. S. K. Tomar**)

Dy. Chief Fire officer

Delhi Fire Service

Copy to:-

1. The Chief Architect, NDMC, Palika Kendra, New Delhi

2. The Manager,

John Tinson & Co. Pvt. Ltd.,

54, Janpath, Connaught Place, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. The use of basement shall be as per BBL concerned.

N. 121

INSPECTION REPORT

1. Name & address of the building

2. Type of occupancy:-

3. Type of case:-

4. Details of previous FSC:-

5. Fire safety directives No.-6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

54, Janpath, Connaught Place New Delhi.

Business /Mercantile Building

B + Gr. + 03 Upper floors,

Renewal

F6/DFS/MS /GH/2019/61 dated 08.01.2019

N/A

17/02/22

Sh. Ravinder Singh (ADO/CC) &

Sh. Rajinder Atwal (DO/CD)

Sh. Amit Sangwan (Manager)

Old Hearitage Building Nil dated 07/02/2022

S.No. Minimum Standards on fire Requirement/ Provided at site Remarks Prevention and fire safety Existing fire MR/NMR U/R 33 safety arrangements 1. Access to Building 1) Road width 09 mtr. 12 mtr. MR 2) Gate width N/A N/A MR 3)Width of internal road N/A N/A Number, Width Type & Arrangement of Exits N/A 2. A. Number of staircases 1. Upper floors 02 02 MR 2. Basements 02 02 MR B. Width of staircase 1. Upper floors 0.90 & 1.25 mtr. 0.90 mtr. & 1.25 MR mtr. 2. Basements 0.90 & 1.25 mtr. 0.90 mtr. & 1.25 MR mtr. C. Protection of exits 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous 01 01 01 staircase to terrace E. Width of corridor N/A N/A N/A F. Door size 1.25 mtr. 1.25 mtr. 3. MR Compartmentation 1) Fire check door N/A N/A N/A 2) Sealing of electrical shafts Required Provided MR 3) Fire rating of shaft door N/A N/A 4) Water curtain N/AN/A N/A N/A 5) Fire Dampers N/A N/A 4. Smoke Management System N/A 1) Basements Required Provided MR 2) Upper floors 12 a/c per hour N/A 5. Fire Extinguishers N/A 1) Total numbers 08 Nos. 08 Nos. MR Types ABC & CO2 ABC & CO2 3) ISI marking MR Required Provided 6. First-Aid Hose Reel MR 1) Total number of eachfloor Provided MR



| | 2) Length of hose reel hose | 30 mtr. | Provided | MR |
|-----|----------------------------------|------------------|-----------|-------|
| | 3) Nozzle diameter | 05 mm | Provided | MR |
| 7. | Automatic Fire Detection | | | |
| | 1) Type of detectors | N/A | N/A | N/A |
| | 2) Location of main panel | N/A | N/A | N/A |
| | 3) Location of repeater pane | | N/A | N/A |
| | 4) Alternate source of power | | N/A | N/A |
| | 5) Hooter's Location | N/A | N/A | N/A |
| 8. | MOEFA | Required | Provided | MR |
| 9. | Public Address System | N/A | N/A | N/A |
| 10. | Automatic Sprinkler System | m | | |
| | 1) Basement | Required | Provided | MR |
| | 2) Upper floors | N/A | N/A | N/A |
| | 3) Sprinkler above false | N/A | N/A | N/A |
| | ceiling | | | |
| 11. | Internal Hydrants | | | |
| | 1) Size of riser/down-comer | 100 mm | 100 mm | MR |
| | 2) Number of hydrants per | 01 | Provided | MR |
| | floor | | | |
| | 3) Hose box | 01 | Provided | MR |
| 12. | Yard Hydrants | | | |
| | 1) Total number of hydrants | N/A | N/A | N/A |
| | 2) Hose box | N/A | N/A | N/A |
| 13. | Pumping Arrangement | | | |
| | Ground level | N/A | N/A | N/A |
| | a) Discharge of main | N/A | N/A | N/A |
| | pump | | | |
| | b) Head of main pump | N/A | N/A | N/A |
| | c) Number of main pump | N/A | N/A | N/A |
| | d) Jockey pump out put | N/A | N/A | N/A |
| | e) Jockey pump head | N/A | N/A | N/A |
| | f) Stand by pump output | N/A | N/A | N/A |
| | g) Stand by pump head | N/A | N/A | N/A |
| | h) Auto starting/Manual | N/A | N/A | N/A |
| | stopping | | | 11.77 |
| | 2) Terrace level | | | |
| | a) Discharge of pump | 900 & 450 LPM | Provided | MR |
| | b) Head of pump | 30 mtr. | Provided | 100 |
| | c) Power supply | Required | | MR |
| | d) Auto starting of pump | Required | Provided | MR |
| 1. | Captive Water Storage for F | ire Fight: | Provided | MR |
| | 1) Under ground tank | N/A | NI/A | |
| | capacity | | N/A | N/A |
| | a) Draw-off connection | N/A | N/A | N/A |
| - | b) Fire service inlet | N/A | N/A | N/A |
| | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank | 2500 ltr. | 2500 ltr. | |
| | capacity | =, - | 2500 111. | MR |
| | Exit Signage. | Required | Provided |) (D) |
| | Provision of Lifts. | | TATOVICE | MR |

| | a) Pressurization of lift shaft | N/A | N/A | N/A |
|-----|---|----------|----------|-----|
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | Required | Provided | MR |
| | d) Fireman's switch | Required | Provided | MR |
| | e) Lift signage | Required | Provided | MR |
| 17. | Stand by Power Supply | N/A | N/A | N/A |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection Syst Risk, if any: ABC & Co2 | MR | | |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if approved, the FSC issued vide letter no. F6/MS/DFS/2019/61 dated 08/01/2019, may be renewed under rule 35 of the Delhi Fire Service rules 2010.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Sh. Rajinder Atwal Designation :- DO (CD)

Name :- Sh. Ravinder Singh Designation: ADO (CC)

As approved Fri pertup force propriet Jegge