46

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

No. F.6/DFS/MS/BNQT/2022/NDZ/

Dated: 28/02/2022

FIRE SAFETY CERTIFICATE

Certified that the G. D. Enterprises (Banquet Hall) at Shop No. 30, 31, 32 & 33, Ground Floor, Plot No. 9B and 9C, Cross River Mall, CBD Ground Shahdara, Delhi-110092 comprised of two basement, ground plus three upper floors (Banquet is running on ground floor only) owned/occupied by G. D. Enterprises have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of this department on 05/02/2022 in the presence of Sh. Rajesh Khanna, Manager and that the building is fit for occupancy Group 'D' "Assembly Building" for ground floor only with effect from [28] [02] [2022]. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 & also conditions printed overleaf.

Issued on 98 02 2022 at New Delhi by

Director

To,

Sh. Subhash Chander Dhingra, Shop No. 30, 31, 32 & 33, Ground Floor 9B and 9C, 3rd Floor, Cross River Mall, CBD Ground Shahdara, Delhi-110092

Copy for information and necessary action, if any:-

- The Commissioner, EDMC, Headquarters,
 419, Udyog Sadan, Patparganj Industrial Area, New Delhi-110092
- The Dy. Health Officer, EDMC, Health Department Shahdara (South) Zone, Karkardooma, Shahdara, Delhi

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities. This Fire Safety Certificate is valid only for permanent building structure as per plan.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. Basement shall not be used for any other purpose except as specified in UBBL/National Building Code.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building

: G. D. Enterprises, Shop No. 30, 31, 32 &

33, Ground Floor, Plot No. 9 B and 9 C, Cross River Mall, CBD Ground, Shahdara,

Delhi-110092

2. Building is comprised of

: 2B+G+3 (Banquet is running on ground

floor only)

3. Type of Occupancy

: Assembly (Banquet Hall)

4. Type of Case

: New Case

5. Details of Previous NOC letter

: Nil

6. Fire Safety direction letter No.

: NBC Part-IV

7. Date of Inspection

: 05/02/2022 & 08/02/2022 : ADO M. K. Sharma &

8. Name of the Inspecting officers

ADO Nagender Singh

9. Name and designation of Officer from the building side

IS marking

: Sh. Rajesh Khanna, Manager

10. Year of Construction

: 2006

MR

ISI marked

11. Applicant's letter No. : 2021071915447 dated 27/12/2022

Minimum Ctauda 1 Di						
	· ·		Remarks			
Prevention and Fire Safety U/R33	Requirement	Site	MR/NMR			
Access to Building						
Road width	06 m	24 m	MR			
Gate width	4.5 m	07 m	MR			
	06 m	06 m	MR			
Number, Width, Type and Arrangement of Exits						
a. Number of Staircases						
 Upper floor 	N/A	N/A	N/A			
 Basement 	N/A	N/A	N/A			
b. Width of Staircases						
Upper floor	N/A	N/A	N/A			
	N/A	N/A	N/A			
Fire check door	N/A	N/A	N/A			
		N/A	N/A			
	N/A	N/A	N/A			
e. Width of Corridor	N/A	N/A	N/A			
f Door Size	2 m & 1.5m	2.10 m, 1.10	MR			
1. Door Size		m & 1.90 m	WIIC			
g. No of doors	2 nos.	2 nos.	MR			
Compartmentation.						
Fire check door	N/A	N/A	N/A			
 Sealing of electrical shafts 	N/A	N/A	N/A			
 Fire rating of shaft door 	N/A	N/A	N/A			
Water curtain	N/A	N/A	N/A			
 Fire dampers 	N/A	N/A	N/A			
Smoke Management System.						
Basement	N/A	N/A	N/A			
 Upper floor 	Required	Provided	MR			
Fire Extinguishers						
Total numbers	04 nos.	08 nos.	MR			
• Types	ABC /CO ₂	ABC/ CO ₂	MR			
	 Gate width Width of internal road Number, Width, Type and Arrangeme a. Number of Staircases Upper floor Basement b. Width of Staircases Upper floor Basement c. Protection of Exits Fire check door Pressurization d. No. of Continuous Staircases to Terrace e. Width of Corridor f. Door Size g. No of doors Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire dampers Smoke Management System. Basement Upper floor Fire Extinguishers Total numbers 	Minimum Standards on Fire Prevention and Fire Safety U/R33 Access to Building • Road width • Gate width • Width of internal road Number, Width, Type and Arrangement of Exits a. Number of Staircases • Upper floor • Basement b. Width of Staircases • Upper floor • Basement C. Protection of Exits • Fire check door • Pressurization d. No. of Continuous Staircases to Terrace e. Width of Corridor f. Door Size g. No of doors Compartmentation. • Fire check door • Sealing of electrical shafts • Fire rating of shaft door • Water curtain • Fire dampers Smoke Management System. • Basement • Upper floor Required N/A N/A N/A N/A N/A N/A N/A N/	Prevention and Fire Safety U/R33 Requirement Site			

ISI marked

06	First-Aid-Hose Reels.							
	Total numbers on each floor	01 no.	Provided	MR				
	Length of hose reel hose	30 m	Provided	MR				
	 Nozzle diameter 	5 mm	Provided	MR				
07	Automatic Fire Detection and Alarming System. Common with Mall							
	Type of detectors	Heat &Smoke	Provided	MR				
	 Location of main panel 	Control room	Provided	MR				
	 Location of repeater panel 	Security room	Provided	MR				
	Alternate source of power	Battery & DG Set	Provided	MR				
	 Hooter's location 	Staircase	Provided	MR				
08	MOEFA	Required	Provided	MR				
09	Public Address System.	N/A	N/A	N/A				
10	Automatic Sprinkler System. Common With Mall							
	Basement	N/A	Provided	N/A				
	Ground floor	N/A	Provided	N/A				
	Sprinkler above false ceiling	N/A	Provided	N/A				
11	Internal Hydrants Common With Mall							
	Size of riser/down-comer	100 mm	Provided	MR				
	 Number of hydrants per floor 	01 no.	Provided	MR				
	Hose box	01 no.	Provided	MR				
12	Yard Hydrants.							
	Total number of hydrants	N/A	N/A	N/A				
	Hose box	N/A	N/A	N/A				
13	Pumping Arrangements. Common With Mall							
	➤ Ground Level							
	Discharge of main pump	2850 LPM	2850 LPM	MR				
	Head of main pump	60 m	60 m	MR				
	 Number of main pumps 	2 nos.	2 nos.	MR				
	 Jockey pump out put 	180 LPM X2	180 LPM X 2	MR				
	Jockey pump head	60 m	60 m	MR				
	Standby pump out put	2850 LPM	2850 LPM	MR				
	Standby pump head	60 m	60 m	MR				
	Auto starting /manual stopping	Required	Auto	MR				
	Pump house access	Required	Provided	MR				
	> Terrace Level							
	Discharge of pump	N/A	N/A	N/A				
	 Head of the pump 	N/A	N/A	N/A				
	 Power supply 	N/A	N/A	N/A				
	 Auto starting of pump 	N/A	N/A	N/A				
14	Captive Water Storage for Fire Fighting. Common With Mall							
	Underground tank capacity	N/A	2,00,000 Ltrs.	MR				
	Draw-off connection	N/A	Provided	MR				
	Fire service inlet	N/A	Provided	MR				
	Access to tank	N/A	Provided	MR				
		10,000 Ltrs.	50,000 Ltrs.	MR				
15	Overhead tank capacity Exit Signage.	10,000 Lifs.	30,000 Lus.	IVIIC				



16	Provision of Lifts. Common With Mall			Annual Annual Street		
	 Pressurization of lift shaft 	N/A	Provided	MR		
	 Pressurization of lift lobby 	N/A	Provided	MR		
	Communication in lift car	N/A	Provided	MR		
	 Firemen's grounding switch 	N/A	Provided	MR		
	Lift signage	N/A	Provided	MR		
17	Standby Power Supply	Provided for Main Building				
18	Refuge Area.					
	Total area	N/A	N/A	N/A		
	 Location 	N/A	N/A	N/A		
19	Fire Control Room Common With Mall					
	Detector system panel	N/A	Provided	MR		
	 Flow switch panel 	N/A	Provided	MR		
	 PA system panel 	N/A	Provided	MR		
	Battery backup	N/A	Provided	MR		
	Building floor plans	N/A	Provided	MR		
20	Special Fire Protection Systems for Protection of Special Risks, if Any:	N/A	Provided in all LT &HT panels	MR		

Keeping in view the compliance of the minimum standards on fire prevention and fire safety measures required under the NBC Part-IV, it is recommended to issue Fire Safety Certificate under rule 35 of Delhi Fire Rules, 2010.

(Nagender Singh) ADO (Shahdara)

(M. K. Sharma) ADO (Laxmi Nagar)

Dy. CFO (NDZ)

(x 16 17 17.

806 15/1/22 5/02/22

Sivertay My 19/02

21/2

ADO (1/25) FT letter to placed for signalues blear

RIGI