GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2022/19 5

Dated: 02/03/2021

FIRE SAFETY CERTIFICATE

Certified that the Hariday Dx. Guest House located at 3787-88, Gali Ram Nath Patwa, Dariba Pan, Pahar Ganj, New Delhi comprised of Ground + Mezzanine + 03 Upper floors, Ground floor (reception + 02 guest rooms + office), Mezzanine floor (03 guest rooms), 1st floor (06 guest rooms), 2nd & 3rd floor (05 guest rooms at each floor), total 21 guest rooms owned/occupied by Hariday Dx. was granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2019/124 dated 17/01/19. Now, the premises was re-inspected by the officer concerned of this department on 22/02/22 in the presence of Sh. Babu Lal (Manager) and found that the said guest house building having Ground floor (reception + 02 guest rooms + office), Mezzanine floor (03 guest rooms), 1st (05 guest room + 01 store room), 2nd floor (05 guest rooms at each level) and having given an affidavit dated 23.02.2022 regarding not to use any floor above second floor, has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (02 guest room+ reception + office), Mezzanine floor (03 guest room), 1st floor to 2nd floor (05 guest rooms at each floor), total 15 guest rooms up to second floor only with effect from 62/63/2022 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 02/03/2022 at New Delhi by.

(Dr. S.K.Tomar) Dy. Chief Fire Officer Delhi Fire Service

Ganj,

Copy to:-

1. The Commissioner, North MCD, Civic Centre, New Delhi: to ensure the occupancy as detailed above.

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID No. 2022013101415 dated 31.01.22.

3. The Manager, Hariday Dx. Guest House at 3787-88, Gali Ram Nath Patwa, Dariba Pan, Pahar New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

INSPECTION REPORT

Name & address of the building:- Hariday Dx. Guest House at 3787-88, Gali Ram Nath Patwa, Dariba Pan, Pahar Ganj,

New Delhi

Type of occupancy:- Residential, Sub Division-A-1

Gr. + Mez.+ 3 upper floor

Ground floor(reception = office = 02 guest room)
Mezzanine floor (03 guest room) , 1st floor(05 guest room = 01 store room) 2nd floor (05 guest rooms at each

floor) and 3rd (5 guest rooms) not in use as per Affidavit dated 23.02.2022.

3. Type of case:-

Renewal

4. Details of previous FSC:-

No. F6/DFS/MS/GH/NDZ/2019/124 dated

17/01/19.

5. Fire safety directives No.-

N/A

6. Date of inspection:-

22/02/22.

7. Name of the inspecting officer:-

Sh. Rayinder Singh (ADO/CC) Sh. Rajinder Atwal (DO/CD)

Name & designation of officer
 From the building side:-

Mr. Babu lal (Manager)

9. Year of construction:-

2009

10. Applicant's letter No:-

ID No. 2022013101415 dated 31.01.22.

				Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			
	1) Road width	N/A	03 mtr.	MR
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arra			
54146.53	A. Number of staircases	-		
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	1.25 mtr.	1.25 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits		45.6.00	1071
	Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A N/A	N/A	N/A
	D. No. of continuous staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	N/A	N/A	N/A
_	F. Door size	1 mtr.	1 mtr.	MR
3.	Compartmentation			MIX
	1) Fire check door	N/A	N/A	N/A
	Sealing of electrical shafts	N/A	N/A	N/A N/A
	3) Fire rating of shaft door	N/A	N/A	100000000000000000000000000000000000000
	4) Water curtain	N/A	N/A	N/A
-	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System		N/A	
	1) Basements	30 ACPH	N/A	NIA
	2) Upper floors	12 ACPH	Natural Ventilation/exh	N/A MR



N-16

			aust fan				
5.	Fire Extinguishers	1 (0)					
	1) Total numbers	12 Nos.		MR			
	2) Types	ABC & CO2		MR			
	3) ISI marking	Required	Provided	MR			
6.	First-Aid Hose Reel			100			
	1) Total number of eachfloor	01		MR			
	2) Length of hose reel hose	30 m		MR			
	3) Nozzle diameter	05 mm		MR			
7.	Automatic Fire Detection &		em	l v r			
	1) Type of detectors CO	Required	Provided	MR			
	Туре		D '1 1	NO			
	2) Location of main panel	Gr. floor		MR			
	3) Location of repeater panel	Required	J. Perinters and Company of the Comp	MR			
	4) Alternate source of power	Required		MR			
	5) Hooter's Location	Gr. floor		MR			
8.	MOEFA	N/A		N/A			
9.	Public Address System	N/A	N/A	N/A			
10.	Automatic Sprinkler System						
	1) Basement	N/A	N/A	N/A			
	2) Upper floors	N/A	N/A	N/A			
	3) Sprinkler above false	N/A	N/A	N/A			
	ceiling						
11.	Internal Hydrants						
	1) Size of riser/down-comer	N/A	N/A	N/A			
	2) Number of hydrants per	N/A	N/A	N/A			
	floor						
	3) Hose box	N/A	N/A	N/A			
12.	Yard Hydrants						
	1) Total number of hydrants	N/A	N/A	N/A			
	2) Hose box	N/A	N/A	N/A			
13.	Pumping Arrangement		Provided Provided Provided Provided Provided N/A				
	 Ground level 	N/A	N/A	N/A			
	a) Discharge of main	N/A		N/A			
	pump		10000000000	1.1			
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pump	N/A		N/A			
	d) Jockey pump out put	N/A		N/A			
	e) Jockey pump head	N/A		N/A			
	f) Stand by pump output	N/A		N/A			
	g) Stand by pump head	N/A					
	h) Auto starting/Manual	N/A		N/A			
	stopping	CT-St. CT-ST-ST-St	14/21	NA			
	2) Terrace level						
	a) Discharge of pump	450 LPM	450 I D) 4	1,1			
	b) Head of pump	30 mtr		MR			
	c) Power supply			MR			
	d) Auto starting of pump	Required		MR			
	Auto starting of pump	Required	Provided	MR			
4.	Captive Water Storage for F	ino Fight's					
	1) Under ground tank	N/A	NI/A				
	-) Chaci ground tank	14/14	N/A	N/A			



-	-	71	c		50	×
	U		_	ı		В
7	ď.			7	-4	Į.
		9	\subset	ı		

b) Flow switch pane c) PA system panel d) Battery backup e) Building floor pla Special Fire Protection	N/A N/A an N/A	N/A N/A N/A N/A	N/A N/A N/A N/A
c) PA system panel	N/A	N/A	N/A N/A
	N/A	N/A	N/A
b) Flow switch pane	A DESCRIPTION		
		2711	TAT/A
a) Detector system panel	N/A	N/A	N/A
Fire Control Room	N/A	N/A	N/A
Total area location	N/A	N/A	N/A
Refuge Area	N/A	N/A	N/A
Stand by Power Supply	Required		- TANK TO THE
e) Lift signage	N/A		N/A MR
	N/A		N/A
	n N/A		132
 b) Pressurization of lobby 			N/A N/A
shaft		#.#XXXXX	N/A
		NIVA	N/A
Exit Signage.	Required	Provided	172.5
capacity		1	MR
c) Access to tank			MR
b) Fire service inlet	N/A	1000	N/A
a) Draw-off connect	tion N/A		N/A N/A
	b) Fire service inlet c) Access to tank d) Over head tank capacity Exit Signage. Provision of Lifts. a) Pressurization of shaft b) Pressurization of lobby c) Communication i lift car d) Fireman's switch e) Lift signage Stand by Power Supply Refuge Area Total area location Fire Control Room a) Detector system panel	a) Draw-off connection b) Fire service inlet c) Access to tank d) Over head tank capacity Exit Signage. Provision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby c) Communication in lift car d) Fireman's switch e) Lift signage N/A Stand by Power Supply Required N/A Total area location N/A Pire Control Room N/A N/A N/A N/A N/A N/A N/A N/A	a) Draw-off connection b) Fire service inlet N/A N/A N/A b) Fire service inlet N/A N/A N/A c) Access to tank N/A N/A d) Over head tank 5,000 ltr. 5,000 ltr. capacity Required Provided Frovision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby c) Communication in lift car d) Fireman's switch N/A N/A e) Lift signage N/A N/A Stand by Power Supply Required Provided Refuge Area N/A N/A Total area location N/A N/A Fire Control Room N/A N/A a) Detector system panel

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/ DFS/ MS/ GH/ NDZ/2019/124 dated 17/01/19, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended up to third floor only.

Signature of the inspecting officer

Signature of the Inspecting Officer

Name: - Rajinder Atwal

Designation: - DO (CD)

Designation: ADO (CC)