GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI-HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2022/ [2]

Dated: 23 | 02 | 2022

FIRE SAFETY CERTIFICATE

Delhi- 110005 was granted FSC for building comprised of basement, ground plus three upper floors, using basement as hall/storage, ground floor as reception & 03 guest rooms, first & second floor each having 07 guest rooms respectively and third floor having 03 guest rooms & 04 rooms for personal use (total 20 guest rooms) and one staff room with pantry for staff in temporary shed on terrace, by this department vide letter No. F6/DFS/MS/GH/SZ/2018/1601 dated 11.07.2018. The premises was reinspected by the officer concerned of this department on 14.02.2022 in presence of Sh. Vivek Jain, Owner, and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential (guest house) for basement (incidental storage), ground floor reception and 03 guest rooms, first & second floor each having 07 guest rooms respectively and third floor having 03 guest rooms and 04 rooms for personal use (total 20 guest rooms only) with effect from 33 value for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on 33 02 2022 at New Delhi by.

(Sunil Chaudhary)

Dy. Chief Fire Officer (SZ)

Delhi Fire Service

Following Fire Safety Directives must be adhered to: -

- 1. No occupancy used above second floor & basement use for only storage purpose, shall be strictly adhered by Owner/Occupier.
- 2. All the means of escape shall be kept free of all type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 6. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 7. All comments / directions of licensing department shall always be permitted and followed.
- 8. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.de/higovt.nic.in
- 9. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six mort is prior to its expiry.

INSPECTION REPORT

1. Name & address of the building

: M/s. Hotel Metropolitan 13A/24, WEA, Karol Bagh,

New Delhi- 110005.

2. Type of Occupancy

: Lodging House

3. Building Composition

: Building comprised of basement, ground plus three upper

floors, using basement as incidental storage, ground floor as reception and 03 guest rooms, first & second floor each

having 07 guest rooms and third floor having 03 guest rooms and 04 rooms for personal use (20 guest rooms)

4. Type of Case

: Renewal

5. Details of previous NOC

: F6/DFS/MS/GH/SZ/2018/1601 dated 11.07.2018

6. Fire Safety directives letter No

: Nil

7. Date of inspection

: 14.02.2022

: Before 2004

8. Name of the Inspecting Officers

: P.V. Rathee, Assit. Divisional Officer (Shankar Road)

9. Name and designation of officers from the building side

: Sh. Vivek Jain, Owner

9. Year of Construction
10. Applicant's letter No.

Online application id 2022021001978 dated 12.02.2022

10.	App <mark>licant's letter No. : Or</mark>	nline application id	1 202202 1001978 da	ted 12.02.2022			
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Fire safety requirements as per FSC dt. 11.07.2018	Provided at site	Remarks MR/NMR			
1	Access to building						
	 Road width 	06 mts	Provided	MR			
	Gate width	4.5 rnts	Directly accessible	MR being old case			
	• Width of internal road	N/A	N/A	N/A			
2	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases	-		-			
	• Upper Floors	Old Case	01	MR being old case			
	Basements	Old Case	01	MR being old case			
	b. Width of staircases	-	-	-			
	• Upper Floors	Old case	1.20 mts	MR being old case			
	Basements	Old case	1.14 mts	MR being old case			
	c. Protection of exits	-	-	-			
		Required	Provided	MR			
	• Fire check door • Pressurization	N/A	N/A	N/A			
	e. No. of continuous staircases to terrace	01	10	MR			
	g. Width of Corridor	Old case	1.90 mts	MR			
	h. Door Size	Old case	0.88 mts	MR being old case			
3	Compartmentation.						
	Fire check door	Required	Provided	MR			
	Sealing of electrical shafts	Required	Sealed	MR			
	Fire Rating of shaft door	N/A	N'A	N/A			
	Water Curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
4	Smoke Management System.						
	Basements	30 a/c per hour	Exhaust fan provided	MR			
	• Upper floors	12 a/c per hour	Exhaust fan provided	MR			

		Night	The second secon	7
5	Fire Extinguishers	1.5	Provided	MR
	Total numbers	15 CO ₂ , ABC, WCO ₂	Provided	MR
	• Types	ISI marked	Provided	MR
	IS marking		and the second s	
6	First-Aid Hose Reels.	01	Provided	MR
	Total numbers on each floor	30 m	Provided	MR
	Length of hose reel hose	5 mm	Provided	MR
	Nozzle diameter			
7	Automatic fire detection and alarming	Carbon Monoxide	Provided	MR
	• Type of detectors	Required	Provided near reception	MR
	Location of Main Panel CR	N/A	N/A	N/A
	Location of Repeater Panel	Required	D.G. set 125 KVA	MR
	Alternate source of power	N/A	N/A	N/A
0	Hooters' Location	N/A	Provided	N/A
8	MOEFA Public Address System.	Required	Provided	MR
	Automatic Sprinkler System.			
10	Basement	N/A	Provided	N/A
	Upper Floor	N/A	N/A	N/A
	• Sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			
1	Size of riser/down-comer	N/A	N/A	N/A
	Number of hydrants per floor	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
12	Yard Hydrants.			
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
3	Pumping Arrangements.			
	Ground Level			
	Discharge of main Pump	N/A	N/A	N/A
	Head of Main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	D and mut	N/A	N/A	N/A
		N/A	N/A	N/A
	F =	N/A	N/A	N/A
	Standby Pump out put	N/A N/A	N/A	N/A
	Standby Pump Head			N/A
	Auto Starting/ Manual stopping		N/A	N/A
	Pump House Access	N/A	N/A	1N/M
	•			
	Terrace level	450 I PM	450 I PM	3.45
	 Terrace level Discharge of pump 	450 LPM	450 LPM	MR
	 Terrace level Discharge of pump Head of the pump 	450 LPM 40 mts	450 LPM 40 mts	MR
	 Terrace level Discharge of pump Head of the pump Power Supply 	450 LPM 40 mts Required	450 LPM 40 mts Provided	
	 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 	450 LPM 40 mts Required Required	450 LPM 40 mts	MR
4	 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting.	450 LPM 40 mts Required Required	450 LPM 40 mts Provided	MR MR
4	 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting. Underground tank capacity 	450 LPM 40 mts Required Required	450 LPM 40 mts Provided Provided N/A	MR MR
4	 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting. Underground tank capacity Draw-off connection 	450 LPM 40 mts Required Required N/A N/A	450 LPM 40 mts Provided Provided	MR MR MR
4	 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting. Underground tank capacity Draw-off connection Fire service inlet 	450 LPM 40 mts Required Required N/A N/A N/A	450 LPM 40 mts Provided Provided N/A	MR MR MR
4	 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting. Underground tank capacity Draw-off connection Fire service inlet Access to tank 	450 LPM 40 mts Required Required N/A N/A N/A N/A	450 LPM 40 mts Provided Provided N/A N/A Provided N/A	MR MR MR N/A
4	 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting. Underground tank capacity Draw-off connection Fire service inlet 	450 LPM 40 mts Required Required N/A N/A N/A	450 LPM 40 mts Provided Provided N/A N/A Provided	MR MR MR N/A N/A

N-29

D

		N-50	·				
,	Provision of Lifts.	the state of the s					
	 Pressurization of Lift Shaft 	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	Required	Provided	MR			
	Fireman's Grounding Switch	Required	Provided	MR			
	Lift Signage	Required	Provided	MR			
	Standby power supply	Required	Provided	MR			
	Re <mark>f</mark> uge Area.						
	Total Area	N/A	N/A	N/A			
	Location	N/A	N/A	N/A			
	Fire Control Room						
	Detector System Panel	N/A	N/A	N/A			
	Flow Switch Panel	N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
	Battery backup	Required	Provided	MR			
	Building Floor Plans	N/A	N/A	N/A			
)	Special Fire Protection Systems for	N/A	N/A	N/A			
	Protection of special Risks, if any:						

The fire protection systems provided in the building were checked at random and found satisfactory at the time of inspection.

Note:- The owner/occupier has given an undertaking (placed at C- 70) not to use any type of occupancy above 3rd floor and basement use for only storage purpose.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/SZ/2018/1601 dated 11.07.2018, renewal under Rule 37 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

MR

Signature of the Inspecting Officer P.V. Rathee

Asstt. Div. Officer (SRD)

WS 17/2/2022

D.0 (S.NS

A DOUBLE S.