GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6 DFS/MS/School/2022/SZ/ 233

Dated: 02/03/2022

FIRE SAFETY CERTIFICATE

Certified that Sarvodaya Kanya Vidyalaya, located at Sector -1, M.B Road, Pushp Vihar, New Delhi-110030 (ID -1923071) comprised of New Building Block, ground plus Three upper floors owned/occupied by The Directorate of Education, Govt. of NCT of Delhi have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by officer concern of this department on 19/02/2022 in the presence of Mrs. Veena Devi Sejwal (Principal) and that the premises is fit for occupancy class "Educational, Group-B" (School) as above with effect from 62/03/2022 for period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on $0^2/0^3/2022$ at New Delhi by

(ATVL GARG) DIRECTOR /DFS

Copy to: -

- 1. The Assistant Engineer (E) Edu. Maint. Sub-div-M1, PWD, Hauz Khas, New Delhi 110016.
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi- 110054

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. This certificate cannot be treated as regularization of unauthorized construction, if any.
- 5. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

0	
1	re

		INCDECT	TON DEBODE				
1	Nam	e & Address of the Building	Sanyadaya Kany	va Vidvalava Sector -	I. M.B Road,		
			Sarvodaya Kanya Vidyalaya, Sector -1, M.B Road, Pushp Vihar, New Delhi-110030 (ID -1923071)				
2	Туре	of Occupancy	Pushp Vinar, New Delin-170050 (ID 1922)				
3	Build	ing Comprised of	Educational, Group-B (School)				
4	rype	of Case	Blocks G + 3 Upper Floor				
5	Deta	s of Previous NOC	New Case				
6	Fire	afety Directives Letter No.	Nil Nil				
7	Date	of Inspection					
8	Nam	of the Inspecting Officers	18-02-2021				
9	Nam	& Designation of Officers	Sh. Rajesh Kumar ADO (BCP)				
	пощ	uie Duilding side	Mrs. Veena Devi Sejwal (Principal)				
10	Year	of construction	2019 10				
11 S. No	Appl	cant letter No.	2018-19				
		110.	54(SPS-School)PWD/Edu./Maint./Sub-Div/M-1-				
	Mini	Minimum standards on Fire Prevention UBBL-2016 Provided at Site					
	and]	ire Safety U/R 33	UBBL-2016	Provided at Site	Remarks MR/NMR		
1	Acce	ss to Building.	requirements		IVEROTATIVE		
	•	Road width	P : 1	0	MR		
		Gate width	Required	9 mtr	-NA-		
		Width of internal road	-NA-	-NA-			
2	Numi	oer width troe & ar	-NA-	-NA-	-NA-		
	a) N	per, width, type & arrangement of exits. umber of Staircase					
	1	Upper floors.		-	1.00		
		Basement floor.	02 Nos	03 Nos	MR		
	1		-NA-	-NA-	-NA-		
	b) V	vidth of Staircase					
		Upper floors	1.5 m	1.50 m each	MR		
		Basement floor	-NA-	-NA-	-NA-		
	c) P	rotection of exits					
	X	Fire check door	-NA-	-NA-	-NA-		
	>	Pressurization	-NA-	-NA-			
	47 /	o. of continuous staircase to terrace			-NA-		
			-NA-	-NA-	-NA-		
		idth of corridor	1.5 mtr	1.5 mtr	MR		
3	_	oor size	1.2 mtr	1.2 mtr	MR		
3	Com	partmentation.					
		Fire check door.	-NA-	- \\TA			
			-NA-	-NA-	-NA-		
		Sealing of electrical shafts.		-NA-	-NA-		
		Fire rating of shaft door.	-NA-	-NA-	-NA-		
	1	Water curtain		-NA-	-NA-		
4	G	Fire dampers.	-NA-	-NA-	-NA-		
4.	Smok	e Management system.					
4.	Smok	e Management system. Basement	-NA-	-NA-			
		e Management system. Basement Upper floors			-NA-		
4. 5.		e Management system. Basement Upper floors axtinguishers.	-NA- -NA-	-NA- -NA-	-NA-		
		e Management system. Basement Upper floors Extinguishers. Total numbers	-NA- -NA- 20no's	-NA-	-NA- -NA-		
		Basement system. Basement Upper floors ixtinguishers. Total numbers Types	-NA- -NA-	-NA- -NA- 32 Nos	-NA- -NA- -NA- MR		
		e Management system. Basement Upper floors Extinguishers. Total numbers	-NA- -NA- 20no's ABC / co2	-NA- -NA- 32 Nos ABC / Co2 Type	-NANANA- MR MR		
	Fire F	Basement system. Basement Upper floors Extinguishers. Total numbers Types ISI Marking	-NA- -NA- 20no's	-NA- -NA- 32 Nos	-NA- -NA- -NA- MR		
	Fire F	Basement system. Basement Upper floors ixtinguishers. Total numbers Types	-NA- -NA- 20no's ABC / co2	-NA- -NA- 32 Nos ABC / Co2 Type	-NA- -NA- -NA- MR MR		
5.	Fire F	Basement system. Basement Upper floors Extinguishers. Total numbers Types ISI Marking	-NA- -NA- 20no's ABC / co2	-NANA- 32 Nos ABC / Co2 Type Provided	-NANANA- MR MR MR		
5.	Fire F	e Management system. Basement Upper floors Extinguishers. Total numbers Types ISI Marking Aid Hose Reels. Total numbers on each floor.	-NANA- 20no's ABC / co2 ISI mark	-NANA- 32 Nos ABC / Co2 Type Provided 02 Nos Provided	-NANANA- MR MR MR		
5.	Fire F	Basement system. Basement Upper floors Extinguishers. Total numbers Types ISI Marking Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose.	-NANA- 20no's ABC / co2 ISI mark 02 at each 30 mm	-NANA- 32 Nos ABC / Co2 Type Provided 02 Nos Provided Provided	-NANANA- MR MR MR MR		
5.	Fire F	Basement system. Basement Upper floors Extinguishers. Total numbers Types ISI Marking Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter	-NANA- 20no's ABC / co2 ISI mark	-NANA- 32 Nos ABC / Co2 Type Provided 02 Nos Provided	-NANANA- MR MR MR		
5.	Fire F	Basement system. Basement Upper floors Extinguishers. Total numbers Types ISI Marking Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter atic fire detection & alarming system.	-NANA- 20no's ABC / co2 ISI mark 02 at each 30 mm 5 m	-NANA- 32 Nos ABC / Co2 Type Provided 02 Nos Provided Provided	-NANANA- MR MR MR MR		
5.	Fire F	Basement system. Basement Upper floors Extinguishers. Total numbers Types ISI Marking Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter atic fire detection & alarming system. Type of detectors	-NANA- 20no's ABC / co2 ISI mark 02 at each 30 mm 5 m	-NANA- 32 Nos ABC / Co2 Type Provided 02 Nos Provided Provided	-NANANA- MR MR MR MR MR		
5.	Fire F	Basement system. Basement Upper floors Extinguishers. Total numbers Types ISI Marking Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter atic fire detection & alarming system. Type of detectors Location of Main Panel	-NANA- 20no's ABC / co2 ISI mark 02 at each 30 mm 5 m	-NANA- 32 Nos ABC / Co2 Type Provided O2 Nos Provided Provided Provided	-NANANA- MR MR MR MR MR -NA-		
5.	Fire F	Basement system. Basement Upper floors axtinguishers. Total numbers Types ISI Marking Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter atic fire detection & alarming system. Type of detectors Location of Main Panel Location of Repeater Panel	-NANA- 20no's ABC / co2 ISI mark 02 at each 30 mm 5 m -NANANA-	-NANA- 32 Nos ABC / Co2 Type Provided 02 Nos Provided Provided Provided -NA-	-NANANA- MR MR MR MR MR -NANA-		
5.	Fire F	Basement system. Basement Upper floors Extinguishers. Total numbers Types ISI Marking Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter atic fire detection & alarming system. Type of detectors Location of Main Panel	-NANA- 20no's ABC / co2 ISI mark 02 at each 30 mm 5 m	-NANA- 32 Nos ABC / Co2 Type Provided 02 Nos Provided Provided Provided -NANA-	-NANANA- MR MR MR MR MR -NANANA-		
5.	Fire F	Basement system. Basement Upper floors axtinguishers. Total numbers Types ISI Marking Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter atic fire detection & alarming system. Type of detectors Location of Main Panel Location of Repeater Panel	-NANA- 20no's ABC / co2 ISI mark 02 at each 30 mm 5 m -NANANA-	-NANA- 32 Nos ABC / Co2 Type Provided O2 Nos Provided Provided Provided -NANANA-	-NANANA- MR MR MR MR MR -NA-		

			-NA-	-NA-
9.	Public Address System	-NA-	-NA-	
10.	Automatic Sprinkler System		-NA-	-NA-
	 Basement 	-NA-	-NA-	-NA-
	 Upper floors 	-NA-	Control of the Contro	-NA-
	 Sprinkler above false ceiling 	-NA-	-NA-	
11.	Internal Hydrants.			-NA-
	Size of Riser/Down-comer	-NA-	100 MM	-NA-
	Number of Hydrant per floor	-NA-	02	-NA-
	Hose box.	-NA-	02	
12.	Yard Hydrants.			-NA-
12.	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-IVA
13.			The state of the s	
13.	Pumping arrangements.			774
	Ground Level	-NA-	-NA-	-NA-
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.		-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.		-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	> Auto Starting / Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-1471	
	Terrace Level		Provided	MR
	Discharge of pump.	2 x 450 LPM		MR
	Head of pump.	40 m	Provided	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	IVIIC
14.	Captive water storage for fire fighting.		50000 Itm	-NA-
	 Underground tank capacity. 	-NA-	58800 ltr	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	> Fire Service Inlet.	-NA-	-NA-	-NA-
	> Access to tank.	-NA-	-NA-	MR
	 Overhead tank capacity. 	10,000 ltr	Provided	
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.) DIA
10.	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	 Pressurization of lift lobby. 	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
	Standby Power Supply	-NA-	-NA-	-NA-
17.				
18.	Refuge Area	-NA-	-NA-	-NA-
	Total area	-NA-	-NA-	-NA-
	 Location 	-1477-	1177	1421
19.	Fire Control Room.	274	NT A	37.4
	 Detector system panel. 	-NA-	-NA-	-NA-
	 Flow switch panel. 	-NA-	-NA-	-NA-
	PA system panel.	-NA-	-NA-	-NA-
	Battery backup.	-NA-	-NA-	-NA-
	Danci, Carrier.	-NA-	-NA-	-NA-
	Building floor plan.			
	 Building floor plan. 	-NA-	-NA-	-NA-
20.	 Building floor plan. Special Fire Protection System for the Protection of special Risk, if any. 		-NA-	-NA-

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in prevention and fire safety measures as required under the rules, it is recommended to issue Fire Safety Certificate under rule 35 (3) of the Delhi Fire Service Rules, 2010

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer
Name: Sh. Rajesh Kumar
Design: ADO (BCP)

DO (SD)

approved, FT- letter is pulp synatise of Director,