GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001

No. F.6/DFS/MS/2022/SZ/ 99

Dated : 07 /03 /2022

FIRE SAFETY CERTIFICATE

Certified that Head Quarter Building for Samajwadi Party at Plot No 1, Institutional Area, Vasant Vihar, New Delhi 110057 is comprised of Lower Basement, Upper Basement, Ground + Four Upper Floors was inspected by officers concerned of this department on 02/03/2022 in presence of Mr. Sunny Raman J.E (Bldg) and found that the said premises / building have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building is fit for occupancy class "Business Occupancy" as above with effect from 67/63/2022 for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .6.7/.6.3..../2022 at New Delhi by

(ATOL GARG) DIRECTOR (DFS

Copy to:

- 1. Mr. Ram Gopal Yadav, Head Quarter Building for Samajwadi Party at Plot No 1, Institutional Area, Vasant Vihar, New Delhi 110057
- 2. The Executive Engineer (Building), HQ South Delhi Municipal Corporation, 9th Floor Civic centre, Minto Road, New Delhi 110002. (Ref. Online ID No 10093339 dated 24/02/2022)

Conditions for the validity of the safety certificate:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 4. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 5. Basement shall be used strictly as per Building Bye Laws.
- 6. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1	Name & Address of the Building	TION REPOR Head Quarte	r Building for Samajwadi	Party at Plot N			
,	Name & Address of the Sanating	1, Institution	1, Institutional Area, Vasant Vihar, New Delhi 110				
2	Type of Occupancy		Business Occupancy				
3	Building Comprised of	Lower Base	Lower Basement, Upper Basement, Ground + Fo Upper Floors				
4	Type of Case	New Case	• •				
5	Details of Previous NOC	Nil					
6	Fire Safety Directives Letter No	F6/DFS/MS/2	F6/DFS/MS/2012/BP/2152 Dated 18/06/2012				
7	Date of Online Inspection	02/03/2022	02/03/2022				
8	Name of the Inspecting Officers	DO (South) &	DO (South) & ADO (BCP)				
9	Name & Designation of Officers from the						
	building side						
10	Year of construction	2012					
11	Online ID No	10093339 date	ed 24/02/2022				
. No	Minimum standards on Fire Prevention	UBBL-2016	Provided at Site	Remarks			
	and Fire Safety U/R 33	requirement		MR/NMR			
1	Access to Building.						
	Road width	Required	12 mtr	MR			
	Gate width	Required	06 mtr	MR			
	Width of internal road	Required	06 mtr	MR			
2	Number, width, type & arrangement of	exits					
	a. Number of Staircase						
	1. Upper floors	03 No's	03 Nos	MR			
	2. Basement floor	03 No's	04 Nos (1 for pump	MR			
	b. Width of Staircase		Room)				
	1. Upper floors	1.50 mtr each	1.50 m each	MR			
	2. Basement floor	1.50 mtr each	1.50 m x 3 & 1.25 mtr	MR			
	c. Protection of exits						
	Fire check door	Required	Provided	MR			
	2. Pressurization	Required	Provided	MR			
	d. No. of continuous staircase to terrace	Required 02	Provided	MR			
	e. Width of corridor	1.50 mtr	Provided	MR			
	f. Door size	1.50 mtr	Provided	MR			
3	Compartmentation.						
	Fire check door.	Required	Provided	MR			
	 Sealing of electrical shafts. 	Required	Provided	MR			
	Fire rating of shaft door.	Required	Provided	MR			
	Water curtain	Required	Provided	MR			
	Fire dampers.	Required	Provided	MR			
4.	Smoke Management system.			IVIIC			
	BasementUpper floors	12 ACPH	Mechanical provided	MR			
5.		12 ACPH	Exhaust fan provided	M/R			
"	Fire Extinguishers • Total numbers	40					
	• Types	40	Provided	MR			
- 1	ISI Marking	ABC / Co2	Provided	MR			
		ISI Marked	Provided	MR			
5.	First Aid Hose Reels.						
5.	First Aid Hose Reels. • Total numbers on each floor.	03 at each floor	Provided				
5.		03 at each floor 30 m	Provided Provided	MR MR			

8. M 9. P 10. A	Automatic Fire Detection & Alarming S Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooter's location MOEFA Public Address System Automatic Sprinkler System Basement Upper floors Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box.	NA NA NA NA NA NA NA Required Required Rouired NA 150 03 03	NA NA NA NA NA NA Provided Provided Provided Provided Provided Provided Provided Provided Provided Provided	NA NA NA NA NA NA NA MR MR MR MR
9. P 10. A 11. II 12. Y	Location of Main Panel Location of Repeater Panel Alternate source of power Hooter's location MOEFA Public Address System Automatic Sprinkler System Basement Upper floors Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box.	NA NA NA NA NA NA Required Required NA 150 03 03	NA NA NA NA NA NA Provided Provided Provided Provided Provided Provided	NA NA NA NA NA MR MR MR MR
9. P 10. A 11. II 12. Y	Location of Repeater Panel Alternate source of power Hooter's location MOEFA Public Address System Automatic Sprinkler System Basement Upper floors Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box.	NA NA NA NA NA Required Required NA 150 03 03	NA NA NA NA Provided Provided Provided Provided Provided Provided Provided	NA NA NA NA MR MR MR MR
9. P 10. A 11. II 12. Y	Alternate source of power Hooter's location MOEFA Public Address System Automatic Sprinkler System Basement Upper floors Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box.	NA NA NA Required Required NA 150 03 03	NA NA NA Provided Provided Provided NA Provided Provided	NA NA NA MR MR MR MR NA
9. P 10. A 11. II 12. Y	Hooter's location MOEFA Public Address System Automatic Sprinkler System Basement Upper floors Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box.	NA NA Required Required NA 150 03 03	NA NA Provided Provided Provided NA Provided Provided	NA NA MR MR MR MR NA
9. P 10. A 11. II 12. Y	Public Address System Automatic Sprinkler System Basement Upper floors Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box.	NA Required Required NA 150 03 03	NA Provided Provided Provided NA Provided Provided	MR MR NA MR
9. P 10. A 11. II 12. Y	Public Address System Automatic Sprinkler System Basement Upper floors Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box.	Required Required NA 150 03 03	Provided Provided NA Provided Provided Provided	MR MR MR NA
10. A 11. II 12. Y	Basement Upper floors Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box.	Required Required NA 150 03 03	Provided Provided NA Provided Provided	MR MR NA
11. II 12. Y	 Basement Upper floors Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box. 	Required NA 150 03 03	Provided NA Provided Provided	MR NA MR
12. Y	 Upper floors Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box. 	Required NA 150 03 03	Provided NA Provided Provided	MR NA MR
12. Y	Sprinkler above false ceiling Internal Hydrants. Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box.	Required NA 150 03 03	Provided NA Provided Provided	MR NA MR
12. Y	 Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box. 	NA 150 03 03	NA Provided Provided	NA MR
12. Y	 Size of Riser / Down-comer Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box. 	150 03 03	Provided Provided	MR
13. P	 Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box. 	03	Provided	
13. P	 Number of Hydrant per floor Hose box. Yard Hydrants. Total number of hydrants. Hose box. 	03	Provided	
13. P	 Hose box. Yard Hydrants. Total number of hydrants. Hose box. 	03		MK
13. P	Total number of hydrants.Hose box.		Provided) (D
13. P	Total number of hydrants.Hose box.	1		MR
	 Hose box. 	1 116	Provided	1.00
		06		MR
	Pumping arrangements.	06	Provided	MR
	Discharge of main pump	2280 LPM	2280 LPM	MR
	Discharge of main pump.Head of main pump.	· 70m	70m	MR
	Number of main pumps.	01	01	MR
	Jockey Pump output.	180 LPM	180 LPM	MR
	Jockey Pump head.	70 m	70 m	MR
	Standby Pump output.	2280 LPM	2280 LPM	MR
	Standby Pump head.	70 m	70 m	
1	Water certain pump	1620 LPM	1620 LPM	MR
- 1	Auto Starting / Manual Stopping.	Required	Provided	MR
	Pump House Access	Required	Provided	MR
•	Terrace Level	roquiou	Trovided	MR
	Discharge of pump.	NA	NA	NIA
	Head of pump.	NA	NA	NA NA
	Power supply.	NA	NA	NA NA
	> Auto starting of pump.	NA	NA	NA NA
14. C	Captive water storage for fire fighting.			IMA
•	Underground tank capacity. Draw-off connection.	1,00,000 ltrs	1,00,000 ltrs	MR
1	> Fire Service Inlet.	Required	Provided	MR
	Access to tank.	Required	Provided	MR
	Overhead tank capacity.	Required	Provided	MR
		10,000 Ltrs	10,000 ltrs	MR
15. E	xit Signage.	Required	Provided	
6. Pr	rovision of Lifts.			MR
	 Pressurization of lift shaft. 	Required	Provided	-
	 Pressurization of lift lobby. 	Required	Provided	MR
	 Communication in lift car. 	Required	Provided	MR
-	 Fireman's switch. 	Required		MR
	 Lift signage. 		Provided	MR
7 Sta	andby Power Supply	Required	Provided	MR
		Required	Provided	MR
	efuge Area			

NIN

19.	• Location Fire Control Room.	NA	NA	NA
	 Detector System Panel. Flow Switch Panel. PA system Panel. Battery backup Building floor plan 	Required	Provided	MR
		Required	Provided	MR
		Required	Provided	MR
20.		Required	Provided	MR
		Required	Provided	MR
	Special Fire Protection System for the Protection of special Risk, if any.	Required	Dry Transformer, LT & HT Panels provided	MR

The Fire protection systems provided in the building were test checked at random and found functional at the time of inspection.

Keeping in view of the substantially satisfactory compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, it is recommended to issue Fire Safety Certificate under rule 35 (3) of the Delhi Fire Service Rules, 2010

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Sh. S.K Dua

Designation: DO (South)

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar Designation: ADO (BCP)

Dy. CFO (8Z)

C. F.O. D. D.)

Director My 13/0082

AMBLO F.T. letteris put up for

WDirectal Hope