## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/School/2022/SZ/ 220

Dated: 28/02/2022

## **FIRE SAFETY CERTIFICATE**

Certified that **Tagore Vidya Niketan** Situated at **203**, **Village Rajpur Khurd**, **New Delhi 110068** comprised of Ground + Two Upper Floors, but School **running at ground and first floor only** owned/occupied by Tagore Vidya Niketan was issued FSC by this department vide letter No. F6/DFS/MS/School/2018/SZ/714 Dated 16-04-2018. The said premise was re-inspected by officer concerned of this department on 19/02/2022 in presence of Mr. Manoj Chaudhary (Principal) of the school and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and the building is fit for occupancy class "**Educational Building Group** – **B"** with effect from 2022 for a period of **Three years** in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued 28/02/2022 at New Delhi by

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER (SZ)

Copy to: -

1. Tagore Vidya Niketan Situated at 203, Village Rajpur Khurd, New Delhi 110068.

2. The Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054

## Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire safety arrangement provided therein shall be maintained in good working condition
  at all time as seen during inspection. Any loss of life property due to non-functional fire safety
  measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."



	INSPECTIO	N REPORT		60 1771	
i	Name & Address of the Building	Tagore Vidya !	Niketan Situated at 2	203, Villagi	
		Rajpur Khurd, New Delhi 110068  Educational, Group-B (School)			
2	Type of Occupancy				
3	Building Comprised of	Ground + 02 upper floors. (second floor totally tin shed &			
3	Building Comprises of	not in use)			
4	Type of Case	Renewal			
5	Details of Previous NOC	F6/MS/DFS/School/2018/SZ/714 Dated 16-04-2018			
6	Fire Safety Directives Letter No	Nil			
7	Date of Inspection	19/02/2021			
8	Name of the Inspecting Officers	Sh. Rajesh Kumar ADO (BCP)			
9	Name & Designation of Officers	Mr. Manoj Chaudhary (Principal)			
7	from the building side				
10	Year of construction	2006 School running at 2 <sup>nd</sup> & 3 <sup>rd</sup> Floor only			
11	Applicant letter No.	Gmail dated 27/01/2022			
No.	Minimum standards on Fire Prevention	Old NOC	Provided at Site	Remarks	
. No.	and Fire Safety U/R 33	requirements		MR/NMF	
1	Access to Building.			,	
1.	Road width	6 mtr	At distance of 2 length	MR	
			hose from road of 6 mir	214	
	Gate width	-NA-	-NA-	-NA-	
	<ul> <li>Width of internal road</li> </ul>	-NA-	-NA-	-NA-	
2.	Number, width, type & arrangement of ex	its.			
4.	a) Number of Staircase				
	> Upper floors.	02 Nos	02 Nos	MR	
	Basement floor.	-NA-	-NA-	-NA-	
	b) Width of Staircase				
		02 stair ways	0.70m & 0.75m	MR	
	<ul><li>Upper floors</li><li>Basement floor</li></ul>	-NA-	-NA-	-NA-	
	c) Protection of exits	1.7.2			
	Fire check door	-NA-	-NA-	-NA-	
	Pressurization	-NA-	-NA-	-NA-	
	d) No. of continuous staircase to terrace	Required	Provided	MR	
	e) Width of corridor	-NA-	-NA-	-NA-	
	f) Door size	-NA-	-NA-	-NA-	
2	Compartmentation.				
3.	Fire check door.	-NA-	-NA-	-NA-	
	C. L. C. L. deirel abotho	-NA-	-NA-	-NA-	
	<ul> <li>Sealing of electrical shalts.</li> <li>Fire rating of shaft door.</li> </ul>	-NA-	-NA-	-NA-	
	Water curtain	-NA-	-NA-	-NA-	
	Fire dampers.	-NA-	-NA-	-NA-	
	Smoke Management system.				
4.	Basement	30 ACPH	-NA-	-NA-	
		12 ACPH	-NA-	-NA-	
	Upper floors	12.1222			
5.		Required	04 Nos	MR	
	Total numbers		ABC & CO2	MR	
	• Types	ABC / CO2			
	ISI Marking	ISI marked	Provided	MR	
6.	First Aid Hose Reels.				
	Total numbers on each floor.	01	Provided	MR	
	<ul> <li>Length of hose-reel hose.</li> </ul>	30m	Provided	MR	
	Nozzle Diameter	5mm	Provided	MR	
	THE PROPERTY OF THE PROPERTY O	1		1	

	Town of later		NIA	-NA-
	<ul> <li>Type of detectors</li> <li>Location of Main Panel</li> </ul>	-NA-	-NA- -NA-	-NA-
		-NA-	-NA-	-NA-
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power	-NA-	-NA-	-NA-
	Hooter's location	-NA-		MR
	MOEFA	Required	Provided	-NA-
	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System		-NA-	-NA-
	Basement	-NA-	-NA-	-NA-
	<ul> <li>Upper floors</li> </ul>	-NA-		-NA-
	<ul> <li>Sprinkler above false ceiling</li> </ul>	-NA-	-NA-	-NA-
11.	Internal Hydrants.		NIA	-NA-
	<ul> <li>Size of Riser/Down-comer</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Number of Hydrant per floor</li> </ul>	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-INA-
12.	Yard Hydrants.			NIA
	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.			
	Ground Level			NT A
	Discharge of main pump.	-NA-	-NA-	-NA-
	➤ Head of main pump	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting/Manual Stopping	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level			MR
	Discharge of pump.	220 LPM	Provided	MR
	Head of pump.	40 m	Provided	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	IVIK
14.	Captive water storage for fire fighting.		N1.4	=NA=
	<ul> <li>Underground tank capacity.</li> </ul>	-NA-	"NA»	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	MR
	<ul> <li>Overhead tank capacity.</li> </ul>	2,500 Ltrs	Provided Provided	MR
	Exit Signage.	Required	Flovided	IVIIX
16.	Provision of Lifts.	-NA-	-NA-	-NA-
	<ul> <li>Pressurization of lift shaft.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Pressurization of lift lobby.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Communication in lift car.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Fireman's switch.</li> </ul>		-NA-	-NA-
	<ul> <li>Lift signage.</li> </ul>	-NA-		-NA-
17.	Standby Power Supply	-NA-	-NA-	-IN/A-
	Refuge Area	N/A	-NA-	-NA-
	Total area	-NA-		
	• Location	-NA-	-NA-	-NA-
-	Fire Control Room.			
19. F	Detector system panel.	-NA-	-NA-	-NA-

t eco

H.

3. 11.

rk

le li fi h

20.	Special Fire Protection System for the Protection of special Risk, if any.			-NA-
	<ul><li>Battery backup.</li><li>Building floor plan.</li></ul>	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	PA system panel.	-NA-	-NA-	-NA-
	<ul> <li>Flow switch panel.</li> </ul>	-NA-	-NA-	-NA-

The fire protection systems provided in the premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/DFS/MS/School/2018/SZ/714 Dated 16-04-2018, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

DO(SD)

AND (BLP)

As appoined, F.T. Letter in pritip for
your synature Pl.

Dy chelse